

GlusterFS

가상화WG


1. GlusterFS 개요
2. GlusterFS 구조
3. GlusterFS Volume Type
4. GlusterFS 서버 설치
5. GlusterFS Brick 생성
6. GlusterFS Distributed Vol 생성
7. GlusterFS Replicated Vol 생성
8. GlusterFS Distributed Replicated Vol 생성
9. GlusterFS 추가 명령어(Optional, Client)
10. GlusterFS 관리 모니터링 tool
11. 오픈스택 연동

1. GlusterFS 개요

GlusterFS란


- Redhat에서 지원하는 오픈소스 파일시스템
- 수천 Petabyte급의 대용량에 수천 개의 클라이언트가 접속하여 사용 가능
- scale-out 방식 분산 파일 시스템
- 기존의 분산 파일 시스템에 비해 비교적 구성이 간단
- 대용량 및 대규모의 I/O처리 능력이 뛰어남
- Client에서 native(FUSE), NFS, CIFS 방식으로 접근가능

Glusterfs 서버 집합
(Client의 가상 저장소)




2. GlusterFS 구조

서버 - 클라이언트 연동 구조




2. GlusterFS 구조

Node는 여러 개의 Brick을 구성할 수 있고 이 중 부분집합을 만들어 Volume을 구성하고 이 Volume이 Client에게 제공된다.






2. GlusterFS 구조




3. GlusterFS volume type

기본 type




복합 type

Distributed Replicated Volume



Distributed Striped Volume



4. GlusterFS 서버 설치

- glusterfs 패키지 설치

```
[root@system01 ~]# yum install -y centos-release-gluster → glusterfs 패키지 repository 설정
[root@system01 ~]# yum install -y glusterfs-server → 실제 glusterfs 패키지 설치
[root@system01 ~]# rpm -qa | grep gluster
glusterfs-3.7.1-16.0.1.el7.centos.x86_64
glusterfs-libs-3.7.1-16.0.1.el7.centos.x86_64
```

- 초기 환경 구성시 연동한 dev 2개 확인

```
[root@system01 ~]# fdisk -l | grep /dev
Disk /dev/sda: 32.2 GB, 32212254720 bytes, 62914560 sectors
/dev/sda1 *      2048    1026047    512000    83 Linux
/dev/sda2      1026048   62914559   30944256    8e Linux LVM
Disk /dev/sdb: 100 GB, 10737418240 bytes, 20971520 sectors
# lsblk
sdb                8:16  0   5G  0 disk
├─gv01-brickpool_tmeta 253:2  0   8M  0 lvm
│ └─gv01-brickpool-tpool 253:4  0   5G  0 lvm
│   ├─gv01-brickpool    253:5  0   5G  0 lvm
│   │ └─gv01-brick1      253:6  0  50G  0 lvm /brick1
│   └─gv01-brick2      253:7  0  50G  0 lvm /brick2
└─gv01-brickpool_tdata 253:3  0   5G  0 lvm
    └─gv01-brickpool-tpool 253:4  0   5G  0 lvm
        ├─gv01-brickpool    253:5  0   5G  0 lvm
        │ └─gv01-brick1      253:6  0  50G  0 lvm /brick1
        └─gv01-brick2      253:7  0  50G  0 lvm /brick2
```


4. GlusterFS 서버 설치

- `vi /etc/hosts` -> `hostname` 등록 (ssh로 접속가능 해야함)

```
[root@system01 ~]# cat /etc/hosts
127.0.0.1    localhost localhost.localdomain localhost4 localhost4.localdomain4
::1         localhost localhost.localdomain localhost6 localhost6.localdomain6
192.168.100.21 system01.example.com system01
192.168.100.22 system02.example.com system02
```

주의 : `systemctl stop firewalld.service`

- **노드간 연동 테스트**

```
[root@system1 ~]# gluster peer probe system2.example.com
peer probe: success.
[root@system1 ~]# gluster peer status
Number of Peers: 1

Hostname: system2.example.com
Uuid: 351418b0-6d8f-435f-a0d5-335f2ed1abaa
State: Peer in Cluster (Connected)
```

5. GlusterFS Brick 생성

(system1에서)

```
[root@system1 ~]# pvcreate /dev/sdb
Physical volume "/dev/sdb" successfully created
[root@system1 ~]# vgcreate vg0 /dev/sdb
Volume group "vg0" successfully created
[root@system1 ~]# lvcreate -l100%free -T vg0/brickspool
Logical volume "brickspool" created.
[root@system1 ~]# lvcreate -V 100M -T vg0/brickspool -n brick1
Logical volume "brick1" created.
[root@system1 ~]# lvcreate -V 100M -T vg0/brickspool -n brick2
Logical volume "brick2" created.
[root@system1 ~]# lvcreate -V 100M -T vg0/brickspool -n brick3
Logical volume "brick3" created.
[root@system1 ~]# lvcreate -V 100M -T vg0
/brickspool -n brick4
[root@system1 ~]# lvs
```

LV	VG	Attr	LSize	Pool	Origin	Data%	Meta%	Move	Log	Cpy%	Sync	Convert
root	centos	-wi-ao----	11.17g									
swap	centos	-wi-ao----	1.30g									
brick1	vg0	Vwi-a-tz--	100.00m	brickspool		0.00						
brick2	vg0	Vwi-a-tz--	100.00m	brickspool		0.00						
brick3	vg0	Vwi-a-tz--	100.00m	brickspool		0.00						
brick4	vg0	Vwi-a-tz--	100.00m	brickspool		0.00						
brickspool	vg0	twi-aotz--	1012.00m			0.00	1.27					

5. GlusterFS Brick 생성

(system1에서)

```
[root@system1 ~]# mkfs.xfs -i size=512 /dev/vg0/brick1
meta-data=/dev/vg0/brick1      isize=512    agcount=4, agsize=6384 blks
        =                       sectsz=512   attr=2,    projid32bit=1
        =                       crc=0        finobt=0
data      =                       bsize=4096   blocks=25536, imaxpct=25
        =                       sunit=16     swidth=16 blks
naming    =version 2           bsize=4096   ascii-ci=0 ftype=0
log        =internal log       bsize=4096   blocks=768, version=2
        =                       sectsz=512   sunit=16 blks, lazy-count=1
realtime  =none                extsz=4096   blocks=0, rtextents=0
```

```
[root@system1 ~]# mkdir -p /brick1
```

vi /etc/fstab 에 추가

/dev/vg0/brick1	/brick1	xfs	rw,noatime,inode64,nouuid	1 2
-----------------	---------	-----	---------------------------	-----

```
[root@system1 ~]# mount -a
```

```
[root@system1 ~]# df -h
```

Filesystem	Size	Used	Avail	Use%	Mounted on
/dev/mapper/centos-root	12G	4.7G	6.5G	42%	/
devtmpfs	474M	0	474M	0%	/dev
tmpfs	489M	144K	489M	1%	/dev/shm
tmpfs	489M	14M	476M	3%	/run
tmpfs	489M	0	489M	0%	/sys/fs/cgroup
/dev/sda1	497M	177M	321M	36%	/boot
tmpfs	98M	16K	98M	1%	/run/user/0
/dev/mapper/vg0-brick1	97M	5.2M	92M	6%	/brick1

5. GlusterFS Brick 생성

(system2에서)

```
[root@system2 ~]# pvcreate /dev/sdb
Physical volume "/dev/sdb" successfully created
[root@system2 ~]# vgcreate vg0 /dev/sdb
Volume group "vg0" successfully created
[root@system2 ~]# lvcreate -l100%free -T vg0/brickspool
Logical volume "brickspool" created.
[root@system2 ~]# lvcreate -V 100M -T vg0/brickspool -n brick5
Logical volume "brick5" created.
[root@system2 ~]# lvcreate -V 100M -T vg0/brickspool -n brick6
Logical volume "brick6" created.
[root@system2 ~]# lvcreate -V 100M -T vg0/brickspool -n brick7
Logical volume "brick7" created.
[root@system2 ~]# lvcreate -V 100M -T vg0/brickspool -n brick8
Logical volume "brick8" created.
[root@system2 ~]# lvs
```

LV	VG	Attr	LSize	Pool	Origin	Data%	Meta%	Move	Log	Cpy%	Sync	Convert
root	centos	-wi-ao----	11.17g									
swap	centos	-wi-ao----	1.30g									
brick5	vg0	Vwi-a-tz--	100.00m	brickspool		0.00						
brick6	vg0	Vwi-a-tz--	100.00m	brickspool		0.00						
brick7	vg0	Vwi-a-tz--	100.00m	brickspool		0.00						
brick8	vg0	Vwi-a-tz--	100.00m	brickspool		0.00						
brickspool	vg0	twi-aotz--	1012.00m			0.00	1.27					

5. GlusterFS Brick 생성

(system2에서)

```
[root@system2 ~]# mkfs.xfs -i size=512 /dev/vg0/brick5
meta-data=/dev/vg0/brick5      isize=512    agcount=4, agsize=6384 blks
        =                       sectsz=512   attr=2,    projid32bit=1
        =                       crc=0        finobt=0
data      =                       bsize=4096   blocks=25536, imaxpct=25
        =                       sunit=16     swidth=16 blks
naming    =version 2           bsize=4096   ascii-ci=0 ftype=0
log        =internal log      bsize=4096   blocks=768, version=2
        =                       sectsz=512   sunit=16 blks, lazy-count=1
realtime  =none                extsz=4096   blocks=0, rtextents=0
```

```
[root@system2 ~]# mkdir -p /brick5
```

```
[root@system2 ~]# vi /etc/fstab
```

/dev/vg0/brick1	/brick1	xfs	rw,noatime,inode64,nouuid	1 2
-----------------	---------	-----	---------------------------	-----

```
[root@system2 ~]# mount -a
```

```
[root@system2 ~]# df -h
```

Filesystem	Size	Used	Avail	Use%	Mounted on
/dev/mapper/centos-root	12G	4.7G	6.5G	42%	/
devtmpfs	474M	0	474M	0%	/dev
tmpfs	489M	144K	489M	1%	/dev/shm
tmpfs	489M	14M	476M	3%	/run
tmpfs	489M	0	489M	0%	/sys/fs/cgroup
/dev/sda1	497M	177M	321M	36%	/boot
tmpfs	98M	4.0K	98M	1%	/run/user/42
tmpfs	98M	16K	98M	1%	/run/user/0
/dev/mapper/vg0-brick5	97M	5.2M	92M	6%	/brick5

6. GlusterFS Distributed Vol 생성

(system1에서)

```
[root@system1 brick1]# gluster vol create dist  
system1.example.com:/brick1/brick  
system2.example.com:/brick5/brick
```

volume create: dist: success: please start the volume to access data

```
[root@system1 brick1]# gluster vol start dist
```

volume start: dist: success

```
[root@system1 brick1]# gluster vol info dist
```

Volume Name: dist

Type: Distribute

Volume ID: bcb947c3-ec2d-4ba9-9ebc-06eed78c22a4

Status: Started

Snapshot Count: 0

Number of Bricks: 2

Transport-type: tcp

Bricks:

Brick1: system1.example.com:/brick1/brick

Brick2: system2.example.com:/brick5/brick

Options Reconfigured:

transport.address-family: inet

performance.readdir-ahead: on

nfs.disable: on

7. GlusterFS Replicated Vol 생성

(system1에서)

```
[root@system1 brick1]# gluster vol create repl replica 2
```

```
system1.example.com:/brick2/brick
```

```
system2.example.com:/brick6/brick
```

```
volume create: repl: success: please start the volume to access data
```

```
[root@system1 brick1]# gluster vol start repl
```

```
volume start: repl: success
```

```
[root@system1 brick1]# gluster vol info repl
```

Volume Name: repl

Type: Replicate

Volume ID: e6d4035a-597d-4825-ab74-46cb6ca87110

Status: Started

Snapshot Count: 0

Number of Bricks: 1 x 2 = 2

Transport-type: tcp

Bricks:

Brick1: system1.example.com:/brick2/brick

Brick2: system2.example.com:/brick6/brick

Options Reconfigured:

transport.address-family: inet

performance.readdir-ahead: on

nfs.disable: on

8. GlusterFS Distributed Replicated Vol 생성

(system1에서)

```
[root@system1 brick1]# gluster vol3 create dist_repl replica 2
system1.example.com:/brick3/brick system2.example.com:/brick7/brick
system1.example.com:/brick4/brick system2.example.com:/brick8/brick
volume create: dist_repl: success: please start the volume to access data
[root@system1 brick1]# gluster vol start dist_repl
volume start: dist_repl: success
[root@system1 brick1]# gluster vol info dist_repl
```

Volume Name: dist_repl

Type: Distributed-Replicate

Volume ID: f72b5da7-14ad-4358-ad60-9c528c43788f

Status: Started

Snapshot Count: 0

Number of Bricks: $2 \times 2 = 4$

Transport-type: tcp

Bricks:

Brick1: system1.example.com:/brick3/brick

Brick2: system2.example.com:/brick7/brick

Brick3: system1.example.com:/brick4/brick

Brick4: system2.example.com:/brick8/brick

Options Reconfigured:

transport.address-family: inet

performance.readdir-ahead: on

nfs.disable: on

9. GlusterFS 추가 명령어(Optional, Client)

```
[root@system1 brick1]# gluster vol set repl nfs.disable on
```

```
volume set: success
```

```
[root@system1 brick1]# gluster vol info repl
```

```
Volume Name: repl
```

```
...
```

```
nfs.disable: on
```

```
[root@system1 brick1]# gluster vol reset repl nfs.disable
```

```
volume reset: success: reset volume successful
```

9. GlusterFS Client 구성

GlusterFS native client 방식

```
yum install glusterfs-fuse
mkdir /distvol
vi /etc/fstab
system1.example.com:/dist /distvol glusterfs _netdev 0 0
mount -a
touch /distvol/file{1..10}
```

서버에서 5개씩 분산되어 생성되는지 확인

```
ls -l /brick1/brick
ls -l /brick5/brick
```

GlusterFS NFS client 방식

```
yum install glusterfs-fuse
mkdir /replvol
vi /etc/fstab
system1.example.com:/repl /replvol nfs vers=3 0 0
mount -a
touch /replvol/file{1..10}
```

서버에서 10개가 복제되어 생성되는지 확인

```
ls -l /brick2/brick
ls -l /brick6/brick
```

9. GlusterFS Client 구성

GlusterFS CIFS client 방식

[system1]

```
systemctl start smb.service
useradd -s /sbin/nologin cifsuser
smbpasswd -a cifsuser <- 패스워드 2번 입력
mount system1.example.com:/dist_repl /mnt
chown :cifsuser /mnt
chmod 775 /mnt
umount /mnt
```


[client]

```
yum install glusterfs-fuse
yum install cifs-utils
mkdir /distreplvol
vi /etc/fstab
//system1.example.com:/gluster-dist_repl /distreplvol cifs user=cifsuser,password=redhat 0 0
mount -a
touch /distreplvol/file{1..10}
```

서버에서 10개가 분배되어 복제되어 생성되는지 확인

```
ls -l /brick3/brick
ls -l /brick4/brick
ls -l /brick7/brick
ls -l /brick8/brick
```

10. GlusterFS 관리 모니터링 tool



10. GlusterFS 관리 모니터링 tool

Nagios®

General

[Home](#)
[Documentation](#)

Current Status

[Tactical Overview](#)

[Map](#)

[Hosts](#)

[Services](#)

[Host Groups](#)

[Summary](#)

[Grid](#)

[Service Groups](#)

[Summary](#)

[Grid](#)

[Problems](#)

[Services](#)

[\(Unhandled\)](#)

[Hosts \(Unhandled\)](#)

[Network Outages](#)

Quick Search:

Reports

[Availability](#)

[Trends](#)

[Alerts](#)

[History](#)

[Summary](#)

[Histogram](#)

[Notifications](#)

[Event Log](#)

System

Current Network Status

Last Updated: Thu Jun 26 14:33:12 IST 2014

Updated every 90 seconds

Nagios® Core™ 3.5.1 - www.nagios.org

Logged in as *nagiosadmin*

[View History For all hosts](#)

[View Notifications For All Hosts](#)

[View Host Status Detail For All Hosts](#)

Host Status Totals

Up Down Unreachable Pending

2 0 0 0

All Problems All Types

0

2

Service Status Totals

Ok Warning Unknown Critical Pending

38 1 1 2 1

All Problems All Types

4


43

Service Status Details For All Hosts

Limit Results: 100

Host	Service	Status	Last Check	Duration	Attempt	Status Information
dhcp4	Brick - /bricks/V1-1	OK	06-26-2014 14:27:55	0d 23h 20m 44s	1/3	OK: Brick /bricks/V1-1 is up
	Brick - /bricks/V1-2	OK	06-26-2014 14:27:54	0d 23h 20m 46s	1/3	OK: Brick /bricks/V1-2 is up
	Brick - /bricks/V1-3	OK	06-26-2014 14:23:56	0d 23h 20m 45s	1/3	OK: Brick /bricks/V1-3 is up
	Brick - /bricks/V1-4	OK	06-26-2014 14:23:56	0d 23h 20m 42s	1/3	OK: Brick /bricks/V1-4 is up
	Brick - /bricks/V1-5	OK	06-26-2014 14:23:56	0d 23h 20m 41s	1/3	OK: Brick /bricks/V1-5 is up
	Brick - /bricks/V1-6	OK	06-26-2014 14:23:56	0d 23h 20m 43s	1/3	OK: Brick /bricks/V1-6 is up
	Brick - /bricks/V2-1	OK	06-26-2014 14:27:42	0d 23h 15m 30s	1/3	OK: Brick /bricks/V2-1 is up
	Brick - /bricks/V2-2	OK	06-26-2014 14:28:28	0d 1h 14m 44s	1/3	OK: Brick /bricks/V2-2 is up
	Brick - /bricks/V2-3	OK	06-26-2014 14:26:28	0d 23h 20m 39s	1/3	OK: Brick /bricks/V2-3 is up
	Brick - /bricks/V2-4	OK	06-26-2014 14:26:28	0d 23h 20m 36s	1/3	OK: Brick /bricks/V2-4 is up
	Brick - /bricks/V2-5	OK	06-26-2014 14:26:28	0d 23h 20m 37s	1/3	OK: Brick /bricks/V2-5 is up
	Brick - /bricks/V2-6	OK	06-26-2014 14:26:28	0d 23h 20m 35s	1/3	OK: Brick /bricks/V2-6 is up
	Brick Utilization - /bricks/V1-1	OK	06-26-2014 14:26:28	2d 4h 27m 30s	1/3	OK : 42.0% used (4.0GB out of 9.0GB)
	Brick Utilization - /bricks/V1-2	OK	06-26-2014 14:26:28	2d 4h 27m 30s	1/3	OK : 42.0% used (4.0GB out of 9.0GB)
	Brick Utilization - /bricks/V1-3	OK	06-26-2014 14:26:28	2d 4h 27m 30s	1/3	OK : 42.0% used (4.0GB out of 9.0GB)
	Brick Utilization - /bricks/V1-4	OK	06-26-2014 14:26:28	2d 4h 27m 30s	1/3	OK : 42.0% used (4.0GB out of 9.0GB)
	Brick Utilization - /bricks/V1-5	OK	06-26-2014 14:26:28	2d 4h 27m 30s	1/3	OK : 42.0% used (4.0GB out of 9.0GB)
	Brick Utilization - /bricks/V1-6	OK	06-26-2014 14:26:28	2d 4h 27m 30s	1/3	OK : 42.0% used (4.0GB out of 9.0GB)
	Brick Utilization - /bricks/V2-1	OK	06-26-2014 14:23:56	2d 4h 10m 44s	1/3	OK : 42.0% used (4.0GB out of 9.0GB)
	Brick Utilization - /bricks/V2-2	OK	06-26-2014 14:23:56	2d 4h 9m 19s	1/3	OK : 42.0% used (4.0GB out of 9.0GB)

11. 오픈스택 연동



■ Ocata 버전부터는 GlusterFS서버에 추가적인 option 설정필요(수강생은 참고)

```
# useradd cinder → uid, gid 확인
# gluster volume set VOL_NAME storage.owner-uid CINDER_UID
# gluster volume set VOL_NAME storage.owner-gid CINDER_GID
# gluster volume set VOL_NAME server.allow-insecure on
```

```
vi /etc/glusterfs/glusterd.vol 에서 아래옵션 추가 (모든 gluster 서버에서)
option rpc-auth-allow-insecure on
systemctl restart glusterd
```

```
gluster vol vol1 set readdir-ahead off
```

[실습] 11. 오픈스택 연동

- glusterfs 설치 `yum install -y glusterfs-fuse`
- cinder의 경우 backend로 LVM, GLUSTERFS 등 구성하여 사용가능
 - `/etc/cinder/cinder.conf`에 아래와 같이 설정

```
[defaults]
...
enabled_backends = lvm, glusterfs
...
[glusterfs]
nfs_shares_config=/etc/cinder/glusterfs
volume_driver=cinder.volume.drivers.nfs.NfsDriver
volume_backend_name=glusterfs
```

- `/etc/cinder/glusterfs`에 아래와 같이 설정후 소유자, 권한 수정

```
glusterfs1.example.com:/dist
```

HOST:/VOL_NAME

```
# chown root:cinder /etc/cinder/glusterfs
# chmod 0640 /etc/cinder/glusterfs
# systemctl restart openstack-cinder-api
# systemctl restart openstack-cinder-scheduler
# systemctl restart openstack-cinder-volume
#df -h시 gluster 볼륨이 자동마운트 됨
```

[실습] 11. 오픈스택 연동

- Backend로 잡아놓은 system cinder type 리스트로 등록하여 볼륨으로 사용할 수 있게 등록

```
[root@controller01 ~]# source keystone_admin
[root@controller01 ~(keystone_admin)]# cinder type-create glusterfs
...
[root@controller01 ~(keystone_admin)]# cinder type-key glusterfs set
volume_backend_name=glusterfs
[root@controller01 ~(keystone_admin)]# cinder type-list
```

ID	Name	Description	Is_Public
b70d196e-151c-42e1-bd0b-d52c90c21e3c	glusterfs	-	True
bdd055bc-30e8-4ae0-a936-c65031657f6a	iscsi	-	True
f6ca0d79-175b-4da1-8328-432bfc770808	nfs	-	True

```
[root@controller01 ~(keystone_admin)]# cinder create --name test --volume-
type glusterfs 1
```