EECS 498 · AASE · FALL 2026

Reaching the Computer: Shell, MCP and the Browser

LAB04 · OCT 12–13, 2026

Today's schedule

- **Part 1: the shell**
- **Part 2: MCP**
- **Part 3: the browser**
- **Part 4: prompt injection**
- **Questions, then the attendance form**

Slides only today: nothing to install and nothing to hand in.

Part 1: The shell


HOW IT RUNS · WHAT IT COSTS · WHAT IT CAN REACH

Short commands

PART 1 · THE SHELL

One command, end to end

The model only asks. The harness runs the command on your computer and sends back what it printed.



The same loop in every harness, from the big ones to a 100-line one.

The shell tool's inputs

The model writes more than the command: a description for you, and how long to wait.


```
{"name": "Bash",
 "input": {
   "command": "pytest -q",
   "description": "Run the test suite",
   "timeout": 120000
 }}
```

`command`	What to run
`description`	What you see when asked to approve
`timeout`	How long to wait, in ms
`run_in_background`	For commands that do not finish

Claude Code 2.1.293's Bash tool, captured Oct 7.

One tool call at a time


Normally each command is its own tool call. Every result goes back to the model before it picks the next command.



An illustrative example: shell() stands for the harness's shell tool.

Code mode: tools called from code


In code mode, the model's tool call is a program. The harness runs all of it, and one result comes back: whatever the program printed.



An illustrative example: shell() stands for the harness's shell tool, called from Python. Anthropic's “Code execution with MCP” (Nov 4, 2025) and Cloudflare's “Code Mode” (Sep 26, 2025) describe the same idea.

Code mode in the same lanes

The model is called once. The commands run while it waits, and only the printed result reaches its context.



The same illustrative example as the last two slides.

Long-running commands

PART 1 · THE SHELL

Commands that do not finish

From outside, a slow command and one that never ends look the same. The harness has to decide when to stop waiting.

Servers

`npm run dev`, `python -m taskrweb`

Watchers

`tsc --watch`, anything that reruns on save

Waiting for input

A password prompt, a pager, a yes or no

Just slow

A full build, a long test suite

Every harness needs an answer for all four.

Commands that wait for input


By default nobody is at the keyboard, so the harness keeps programs from stopping to ask.

The program wants	What the harness does
A pager (`git log`)	Sets `PAGER=cat`, so it prints and exits
Colors and progress bars	Sets `TERM=dumb` and `NO_COLOR=1`
An editor or a prompt (`git rebase -i`)	Tells the model not to run them

Codex 0.161 source: every command gets TERM=dumb, NO_COLOR=1 and PAGER=cat · Claude Code 2.1.293 Bash tool description: interactive flags are not supported.

A wait has a deadline


The harness waits up to 2 minutes. Then it stops waiting, but the command keeps running, and the harness tells the model when it ends.



Simplified from Claude Code 2.1.293's Bash tool (timeout 2 minutes by default, 10 at most), captured Oct 7, and its docs.

Starting in the background


When the model knows a command will not end, it says so up front. The harness answers at once with a task id.



Simplified from Claude Code 2.1.293's Bash tool (run_in_background), captured Oct 7.

Four ways into a running command

A running command has an output, an input, a port and a stop. The model reaches each one through the harness, by task id.




Simplified from Claude Code 2.1.293's Monitor and TaskStop and Codex 0.160.0's write_stdin, captured Oct 7.

Part 2: MCP

TOOLS THAT SOMEONE ELSE WROTE

What MCP is


MCP is how a harness gets more tools from other programs, and hands them to the model.



MCP, the Model Context Protocol, is an open standard (modelcontextprotocol.io), announced by Anthropic Nov 2024 and now under the Linux Foundation.

Without MCP, every harness writes its own


Codex, Claude Code and ChatGPT would each write their own GitHub code, and their own Slack code, and so on.



Four harnesses and four services: sixteen integrations, each written and kept up by a harness's makers.

With MCP, the service writes it once


GitHub writes one MCP server. Every harness that speaks MCP can use it.



Each harness speaks MCP once, each service writes one server: eight pieces instead of sixteen. The idea is borrowed from the Language Server Protocol.

MCP in two calls

The harness asks the server for its tools, then calls one. The model never talks to it.



The two calls are tools/list and tools/call in the MCP spec. Tool names from GitHub's MCP server; the call and its result are illustrative.

What a server tells the model


For each tool: a name, a description of when to use it, and the arguments it takes.

```
{"name": "list_issues",
 "description": "List issues in a GitHub repository with optional
                 filtering by labels, states, and custom fields.",
 "inputSchema": {"type": "object",
   "properties": {
     "owner": {"type": "string", "description": "The owner of the repository"},
     "repo":  {"type": "string", "description": "The name of the repository"},
     "state": {"type": "string", "description": "Filter by issue state (open, closed, all)"}},
   "required": ["owner", "repo"]},
 "annotations": {"readOnlyHint": true}}
```

list_issues from GitHub's MCP server source (github/github-mcp-server), trimmed to three of its seven arguments. The harness copies this into the model's tool list.

Where MCP servers run

A local server is a program the harness starts on your computer. A remote one runs on someone else's machines.



MCP specification, 2026-07-28 · modelcontextprotocol.io

How the harness sends a call

One line of JSON. A local server reads it from its input; a remote server gets it over HTTPS.

```
the harness writes:
{"jsonrpc": "2.0", "id": 3, "method": "tools/call",
 "params": {"name": "list_issues",
            "arguments": {"owner": "Aider-AI", "repo": "aider"}}}

the server answers:
{"jsonrpc": "2.0", "id": 3,
 "result": {"content": [{"type": "text", "text": "[{\"number\": 4521, …}]"}]}}
```

MCP specification: JSON-RPC 2.0, one message per line on a local server's stdin and stdout. Trimmed; the result is illustrative.

More than tool calls

A server can also handle login, share data, ask you questions, and add tools.

Login

Sign in once; the token stays in the server

Data

Files and records, not just tools

Questions

Asks you for something it is missing

Updates

New tools without a harness release

MCP specification: authorization (OAuth), resources, elicitation, and list-changed notifications.

An MCP server or a CLI

If the harness has a shell, a CLI the model already knows is usually cheaper.

`gh` through the shell

The model already knows it

Nothing added to each request

Needs a shell and your login

The GitHub MCP server

Typed arguments, described tools


Works where there is no shell

Handles your login itself

Playwright MCP's README now points coding tools at its CLI as “more token-efficient” · M. Zechner, Nov 2, 2025 · S. Willison on skills, Oct 16, 2025.

Loading tools on demand

MCP tools go into every request, like any tool. Send only names, and load the rest when needed.



Claude Code defers MCP tools by default. Anthropic measured about 77K tokens of definitions dropping to 8.7K (advanced tool use, Nov 24, 2025).


Part 3: The browser

PAGES, PIXELS AND TREES

Three ways to see a page

A screenshot shows the layout, the tree names what can be clicked, the DOM holds everything.

Pixels: a screenshot



The accessibility tree

```
- navigation "Main" [ref=e7]:
  - list [ref=e8]:
    - listitem [ref=e9]:
      - link "Installation" [ref=e13]
```

The DOM, through JavaScript

```
() => [...document.querySelectorAll('nav a')]
  .slice(1, 5).map(a => a.getAttribute('href'))
// ["/docs/install/optional.html", …]
```


Captured Oct 7 · Playwright MCP 0.0.83 on aider.chat/docs: browser_take_screenshot, browser_snapshot, browser_evaluate.

A click by reference

The model clicks a name from the tree, not a pixel, and the reply says what it clicked.

```
browser_click {"element": "Installation link",
               "target": "e13"}
```

```
// Ran Playwright code
await page
  .getByRole('navigation', { name: 'Main' })
  .getByRole('link', { name: 'Installation' })
  .click();
```



Captured Oct 7 · Playwright MCP 0.0.83: the snapshot, the call and the reply. Computer use clicks by screen coordinates instead.

Browser tools, side by side

Claude in Chrome works like Playwright: the same three views, and clicks by reference.

	Playwright MCP	Chrome DevTools MCP	Claude in Chrome
Screenshot	`browser_take_screenshot`	`take_screenshot`	`computer` screenshot
The tree	`browser_snapshot`	`take_snapshot`	`read_page`
The DOM	`browser_evaluate`	`evaluate_script`	`javascript_tool`
Click	`browser_click` by ref	`click` by uid	`computer` by ref or x, y
Open a page	`browser_navigate`	`navigate_page`	`navigate`

Playwright MCP 0.0.83 tools/list, Oct 7 · Chrome DevTools MCP tool reference · Claude in Chrome's tool definitions as Claude Code receives them over MCP, Oct 8.

One page, two costs

On this page the tree cost almost six times the screenshot. Which works better depends on the page.

1,196

tokens for the 1280 × 720 screenshot


6,802

tokens for the same page's tree, 523 lines

Screenshot: Anthropic's 28 × 28 pixel patches. Tree: o200k tokenizer. WebVoyager (ACL 2024): on Booking and Google Flights, screenshots beat the tree by 41 and 52 points.

Three ways into a browser

Each step out reaches more of you: a fresh browser, your logged-in Chrome, your whole screen.



Playwright MCP README · Chrome DevTools MCP (Google, Sep 2025) · Vibium (J. Huggins) · Claude in Chrome docs · Anthropic computer use docs.

Part 4: Prompt injection

WHEN WHAT THE MODEL READS GIVES ORDERS

What prompt injection is

Prompt injection is text the model reads that it *follows as if you wrote it*.

Through the shell

A README or a file in a repo you cloned

Through MCP

A tool's description, or an issue it fetches


Through the browser

Hidden text on any page it visits

The model receives your request and everything its tools return as one stream of text. Nothing in that stream marks which words are yours.

A server's words in your prompt


A tool description is an instruction to your model. Install a server like code that runs as you.



After Invariant Labs, "Tool Poisoning Attacks," Apr 1, 2025. The MCP spec: tool descriptions are untrusted unless the server is trusted.

The lethal trifecta

Private data, untrusted content and a way to send data out, in one harness, is how data gets stolen.



Simon Willison, “The lethal trifecta for AI agents,” Jun 16, 2025.

The trifecta in each channel

Each channel can supply all three legs on its own. Cut one leg and the attack fails.

	private data	untrusted content	a way out
shell	~/.ssh · .env	a README it reads	curl · git push
MCP	your private repos	an issue anyone files	a public pull request
browser	your logged-in sessions	every page it reads	any form it submits

The MCP row happened: Invariant Labs, May 26, 2025. An issue on a public repo led a harness with GitHub's MCP server to copy private repo data into a public pull request.

Questions?