

Assert-Driven Parametric Design for FDM-Printed Replacement Parts: A Formatting Demonstration

Jay Cho¹

¹*Independent maker (this document is a formatting demonstration for the arxiv-pdf skill, not a real preprint)*

August 2026

Abstract. Consumer fused-deposition-modeling (FDM) printers make one-off replacement parts practical, but the dominant failure mode is not printing, it is specification: parts fail at install time because a dimension was measured once, trusted, and wrong. We describe a code-as-CAD workflow in which every part is a parametric program, every physical constraint is an executable assertion, and every exported mesh passes a validation battery before a slicer ever sees it. Constraints such as printer build volume, child-safety opening limits, and motion-envelope clearances are encoded as asserts that fail at build time rather than at install time. We illustrate the workflow with dimension-sourcing rules, a containment-probe validation scheme, and a tolerance-bracketing test-print protocol. This document is a worked example for a Markdown-to-arXiv-PDF conversion skill; the methods are real, the paper framing is illustrative.

1 Introduction

A replacement part has a harder specification problem than an original design: the geometry it must match already exists, is often undocumented, and was manufactured to tolerances unknown to the person holding the calipers. The workflow described here treats that uncertainty as the central design input.

The core rule is that no dimension is drawn; every dimension is a named constant, and everything else derives from it. When a caliper reading is revised after a test fit, the revision is a one-line change and a re-run, not a remodel.

1.1 Constraints as assertions

Physical constraints are encoded as executable assertions evaluated at mesh-generation time. A bed-size constraint takes the form

$$\max(W_{\text{part}}, D_{\text{part}}) \leq B - 2m,$$

where B is the printable bed dimension and m is a margin reserved for brims and skirts. A child-safety constraint on opening width g is simply $g \leq 5$ mm, asserted over every generated aperture. A violated constraint fails the build loudly; a printed part cannot violate it quietly.

1.2 Rotated-footprint analysis

A recurring question is whether a part wider than the bed can be printed diagonally. For a part of length L and width W rotated by angle θ , the bounding width is

$$W_{\text{bb}}(\theta) = L \cos \theta + W \sin \theta,$$

which is minimized at $\theta = 0$ for wide parts. Rotation rescues long thin parts only; for wide parts the design must change instead. Encoding this as a check prevents a class of optimistic slicing attempts.

2 Validation battery

Every exported mesh passes four checks before slicing, summarized in Table 1.

Check	Method	Catches
Watertightness	manifold analysis of the exported mesh	non-manifold booleans
Containment truth table	12 to 17 point probes per part	inverted or missing volumes
Envelope assert	bounding box vs. printer limits	bed and height violations
Orientation render	image of what touches the bed	flipped exports

The fourth check exists because the first three share the part’s own coordinate transforms: a wrongly rotated export once passed every containment probe, since the probes were derived from the same wrong transform. Only rendering “what touches the bed” made the error visible. Validation derived from intent validates the intent, not the artifact.

3 Tolerance bracketing

Where a mating dimension is uncertain, the workflow prints a bracket: a small matrix of test rings or tabs spanning the plausible range in fixed increments, printed overnight, test-fitted in the morning. The surviving increment becomes a named constant with a comment recording the date and the mating part. This is cheaper than precision measurement and more honest than optimism.

4 Conclusion

Treating parts as programs moves failure from install time to build time, where it costs seconds. The asserts, probes, and brackets described here are not sophisticated; their value is that they run every time, which is precisely what manual checking does not do.

This document demonstrates the arxiv-pdf skill’s output format: YAML frontmatter to a titled, numbered, single-column preprint with display mathematics and tables. It is not a submitted or planned publication.