

Introduction

This report outlines and analyses an implementation of a parallel algorithm for the following problem: Given a grid, where each square has a positive integer as its cost, find the shortest 8 connected path from the top left most square to the bottom right most square, where the distance of a path is defined as the sum of costs of all squares on the path.

The algorithm I've devised is a modified version of the delta stepping algorithm from Mayer and Sanders [1], described in the following pseudocode:

Note that $\text{COST}(x, y)$ returns the cost of the cell on x_{th} row and y_{th} . Furthermore, while the cost takes a long time to calculate for the first time. This function caches the cost in a 2D array so subsequence call returns instantly. This has the additional effect of calculating the cost of each cell upfront in a parallel fashion during the `find_delta` procedure. Not only does this allow delta to be calculated at the optimal value. It also allows the load of calculating the cost of each cell to be spread evenly among all processors, taking advantage of parallelization for the most expensive part of the algorithm. Furthermore, to ensure that relaxed and removed can be queried in constant time as well as being made emptied in constant time, I implemented them as 2D int arrays where (x, y) is in the set if $\text{set}[x][y] = \text{true-value}$. Here true value is an int. By incrementing true-value by 1 we can empty the set very quickly.

Methodology

To confirm and measure the performance of my algorithm, I've

Experiments

Discussion

Conclusion

References

- [1] U. Meyer and P. Sanders, " Δ -stepping: A parallelizable shortest path algorithm," *Journal of Algorithms*, vol. 49, no. 1, pp. 114–152, 1998, 1998 European Symposium on Algorithms, ISSN: 0196-6774. DOI: [https://doi.org/10.1016/S0196-6774\(03\)00076-2](https://doi.org/10.1016/S0196-6774(03)00076-2). [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0196677403000762>.

```

1:  $x_{end} \leftarrow x_{size} - 1$ 
2:  $y_{end} \leftarrow y_{size} - 1$ 
3:  $\delta \leftarrow \text{FINDDELTA}()$ 
4: for  $x \leftarrow 0$  to  $x_{end}$  do in parallel
5:   for  $y \leftarrow 0$  to  $y_{end}$  do in parallel
6:      $\text{distance}[x][y] \leftarrow \infty$ 
7:      $\text{bmap}[x][y] \leftarrow -1$   $\triangleright$  bmap map (x, y) to the which b[i] set they're in, hence speeding up the
        process.
8:   end for
9: end for
10:  $\text{distance}[0][0] \leftarrow \text{COST}(0, 0)$ 
11:  $\text{INSERT}(0, 0)$ 
12:  $i_{dest} \leftarrow \infty$ 
13:  $\text{removed} \leftarrow \emptyset$ 
14:  $\text{relaxed} \leftarrow \emptyset$ 
15:  $i \leftarrow 0$ 
16: while  $i < i_{dest}$  do
17:   while  $\text{b}[i]$  is not empty do
18:      $\text{RELAX}(\text{b}[i], \text{relaxed}, \text{removed})$ 
19:      $\text{b}[i] \leftarrow \emptyset$ 
20:     for each  $(x, y) \in \text{relaxed}$  do in parallel
21:        $\text{INSERT}(x, y)$ 
22:       if  $x_{end} = x \wedge y_{end} = y$  then
23:          $i_{dest} \leftarrow i$ 
24:       end if
25:     end for
26:   end while
27:    $\text{relaxed} \leftarrow \emptyset$ 
28:    $\text{removed} \leftarrow \emptyset$ 
29: end while

30:  $x \leftarrow x_{end}$ 
31:  $y \leftarrow y_{end}$ 
32:  $\text{path} \leftarrow []$ 
33: while  $x \neq 0 \wedge y \neq 0$  do
34:    $x_{pred} \leftarrow x$ 
35:    $y_{pred} \leftarrow y$ 
36:   for  $dx \leftarrow -1, 0, 1$  do
37:     for  $dy \leftarrow -1, 0, 1$  do
38:        $x_{new} \leftarrow x + dx$ 
39:        $y_{new} \leftarrow y + dy$ 
40:       if  $(x_{new}, y_{new})$  is valid coordinate  $\wedge (x_{new}, y_{new}) \neq (x, y)$  then
41:         if  $\text{distance}[x_{new}][y_{new}] < \text{distance}[x_{pred}][y_{pred}]$  then
42:            $x_{pred} \leftarrow x_{new}$ 
43:            $y_{pred} \leftarrow y_{new}$ 
44:         end if
45:       end if
46:     end for
47:   end for
48:    $\text{pathprepend}(x_{pred}, y_{pred})$ 
49: end while
50: return path

```

\triangleright Reconstruct the path from distance.

```

1: function FINDDELTA( )
2:   for  $x \leftarrow 0$  to  $x_{end}$  do in parallel
3:     for  $y \leftarrow 0$  to  $y_{end}$  do in parallel
4:        $cost_{max} \leftarrow \text{MAX}(cost_{max}, \text{COST}(x, y))$ 
5:     end for
6:   end for
7:   return  $cost_{max}/8$ 
8: end function
9: function REMOVE( $x, y$ )
10:  if  $bmap[x][y] \neq -1$  then
11:     $b[bmap[x][y]] \leftarrow b[bmap[x][y]] \setminus (x, y)$ 
12:  end if
13: end function
14: function INSERT( $x, y$ )
15:   $i \leftarrow \lfloor distance[x][y]/delta \rfloor$ 
16:   $bmap[x][y] \leftarrow i$ 
17:   $b[i] \leftarrow b[i] \cup (x, y)$ 
18: end function
19: function RELAX( $to\text{-}relax, relaxed, removed$ ) ▷ pass NULL as removed will cause the
   function to only Relax heavy edges. Pass a set as removed will cause the function to call REMOVE
   for each coordinate in  $to\text{-}relax$  and add them to  $removed$ .
20:  for each  $(x, y) \in to\text{-}relax$  do in parallel
21:    if  $removed \neq NULL$  then
22:      REMOVE( $x, y$ )
23:       $removed \leftarrow removed \cap (x, y)$ 
24:    end if
25:    for  $dx \leftarrow -1, 0, 1$  do
26:      for  $dy \leftarrow -1, 0, 1$  do
27:         $x_{next} \leftarrow x + dx$ 
28:         $y_{next} \leftarrow y + dy$ 
29:        if  $(x_{next}, y_{next})$  is valid coordinate  $\wedge (x_{next}, y_{next}) \neq (x, y)$  then
30:          if  $(\text{COST}(x_{next}, y_{next}) \leq delta) \oplus (removed = NULL)$  then ▷ If removed is null,
            only relax heavy edges, otherwise only relax light edges.
31:             $distance_{new} \leftarrow distance[x][y] + \text{COST}(x_{next}, y_{next})$ 
32:            if  $distance_{new} < distance[x_{next}][y_{next}]$  then
33:               $distance[x_{next}][y_{next}] \leftarrow distance_{new}$ 
34:               $relaxed \leftarrow relaxed \cap (x_{next}, y_{next})$ 
35:            end if
36:          end if
37:        end if
38:      end for
39:    end for
40:  end for
41: end function

```
