

Tab 1

1. Add GitLab Helm repo

```
helm repo add gitlab https://charts.gitlab.io/  
helm repo update
```

2. Create namespace

```
kubectl create namespace gitlab
```

3. Create values file (recommended)

```
vi gitlab-values.yaml
```

Minimal working config:

```
global:  
  hosts:  
    domain: example.com  
    https: false  
  
ingress:  
  configureCertmanager: false  
  
nginx-ingress:  
  controller:  
    service:  
      type: NodePort  
gitlab-runner:  
  install: false
```

4. Install GitLab

```
helm install gitlab gitlab/gitlab \  
-n gitlab \  
-f gitlab-values.yaml
```

5. Upgrade (after changes)

```
helm upgrade gitlab gitlab/gitlab \  
-n gitlab \  
-f gitlab-values.yaml
```

6. Uninstall GitLab

```
helm uninstall gitlab -n gitlab
```

7. Delete namespace (full cleanup)

```
kubectl delete namespace gitlab
```

8. Check status

```
helm list -n gitlab
```

```
kubectl get pods -n gitlab
```

```
kubectl get svc -n gitlab
```

9. Get NodePort (access UI)

```
kubectl get svc -n gitlab | grep nginx
```

Example output:

80:31866

Access:

<http://gitlab.example.com:31866>

10. Get root password

```
kubectl get secret gitlab-gitlab-initial-root-password \
```

```
-n gitlab \
```

```
-o jsonpath="{.data.password}" | base64 --decode ; echo
```

11. Exec into toolbox

```
kubectl exec -it -n gitlab deploy/gitlab-toolbox -- bash
```


Tab 2

