


Minimum Cut Problem

Flow network.


- Abstraction for substance **flowing** through the edges.
- $G = (V, E)$ = directed graph, no parallel edges.
- Two distinguished nodes: s = source, t = target.
- $c(e)$ = capacity of edge e .



Cuts

Def. An **s-t cut** is a partition (A, B) of V with $s \in A$ and $t \in B$.

Def. The **capacity** of a cut (A, B) is: $cap(A, B) = \sum_{e \text{ out of } A} c(e)$




Flows

Def. An **s-t flow** is a function that satisfies:

- For each $e \in E$: $0 \leq f(e) \leq c(e)$ (capacity)
- For each $v \in V - \{s, t\}$: $\sum_{e \text{ in to } v} f(e) = \sum_{e \text{ out of } v} f(e)$ (conservation)


Def. The **value** of a flow f is: $v(f) = \sum_{e \text{ out of } s} f(e)$.



Flows and Cuts

Flow value lemma. Let f be any flow, and let (A, B) be any s - t cut. Then, the net flow sent across the cut is equal to the amount leaving s .

$$\sum_{e \text{ out of } A} f(e) - \sum_{e \text{ in to } A} f(e) = v(f)$$



Flows and Cuts

Flow value lemma. Let f be any flow, and let (A, B) be any s - t cut. Then

$$\sum_{e \text{ out of } A} f(e) - \sum_{e \text{ in to } A} f(e) = v(f).$$

Pf.

$$v(f) = \sum_{e \text{ out of } s} f(e)$$


$$\begin{array}{l} \text{by flow conservation, all terms} \\ \text{except } v = s \text{ are } 0 \end{array} \quad \rightarrow \quad = \sum_{v \in A} \left(\sum_{e \text{ out of } v} f(e) - \sum_{e \text{ in to } v} f(e) \right)$$

$$= \sum_{e \text{ out of } A} f(e) - \sum_{e \text{ in to } A} f(e).$$

Flows and Cuts

Weak duality. Let f be any flow, and let (A, B) be any s - t cut. Then the value of the flow is at most the capacity of the cut.

Cut capacity = 30 \Rightarrow Flow value \leq 30




Flows and Cuts

Weak duality. Let f be any flow. Then, for any s - t cut (A, B) we have $v(f) \leq \text{cap}(A, B)$.

Pf.

$$\begin{aligned} v(f) &= \sum_{e \text{ out of } A} f(e) - \sum_{e \text{ in to } A} f(e) \\ &\leq \sum_{e \text{ out of } A} f(e) \\ &\leq \sum_{e \text{ out of } A} c(e) \\ &= \text{cap}(A, B) \quad \blacksquare \end{aligned}$$




Certificate of Optimality

Corollary. Let f be any flow, and let (A, B) be any cut. If $v(f) = \text{cap}(A, B)$, then f is a max flow and (A, B) is a min cut.

Value of flow = 28

Cut capacity = 28 \Rightarrow Flow value ≤ 28





Towards a Max Flow Algorithm

Greedy algorithm.

- Start with $f(e) = 0$ for all edge $e \in E$.
- Find an s-t path P where each edge has $f(e) < c(e)$.
- Augment flow along path P .
- Repeat until you get **stuck**.


↙ locally optimality \neq global optimality



Residual Graph

Original edge: $e = (u, v) \in E$.


- Flow $f(e)$, capacity $c(e)$.



Residual edge.

- "Undo" flow sent.
- $e = (u, v)$ and $e^R = (v, u)$.
- Residual capacity:

$$c_f(e) = \begin{cases} c(e) - f(e) & \text{if } e \in E \\ f(e^R) & \text{if } e^R \in E \end{cases}$$




Residual graph: $G_f = (V, E_f)$.

- Residual edges with positive residual capacity.
- $E_f = \{e : f(e) < c(e)\} \cup \{e^R : f(e) > 0\}$.


Ford-Fulkerson Algorithm

G :




Flow value = 18

G_f :




Ford-Fulkerson Algorithm

G :




Flow value = 19

G_f :




Ford-Fulkerson Algorithm



Cut capacity = 19

Flow value = 19



Augmenting Path Algorithm

```
Augment(f, c, P) {  
    b ← bottleneck(P, c, f)  
    foreach e ∈ P {  
        if (e ∈ E) f(e) ← f(e) + b  
        else      f(eR) ← f(eR) - b  
    }  
    return f  
}
```

min residual capacity of edge on P

forward edge

reverse edge

```
Ford-Fulkerson(G, s, t, c) {  
    foreach e ∈ E f(e) ← 0  
    Gf ← residual graph  
  
    while (there exists augmenting path P in Gf) {  
        f ← Augment(f, c, P)  
        update Gf (along path P)  
    }  
    return f  
}
```

Max-Flow Min-Cut Theorem

Augmenting path theorem. Flow f is a max flow iff there are no augmenting paths.

Max-flow min-cut theorem. [Ford-Fulkerson 1956] The value of the max flow is equal to the value of the min cut.

Proof strategy. We prove both simultaneously by showing the following are equivalent:

- (i) There exists a cut (A, B) such that $v(f) = \text{cap}(A, B)$.
- (ii) Flow f is a max flow.
- (iii) There is no augmenting path relative to f .

(i) \Rightarrow (ii) This was the corollary to weak duality lemma.


(ii) \Rightarrow (iii) We show contrapositive: Let f be a flow. If there exists an augmenting path, then we can improve f by sending flow along path.

Proof of Max-Flow Min-Cut Theorem

(iii) \Rightarrow (i)

- Let f be a flow with no augmenting paths.
- Let A be set of vertices reachable from s in residual graph.
- By definition of A , $s \in A$.
- By definition of G_f , $t \notin A$.

$$\begin{aligned} v(f) &= \sum_{e \text{ out of } A} f(e) - \sum_{e \text{ in to } A} f(e) \\ &= \sum_{e \text{ out of } A} c(e) \quad \text{(otherwise connects outside } A) \\ &= \text{cap}(A, B) \quad \blacksquare \end{aligned}$$



original network

Running Time

Assumption. All capacities are integers between 1 and C .

Invariant. Every flow value $f(e)$ and every residual capacities $c_f(e)$ remains an integer throughout the algorithm.

Theorem. The algorithm terminates in at most $v(f^*) \leq nC$ iterations.

Pf. Each augmentation increases value by at least 1. ■

Corollary. If $C = 1$, Ford-Fulkerson runs in $O(mn)$ time.

Integrality theorem. If all capacities are integers, then there exists a max flow f for which every flow value $f(e)$ is an integer.

Pf. Since algorithm terminates, theorem follows from invariant. ■


7.3 Choosing Good Augmenting Paths

Ford-Fulkerson: Exponential Number of Augmentations


Q. Is generic Ford-Fulkerson algorithm polynomial in input size?

$m, n,$ and $\log C$

A. No. If C =largest capacity, then algorithm can take $\geq C$ iterations.



$2C$ iterations



Choosing Good Augmenting Paths

Use care when selecting augmenting paths.

- Some choices lead to exponential algorithms.
- Clever choices lead to polynomial algorithms.
- If capacities are irrational, algorithm not guaranteed to terminate!

Goal: choose augmenting paths so that:

- Can find augmenting paths efficiently.
- Few iterations.


Choose augmenting paths with: [Edmonds-Karp 1972, Dinitz 1970]

- Max bottleneck capacity.
- Sufficiently large bottleneck capacity.
- Fewest number of edges.


Capacity Scaling

Intuition. Choosing path with highest bottleneck capacity increases flow by max possible amount.

- Don't worry about finding exact highest bottleneck path.
- Maintain scaling parameter Δ .
- Let $G_f(\Delta)$ be the subgraph of the residual graph consisting of only edges with capacity at least Δ .



G_f



$G_f(100)$


Capacity Scaling

i think first Scale to find better aug
paths, then run Ford-Fulker

chose by $\max(\min(\text{edge in path}))$
of all paths

```
Scaling-Max-Flow( $G, s, t, c, C$ ) {  
  foreach  $e \in E$   $f(e) \leftarrow 0$   
   $\Delta \leftarrow$  largest power of 2  $\leq C$   
   $G_f \leftarrow$  residual graph  
  
  while ( $\Delta \geq 1$ ) {  
     $G_f(\Delta) \leftarrow \Delta$ -residual graph  
    while (there exists augmenting path  $P$  in  $G_f(\Delta)$ ) {  
       $f \leftarrow \text{augment}(f, c, P)$   
      update  $G_f(\Delta)$  (along  $P$ )  
    }  
     $\Delta \leftarrow \Delta / 2$   
  }  
  return  $f$   
}
```


Ford-Fulkerson Algorithm with Capacity Scaling





Flow value = 8

$\Delta = 4$

$G_f(8)$:




Ford-Fulkerson Algorithm with Capacity Scaling



Ford-Fulkerson Algorithm with Capacity Scaling


G :



Flow value = 14


$\Delta = 4$

G_f :



Ford-Fulkerson Algorithm with Capacity Scaling


G :




Flow value = 14

$\Delta = 2$


$G_f(4)$:




Ford-Fulkerson Algorithm with Capacity Scaling




Flow value = 19





Ford-Fulkerson Algorithm with Capacity Scaling



Flow value = 19



Ford-Fulkerson Algorithm with Capacity Scaling



Capacity Scaling: Correctness

Assumption. All edge capacities are integers between 1 and C .

Integrality invariant. All flow and residual capacity values are integral.

Correctness. If the algorithm terminates, then f is a max flow.

Pf.

- By integrality invariant, when $\Delta = 1 \Rightarrow G_f(\Delta) = G_f$.
- Upon termination of $\Delta = 1$ phase, there are no augmenting paths. ▪


Capacity Scaling: Running Time

Lemma 2. Let f be the flow at the end of a Δ -scaling phase. Then the value of the maximum flow is at most $v(f) + m \Delta$.

Pf. (almost identical to proof of max-flow min-cut theorem)

- We show that at the end of a Δ -phase, there exists a cut (A, B) such that $\text{cap}(A, B) \leq v(f) + m \Delta$.
- Choose A to be the set of nodes reachable from s in $G_f(\Delta)$.
- By definition of A , $s \in A$.
- By definition of $G_f(\Delta)$, $t \notin A$.

$$\begin{aligned}
 v(f) &= \sum_{e \text{ out of } A} f(e) - \sum_{e \text{ in to } A} f(e) \\
 &\geq \sum_{e \text{ out of } A} (c(e) - \Delta) - \sum_{e \text{ in to } A} \Delta \\
 &= \sum_{e \text{ out of } A} c(e) - \sum_{e \text{ out of } A} \Delta - \sum_{e \text{ in to } A} \Delta \\
 &\geq \text{cap}(A, B) - m \Delta \quad \blacksquare
 \end{aligned}$$



original network

Capacity Scaling: Running Time

Lemma 1. The outer while loop repeats $1 + \lceil \log_2 C \rceil$ times.

Pf. Initially $C/2 < \Delta \leq C < 2\Delta$. Δ decreases by a factor of 2 each iteration. ■

Lemma 2. Let f be the flow at the end of a Δ -scaling phase. Then the value of the maximum flow is at most $v(f) + m \Delta$. ← proof on previous slide

Lemma 3. There are at most $2m$ augmentations per scaling phase.

Pf.

- Initially, each of the m edges can carry at most $C < 2\Delta$ flow.
- In general, consider the situation at the beginning of a Δ -phase.
- Each augmentation in a Δ -phase will increase $v(f)$ by at least Δ .
- Let f be the flow at the end of the previous scaling (2Δ -)phase.
- Lemma 2 $\Rightarrow v(f^*) \leq v(f) + m (2\Delta)$. ■

Theorem. The scaling max-flow algorithm finds a max flow in $O(m \log C)$ augmentations. It can be implemented to run in $O(m^2 \log C)$ time. ■