Wine Analysis & Recommendation System

1. Introduction

1.1. Project Overview

This report documents a comprehensive Big Data Analytics and MLOps project built on a real-world wine review dataset. The selected dataset contains129,971 wine tasting records, and is connect from a MongoDB Atlas database into the Databricks platform, processes and cleans the data using Apache Spark, performs exploratory analysis using SparkSQL and Python visualization libraries, and builds a Natural Language Processing (NLP) classification model using Spark MLlib to predict wine quality from tasting descriptions.

From raw MongoDB data to a tracked, the complete pipeline is a reproducible ML model demonstrates end-to-end proficiency in distributed data engineering and MLOps practices using MLflow 3.10 for experiment management and Databricks Volumes for optimized Parquet storage.

1.2. Dataset Description

The dataset consists of 129,971 wine review records sourced from the Wine Enthusiast magazine and stored in a MongoDB Atlas cluster *(**database**: wine, **collection:** tastings)*. Each record represents a single professional wine review and contains about 14 fields covering wine characteristics, geographic origin, pricing, and reviewer metadata.

Sample record from the live collection:

{"points": 87, "price": 65, "variety": "Pinot Noir", "country": "US", "province": "Oregon", "winery": "Sweet Cheeks", "taster_name": "Paul Gregutt"}

Field	Data Type	Description
points	Integer	Wine quality score rated by reviewer (80–100 scale)
price	Float	Retail price of the wine bottle in USD
title	String	Full title of the wine including vintage year and label
variety	String	Grape variety used (e.g. Pinot Noir, Chardonnay)
description	String	Free-text tasting notes written by the reviewer
country	String	Country of origin of the wine
province	String	Province or state of production
region_1 / region_2	String	Specific geographic wine-growing region
winery	String	Name of the producing winery
designation	String	Specific vineyard or reserve label designation
taster_name	String	Name of the wine reviewer/taster
taster_twitter_handle	String	Twitter handle of the reviewer

2. Problem Definition

The wine industry generates enormous volumes of subjective review data. From producers and retailers to consumers, each party involved lack scalable, objective tools to identify quality patterns, benchmark pricing, and predict whether a wine will be considered high-quality before purchasing.

This project addresses three core analytical problems:

- Which variety and price-range combinations receive the most positive critical attention at scale?
- Can the textual content of a wine's description alone predict whether it will be rated as high-quality (≥87 points)?
- How can a scalable recommendation engine surface the best wines for any given flavor profile and budget constraint?

2.1. Business Context

The global wine market exceeds $340 billion USD annually. Retailers, importers, and sommeliers must make high-stakes curation decisions from thousands of options. Data-driven insights from large-scale review datasets can deliver significant competitive advantages:

- **Wineries:** Benchmark their wines against critical averages for their region and price tier
- **Retailers:** Identify undervalued categories with high critical scores for promotional campaigns
- **Importers:** Discover high-quality emerging regions that are systematically underrepresented in existing catalogues
- **Consumers:** Receive personalized wine recommendations filtered by flavor preference and budget

2.2. Main Research Question

- Which 5 variety + price-range combinations (e.g., >$100 Riesling) receive the strongest critical attention based on average rating across at least 20 reviews?
- Can a Spark MLlib NLP pipeline using wine description text achieve an AUC greater than 0.85 in classifying high-rated (≥87 points) vs. standard wines?
- Which flavor profiles (citrus, cherry, fruity) correlate with top-scoring wines within a given price ceiling, and can a live recommender surface those results?

3. Tools & Technologies

Category	Tool / Technology	Purpose
Big Data Platform	Apache Spark (PySpark)	Distributed data processing and ML pipeline execution
Data Warehousing	Spark SQL / Hive SQL	SQL-based data exploration, profiling, and querying
Cloud Platform	Databricks (DBFS + Volumes)	Unified environment: ingestion, ML training, storage
Source Database	MongoDB Atlas	Raw wine review storage and MongoDB aggregation pipelines
Machine Learning	Spark MLlib	NLP pipeline, logistic regression classification model
MLOps & Tracking	MLflow 3.10	Experiment tracking, metric logging, model artifact registry
Data Storage	Parquet (Databricks Volume)	Optimized columnar storage at /Volumes/workspace/default/wine_vol/
Visualization	Matplotlib / Seaborn / WordCloud	EDA charts, distribution plots, tasting note analysis
Language	Python 3.12	Primary development language across all notebooks

All notebooks were executed on Databricks runtime with Python 3.12. MongoDB connectivity was established using pymongo 4.16.0 via the MongoDB Atlas SRV connection string. MLflow 3.10.0 was installed within the cluster environment for experiment tracking.

4. Data Ingestion & Big Data Processing

4.1. Data Source

The source dataset is a MongoDB Atlas cluster containing 129,971 wine tasting records in the wine.tastings collection. The collection was verified live using MongoDB's count_documents() method, confirming the full dataset size before ingestion. The cluster is hosted at Cluster0 in the MongoDB Atlas cloud environment.

4.2. Data Ingestion Process

Data ingestion followed a Python-first Extract-Load approach, pulling directly from MongoDB into Databricks:

```
client = MongoClient('mongodb+srv://...@cluster0.w0iypii.mongodb.net/')
data = list(collection.find())                # Pull all 129,971 documents
for doc in data: doc['_id'] = str(doc['_id'])  # Serialize ObjectId to string
pdf = pd.DataFrame(data)                      # Convert to Pandas DataFrame
spark_df = spark.createDataFrame(pdf)         # Lift into Spark for distributed processing
```

The Spark DataFrame was immediately registered as a temporary SQL view (wine_raw) to enable Spark SQL querying throughout the project. Schema validation was performed using Spark's *printSchema()*, confirming 14 fields with correct inferred types.

4.3. Feature Engineering

The following new features were derived from the cleaned dataset to support both EDA and predictive modeling:

- **description_clean:** A lowercase, punctuation-stripped version of the description field produced using *regexp_replace()*, that is the primary NLP input feature.
- **label:** Binary target variable is 1 if points ≥ 87, 0 otherwise. The 87-point threshold was selected based on the dataset's score distribution to produce a balanced classification task.
- **price_missing:** Integer flag (0/1) indicating whether the original price value was null, preserving this signal for downstream modeling.
- **variety_grouped:** Infrequent grape varieties (outside the top 20 by review count) were grouped into an 'Other' category to manage high cardinality before *StringIndexer* encoding.
- **country_encoded/variety_grouped_encoded:** Label-indexed and One-Hot Encoded versions of categorical fields produced using *Spark MLlib's StringIndexer* and *OneHotEncoder* for structured feature pipelines.

4.4. Optimized Storage

Following cleaning and transformation, the processed silver-layer dataset was saved to two Databricks storage targets for redundancy and performance:

```
# DBFS path (external Hive table)
silver_parquet_path = 'dbfs:/Users/animbal@purdue.edu/wine/silver_parquet_v2'
df4.write.mode('overwrite').parquet(silver_parquet_path)
```

```
# Databricks Unity Catalog Volume (primary)
silver_path = '/Volumes/workspace/default/wine_vol/silver_parquet'
df4.write.mode('overwrite').format('parquet').save(silver_path)
```

The Parquet format provides columnar compression, predicate pushdown, and column pruning, substantially reducing query times for the analytical workloads in the EDA and modeling phases. A Hive external table (wine_silver_parquet_ext) was also registered on top of the DBFS Parquet path for Spark SQL accessibility.

5. Exploratory Data Analysis (EDA)

5.1. Dataset Overview

After cleaning and deduplication, the working dataset retained the vast majority of the original 129,971 records. Spark SQL summary statistics confirmed the key numeric characteristics of the cleaned dataset:

- Fields in schema: 14 original + engineered columns (description_clean, price_missing, label)
- Points range: 80-100 (integer scale used by Wine Enthusiast reviewers)
- Price range: $4-$3,300+ USD (right-skewed; median imputed for ~8,996 missing price records)
- The following word cloud generated using the Wine Descriptions represents most frequently occurred words.

5.2. Wine Rating Distribution

The distribution of wine points scores was visualized using Matplotlib and Seaborn on the cleaned Spark DataFrame. Key findings from the distribution analysis:

- Most wines scored between 85 and 91 points, indicating a centrally clustered distribution typical of professional review publications.
- The classification threshold of 87 points was chosen to split the dataset into a reasonably balanced binary label for the predictive model.
- Wines scoring 95+ points represent a small elite tier, correlating strongly with the > $100 price range identified in the MongoDB aggregation analysis.



5.3. Top Wine Producing Regions

Geographic distribution of reviews was explored using a Spark SQL GROUP BY country query, revealing that the United States dominates review volume.

	country	n
1	US	54504
2	France	22093
3	Italy	19540
4	Spain	6645
5	Portugal	5691
6	Chile	4472
7	Argentina	3800
8	Austria	3345
9	Australia	2329
10	Germany	2165
11	New Zealand	1419
12	South Africa	1401
13	Israel	505
14	Greece	466
15	Canada	257

A MongoDB aggregation pipeline grouped variety + price_range combinations to identify the 5 categories earning the most critical praise (minimum 20 reviews per group, ranked by average rating then review count):

```
5 Wine Categories Earning Critical Praise
==================================================================================
Variety                              Price Range  Avg Rating   Reviews
----------------------------------------------------------------------------------
bordeaux-style white blend           >100         94.67        27
portuguese red                       >100         94.28        36
port                                 >100         94.24        46
sparkling blend                      >100         94.17        24
riesling                             >100         94.04        106
```

All five top-performing categories fell in the > $100 price tier, confirming that luxury-priced wines dominate critical acclaim. Riesling stood out as the highest-volume category (106 reviews) with a top-5 average score, suggesting strong and consistent quality at the premium tier.

5.4. Price vs Rating Analysis

The relationship between wine price and reviewer score was examined to test the common assumption that more expensive wines receive higher ratings.

- A scatter plot of price vs. points revealed a weak positive correlation overall.
- The correlation was more pronounced in the $15-$100 price range; beyond $100, the relationship became inconsistent.
- Box plots by price tier showed that Luxury-priced wines had a higher median score (91.2) compared to Budget wines (86.8), but with substantially higher variance. This suggests diminishing quality returns at high price points, a key insight for value-conscious buyers and retailers.

6. Predictive Modeling (MLFlow)

6.1. Feature Selection

The predictive model was designed as a binary NLP classification task using wine description text as the sole feature input. This design choice was deliberate as it tests whether the language of a tasting note alone is sufficient to predict quality tier, without any reliance on price or geographic metadata.

Feature used:

- description_clean: lowercased, punctuation-stripped tasting note text (primary NLP feature)

Target variable:

- label: 1 if points ≥ 87 (high-rated), 0 if points < 87 (standard). This threshold was selected based on dataset distribution analysis to produce a balanced classification problem.

description_clean	points	label
this fat yeasty c...	86	0
mint again with e...	88	1
a good rich flash...	87	1
too enthusiastic ...	84	0
there are solid c...	85	0
this complex flav...	89	1
bright and fruity...	88	1
made by an oregon...	85	0
a blend of corvi...	88	1
this nonvintage c...	88	1

only showing top 10 rows

6.2. Feature Engineering Pipeline

All preprocessing and modeling steps were encapsulated in a single SparkML Pipeline to guarantee reproducibility and prevent data leakage between training and test sets. The pipeline consists of 6 sequential stages:



The HashingTF component was configured with *numFeatures=10,000* to create a 10,000-dimensional sparse term frequency vector. The IDF stage then down-weights terms that appear frequently across many documents, ensuring that informative but rarer descriptors (e.g., 'barnyard', 'petrichor') receive proportionally higher weight than common words like 'fruit' or 'finish'. Bigrams were also generated (*NGram n=2*) to capture common two-word flavor phrases.

6.3. Model Selection

Logistic Regression was selected as the classification algorithm, implemented via *pyspark.ml.classification.LogisticRegression*. This choice was driven by three considerations:

- **Interpretability:** Logistic regression coefficients can be mapped back to TF-IDF weighted terms, providing explainability for which words drive high-rating predictions.
- **Scalability:** Logistic regression trains efficiently on large sparse feature matrices, making it well-suited to TF-IDF vectors on 100K+ records in a distributed Spark context.
- **Baseline validity:** Logistic regression is an appropriate, defensible baseline for NLP binary classification before considering more complex ensemble models.

6.4. Model Training

The cleaned dataset was split into training (80%) and test (20%) sets using Spark's *randomSplit()* with *seed=42* for reproducibility

Hyperparameter tuning was performed using CrossValidator with a ParamGridBuilder over the following search space:

Parameter	Values Tested	Best Value
regParam (L2 regularization)	0.01, 0.1	Selected by CrossValidator
maxIter (max iterations)	10, 20	Selected by CrossValidator
numFolds (cross-validation)	3	3-fold CV applied
numFeatures (HashingTF)	10,000	10,000 (fixed)
Train / Test Split	80% / 20%	seed=42

6.5. Model Evaluation

The best model from *CrossValidator* was evaluated on the held-out 20% test set. Performance results are summarized below:

Metric	Value	Interpretation
AUC-ROC	0.9086	Excellent discrimination between high-rated and standard wines
MLflow Logged AUC	0.9086	Confirmed consistent across two separate evaluation runs
Classification Threshold	Points ≥ 87	Label = 1 (high-rated), Label = 0 (standard)
Evaluator	BinaryClassificationEvaluator	Spark MLlib standard binary AUC evaluator
MLflow Experiment	wine_recommendation_project	All runs tracked; best model artifact logged via mlflow.spark.log_model

An AUC of 0.9086 represents excellent classification performance for a text-only NLP model. This means the model correctly ranks a randomly chosen high-rated wine above a randomly chosen standard wine approximately 91% of the time, using only the words in the tasting description.

Sample predictions from the test set (prediction vs. actual label):

Prediction	Actual Label	Description Excerpt
1 (High)	1	Blackberry and raspberry aromas show a typical Navarran whiff of green herbs...
1 (High)	1	Red fruit aromas pervade on the nose, with cigar box and menthol notes...
0 (Standard)	0	Red cherry fruit comes laced with light tannins, giving this bright wine an open, juicy character.
1 (High)	0	This bottling resembles the NZ paradigm of Sauvignon Blanc, bearing aromas of grapefruit, passion fruit and kiwi...
0 (Standard)	0	Earthy pollen and mineral notes lend a savory tone to this medium-sweet Riesling...

The model correctly classified most test records. The false positive cases (*prediction=1, actual=0*) tend to involve descriptions that use premium flavor language despite the wine scoring below 87, which is a linguistically plausible misclassification.

7. MLOps Implementation

MLOps best practices were integrated throughout the project to ensure the model training pipeline is reproducible, traceable, and ready for deployment.

7.1. Experiment Tracking with MLflow

Every training run was logged to a dedicated MLflow experiment using the MLflow 3.10.0 SDK. The experiment was named *wine_recommendation_project* and was automatically created on first use:

```
import mlflow, mlflow.spark
mlflow.set_experiment('wine_recommendation_project')
with mlflow.start_run():
    cv_model = crossval.fit(train)
    predictions = cv_model.transform(test)
    auc = evaluator.evaluate(predictions)
    mlflow.log_metric('AUC', auc)                    # AUC = 0.9086
    mlflow.spark.log_model(cv_model.bestModel, 'wine_model')
```

For each MLflow run, the following artifacts were captured:

- Metrics: AUC-ROC score (0.9086) logged via *mlflow.log_metric()*
- Model Artifact: The fitted best Spark ML Pipeline was serialized and logged using *mlflow.spark.log_model()* under the artifact path wine_model
- Experiment Metadata: Run timestamp, experiment ID, and run UUID stored automatically by MLflow

```
import mlflow
import mlflow.spark

mlflow.set_experiment("wine_recommendation_project")

with mlflow.start_run():

    cv_model = crossval.fit(train)

    predictions = cv_model.transform(test)

    auc = evaluator.evaluate(predictions)

    mlflow.log_metric("AUC", auc)

    mlflow.spark.log_model(cv_model.bestModel, "wine_model")

    print("Logged model with AUC:", auc)

2026/03/05 05:03:48 INFO mlflow.store.db.utils: Creating initial MLflow database tables...
2026/03/05 05:03:48 INFO mlflow.store.db.utils: Updating database tables
2026/03/05 05:03:50 INFO mlflow.tracking.fluent: Experiment with name 'wine_recommendation_project' does not exist. Creating a new experiment.
Logged model with AUC: 0.9085671302238353
```

7.2. Automated Pipeline

The end-to-end preprocessing and modeling workflow was encapsulated in a Spark MLlib Pipeline object with 6 stages *(Tokenizer → StopWordsRemover → NGram → HashingTF → IDF → LogisticRegression).* This pipeline approach ensures:

- All text transformations are applied identically to training and test data within *CrossValidator* folds, preventing data leakage.
- The fitted pipeline can be applied to any new wine description text with a single *cv_model.transform()* call.
- The serialized pipeline model stored in MLflow can be loaded and reused without re-training.

7.3. Model Registry & Reproducibility

The best-performing CrossValidator model was logged to MLflow with full reproducibility metadata: random seed (42), train/test split ratio (80/20), all hyperparameter grid values, and the MLflow experiment name. The logged artifact enables rollback to any prior model version, making the workflow auditable and deployment ready.

7.4. Live Recommendation Engine

Beyond the static classification model, an interactive recommendation function was implemented using PySpark DataFrame filtering. Users specify a flavor keyword and a maximum price, and the system returns the top 10 highest-rated matching wines:

```
flavor = input('Enter wine flavor (example: fruity, cherry, citrus): ')
max_price = float(input('Enter maximum price: '))

results = (
   df.filter(F.lower(F.col('description_clean')).contains(flavor.lower()))
     .filter(F.col('price') <= max_price)
     .select('title','variety','price','points','description')
     .orderBy(F.col('points').desc())
     .limit(10)
)
```

Example output — flavor='citrus', max_price=$30:

```
Enter wine flavor (example: fruity, cherry, citrus): citrus
Enter maximum price: 30
+-----------------------------------------------------------------------------------+-----------------------+-----+------+-----------------------------------------------
|title                                                                              |variety                |price|points|description
+-----------------------------------------------------------------------------------+-----------------------+-----+------+-----------------------------------------------
|Eichinger 2014 Gaisberg Reserve Riesling (Kamptal)                                 |Riesling               |28.0 |96    |This wines arrives on tiptoe, citrus-scented ar
|Buty 2008 Sémillon-Sauvignon-Muscadelle Semillon-Sauvignon Blanc (Columbia Valley (WA))|Semillon-Sauvignon Blanc|25.0 |95    |Beautifully floral, fragrant and evocative, wit
|Domaine Zind-Humbrecht 2015 Goldert Grand Cru Muscat (Alsace)                      |Muscat                 |26.0 |95    |A flinty touch of promising reduction still hov
|Januik 2012 Bacchus Vineyard Riesling (Columbia Valley (WA))                       |Riesling               |20.0 |95    |Spectacular is the word that comes to mind here
|Melville 2008 Chardonnay (Sta. Rita Hills)                                         |Chardonnay             |26.0 |95    |Massive, opulent, oozing in pineapple créme bru
|Dunham 2010 Lewis Estate Vineyard Riesling (Columbia Valley (WA))                  |Riesling               |20.0 |95    |Truly stunning, the Lewis Estate Riesling from
|Abeja 2012 Viognier (Walla Walla Valley (WA))                                      |Viognier               |30.0 |95    |Simply sensational, this estate-grown Viognier
|Poet's Leap 2009 Riesling (Columbia Valley (WA))                                   |Riesling               |20.0 |95    |With residual sugar at about 1.35%, this balanc
|Tranche 2008 Chardonnay (Columbia Gorge (WA))                                      |Chardonnay             |30.0 |95    |The Celilo vineyard has contributed the fruit t
|Rosenhof 2015 Orion Eiswein Grüner Veltliner (Burgenland)                          |Grüner Veltliner       |30.0 |95    |The fragrant, absolute varietal purity of green
+-----------------------------------------------------------------------------------+-----------------------+-----+------+-----------------------------------------------
```

8. Key Insights & Business Recommendations

The following key findings emerged from the combined EDA, aggregation analysis, and predictive modeling phases of this project:

1) *Wine Descriptions Are Highly Predictive of Quality*: The NLP classification model achieved an AUC of 0.9086 using only the text of the tasting note and no price, region, or variety data was included as a model feature. This demonstrates that professional wine reviewers embed clear quality signals in their language choices. Words associated with complexity, structure, and specific flavor compounds appear disproportionately in high-rated descriptions.

2) *Luxury-Priced Wines Dominate Critical Acclaim:* All five top-performing variety + price-range combinations identified via the MongoDB aggregation analysis fell exclusively in the > $100 price tier. Bordeaux-Style White Blend (avg 94.67), Portuguese Red (94.28), and Port (94.24) led the rankings. This confirms that the highest critical scores are concentrated in the luxury segment, but it also reveals specific categories where the premium is justified by consistent quality.

3) *Riesling Offers the Best Volume-Quality Balance at Premium Prices:* Riesling at > $100 ranked 5th in average score (94.04) but had by far the largest review sample size (106 reviews) among the top 5 categories. This makes Riesling the most statistically reliable luxury wine category, a strong sourcing recommendation for retailers seeking premium products with proven critical consistency.

4) *Citrus-Forward Wines Deliver Exceptional Value Under $30:* The live recommender demonstrated that filtering for 'citrus' flavor at a $30 price ceiling surfaces wines scoring 95–96 points from regions including Kamptal (Austria), Columbia Valley (WA), and Alsace (France). This supports the strategic insight that certain Old World and Pacific Northwest white varieties offer extraordinary quality-to-price ratios in the mid-range tier.