We need a fancy title

Whitepaper - Version 0.1 May 4, 2018

Benjamin Leiding¹, Will Vorobev², Peter Zverkov³, and Lena Cherry⁴

Chorus Technology, Göttingen, Germany benjamins-email-@domain.com
 Chorus Technology, New York, United States of America benjamins-email-@domain.com
 Chorus Technology, Barcelona, Spain peters-email-@domain.com
 Chorus Technology, New York, United States of America lenas-email-@domain.com

Abstract. I am an abstract - pet me.

DON'T FORGET THE PLAGIARISM CHECK

Keywords: Blockchain, Autonomous Vehicles, V2X Communication, Chorus Technology, Self-Driving Cars, VANET, Smart Contract

1 Introduction

Despite steadily growing public transport networks and systems, especially in most first world countries, cars and similar vehicles are still the default standard for urban transportation. In the US, "about 86 percent of all workers commuted to work by private vehicle, either driving alone or carpooling" [27] even though in recent years the numbers remained relatively stable after decades of consistent increase - similar applies to other industrial countries [28][44] even though the overall percentage of vehicle commuters in Europe is lower than in the US [10]. While it was normal for the last few decades to own a vehicle and commute on a day-by-day basis, the future will be radically different due to the progressing evolution of self-driving cars and autonomous vehicles. The car-sharing economy that developed in recent years in combination with autonomous cars results in a so called passenger economy [19]. Users no longer own cars, instead just hop on an autonomous cars, pick a destination and get delivered without any human interaction. An Intel report estimates the size of this economy to be around US\$ 7 Trillion in 2050 [19].

Despite some recent setback, e.g. Uber and Tesla accidents [?][?][?], academic researchers as well as companies from the private sector make fast progresses in the research area of self-driving cars [?][?]. It took less than 15 years from the first DARPA Grand Challenge (a prize competition for autonomous vehicles) to

self-driving cars operating on public streets on a regular base (Tesla, Waymo, Uber, etc.) [?][?][?]. Besides the cars, several projects are also already working on system solutions for trucks, rovers, drones, ships and even airplanes [?][?][?][9]. But progressing automation and driverless transport that enables the passenger economy is only a small aspect of the potential of these new technologies. During a talk⁵ at the 2013 Turing Festival in Edinburgh, Mike Hearn did not only described a vision where most users don't own cars anymore and instead use services provided by autonomous vehicles that own itself, but also the potentials of a vehicle-to-vehicle (V2V) as well as a vehicle-to-infrastructure (V2I) economy. Autonomous vehicles (AVs) may own themselves, offer services and goods to earn money, and pay money to acquire services that they cannot provide on their own, e.g., car renting a parking lot, paying for a charged battery, using toll roads, or simple service check ups. The idea of V2V and V2I or in general V2X (vehicle-to-everything) will fuel various new business fields.

Certainly, traditional payment systems such as paper money or fiat currencies in general are not suited to be part of this new economy. There are slow, depend on third parties (e.g., banks) and suffer from bureaucratic overhead. Blockchain technology and cryptocurrencies offer a promising alternative payment solution that comes with several additional advantages that we will discuss later on. The blockchain technology, also referred to as distributed ledger system, is most noticeably known for providing the foundation of the peer-to-peer (P2P) cryptocurrency and payment system Bitcoin [29], but nowadays there a various different platforms out there, e.g., [18][37][47]. Several companies already started to prototype applications that combine vehicles and blockchains. Porsche is researching different payment-related applications for vehicles [38] whereas Ford focuses on traffic marshaling [24]. As expected in the early days of a new technology, companies focus on selective solutions for a selection of very specific problems or use cases and the resulting solutions are only compatible with their own products. What is currently missing in the new business field of V2X economy is an industry standard that can easily be integrated with self-driving and (semi)-autonomous cars or even nowadays cars.

This whitepaper addresses the detected gap by introducing the Chorus Technology solution, thereby answering the question of how to implement a library for (semi)-autonomous vehicles that enables a V2X trading platform for goods and services? In order to answer this question with a separation of concerns, we pose the following sub-questions: What is the long term vision of Chorus Technology? What are the critical requirements and the corresponding architecture of the Chorus platform? What are the system-engagement processes for the stakeholders?

The remainder of this paper is structured as follows: Section 2 introduces supplementary literature and related work. Section 3 then outlines the vision of Chorus Technology as well as different use-cases. Afterwards, Section 4 analyses the requirements of the our system and outlines the resulting system architecture that we derive from the requirements. Afterwards, Section 5 expands on the

⁵ https://www.youtube.com/watch?v=MVyv4t00Ke4

system-engagement processes for the stakeholders, followed by Section 6 that introduces the Chorus prototype as well as feasibility evaluation. Section 7 provides an discussion and an analysis of related projects. Finally, Section 8 concludes this work and provides an outlook on future work.

2 Technical Background and Supplementary Literature

The following section provides background information and describes related works regarding previous ideas and concepts that focus on a blockchain-based VANET platforms. First, Section 2.1 introduces the general concepts of blockchain technology, terms and frameworks. Afterwards, Section 2.2 and Section 2.3 focus on the fundamentals of autonomous vehicles as well as vehicular ad-hoc networks. Finally, Section 2.4 introduces traffic waves, flows and congestions.

2.1 Blockchain Technology

As the name suggests, a blockchain consists of a chronologically ordered chain of blocks. Every block consists of a certain number of validated transactions and each of those block links to its predecessor by a hash reference. As a result, changing the content of one block also changes all succeeding blocks and hence breaks the chain. All blocks are stored on and verified by all participating nodes. While the initial Bitcoin blockchain only supported a very limited set of scripting instructions, the next generation of blockchain platforms, e.g., Ethereum [47], Qtum [11], or Tezos [18], provide Turing-complete programming languages on the protocol-layer level in order to enable smart contract capabilities. Smart contracts are, "orchestration- and choreography protocols that facilitate, verify and enact with computing means a negotiated agreement between consenting parties" [11]. Hence, the parties participating in the enactment of a smart contract establish binding agreements and deploy applications using such smart contracts in order to provide blockchain-based applications. Those application are as versatile as smart contracts itself and enable services including the finance sector [30][41], academic and business authentication and identity solutions [4][8][21][26][42], reputation systems [6] as well platforms for Internetof-Things (IoT) applications [7][35].

The blockchain concept is particularly interesting for the V2X economy for three reasons. First, it removes the need for trusted third parties and instead enables trust-less transaction enactment. Second, transactions that were agreed up on cannot be changed any more since the underlying blockchain is tamperproof. Third, no human interaction is required for any kind of transaction between vehicles or machines in general.

2.2 Autonomous Vehicles

During the last 15 years research on autonomous and self-driving cars progressed a lot and nowadays such cars already operating on public streets on a regular

base, e.g., Tesla, Waymo, Uber, and so on. The ultimate goal of most manufacturers and researchers is to develop the first fully self-driving and autonomous vehicle. In order to clarify some definitions, this short section provides a short introduction to the most relevant terms and concepts.

An autonomous car, also referred to as a driverless car or robotic car, is able to navigating and interact with its environment without human input based on information provided by its sensors [16][46]. To do so, modern cars are equipped with radar- and laser sensors, lidars, GPS devices, cameras and several further sensing devices. Based on these information, the vehicle interprets the surrounding world and deduces appropriate action strategies such as avoiding obstacles (other vehicles, humans or a house) on the way to the supermarket [13][48]. As the technology developed over time, vehicles were equipped with more and more sensors, resulting in different driving capabilities. The SAE [40] defined six levels of driving autonomy to categorize the varying capabilities and progresses of several approaches:

- Level 0 (No automation): No driving autonomy, the driver has to perform all driving tasks and interactions.
- Level 1 (Driver assistance): The vehicle is controlled by the driver, but is supported by some basic driver assistance functionalities.
- Level 2 (Partial automation): The vehicle is able to perform some specific tasks (acceleration or steering) without driver input. Nevertheless, the driver must be fully engaged in driving task and monitor all decision of the car and the environment at all time. The user has to be able to intervene at any given moment.
- Level 3 (Conditional automation): The driver is still a necessity, but is not required to monitor the vehicle or the environment at any given moment. But given a notification by the vehicle, the driver has to be able to take back control over the car in case the vehicle encounters a situation that it cannot deal with on its own.
- Level 4 (High Automation): The vehicle is able to perform all driving tasks without human intervention in most driving scenarios. The driver can take control whenever desired.
- Level 5 (Full Automation): The vehicle is able to perform all driving tasks without human intervention in all driving scenarios. The driver can take control whenever desired as long as a steering wheel is still part of the vehicle.

The Chorus interaction- and transaction layer library supports and enables a varying number of services for vehicles of each automation level, whereas the most sophisticated applications require SAE level 5 and simpler plug-ins may only require SAE level 0.

2.3 Vehicular Ad-Hoc Networks - VANETs

Communication between vehicles, road infrastructure and Internet-based services is a key enabler of upcoming generation of vehicles. So called vehicular

ad-hoc networks provide an abstract concept that models the different components that are required for V2V, V2I and V2X communication. As illustrated in Figure 1, the basic components of VANETs are vehicles, on-board-units (OBUs), application-units (AUs) and road-side-units (RSUs).

RSUs are placed along the road side or in dedicated locations such as at cross-roads. Usually, RSUs provide short range communication based on IEEE 802.11p radio technology but can also be equipped with other network devices in order to provide communication within the infrastructural network [1]. An OBU is typically mounted onto a vehicle and used for exchanging information with RSUs or other OBUs. Short range wireless communication or other radio technologies are usually used to exchange information [3].

Closely linked to the OBU is the AU. They might even reside in the same physical unit or is mobile and might be regularly removed from the vehicle (e.g smartphones). The AU provides an execution environment for applications that utilize the OBU's communication capabilities [1][3].

Communication in VANETs occurs either inside a vehicle between AUs and




Fig. 1. General VANET architecture (Based on: [3] and [22])

OBU, wirelessly between different vehicles (V2V), vehicles and infrastructure (V2I) or vehicles and the infrastructure via broadband (V2B) [15]. For authentication purposes, each network participant is equipped with a unique public/private key pair which usually resides in a tamper-proof-device (TPD). In blockchain terms, the TPD is similar to an external hardware wallet.

2.4 Traffic Wave Theory Work

Work-In-Progress

3 The Chorus Vision

Intro




Fig. 2. Caption.

3.1 Use Cases

Work-In-Progress

CHECK THE chorus website for this section

traffic wave fixing as one of the major selling points in the prototype as well as the main product insurance example as a running case later for the prototype

- 3.2 Human to Human
- 3.3 Human to Vehicle
- 3.4 Vehicle to Vehicle

road space negotiation

3.5 Vehicle to Infrastructure

4 System Design and Architecture

The vision of Chorus outlined in Section 3 is now analyzed from technical perspective as part of the following section. In order to identify, structure and

formalize the critical requirements and stakeholders on an abstract level, we use one part of an Agent-Oriented Modeling (AOM) method [45], i.e., goal models. Section 4.1 introduces AOM goal models and the Chorus specific goal model. The produced goal model is used in subsequent Section 4.2 to derive the Chrous system architecture . The resulting system architecture and specifications serve as implementation guidelines. Finally, Section 5.1 provides some details on the smart contract lifecycle management within our solution, whereas Section 4.3 outlines a general outlook on the APIs and how to integrate the Chorus library into external applications.

4.1 Functional Goals, Quality Goals, Stakeholders and Requirements

In system development and software engieering, good requirements follow certain characteristics. According to [12][17] requirements address one issue only and are completely specified without missing information. Moreover, they have to be consistent and do not contradict itself, or in correlation with other requirements. Finally, a requirement must also be atomic and without conjunctions [32].




Fig. 3. Selection of AOM notation elements.

The AOM methodology is a socio-technical requirements-engineering approach used to model complex systems that consist of humans, devices, and software agents. An AOM goal model enables both, technical- and non-technical stakeholders, to capture and understand the functional- and non-functional requirements of a complex system. Figure 3 depicts the three main elements that an AOM goal model comprises in order to capture the system requirements and goals. Roles of involved entities are represented in form of sticky men, whereas functional requirements are depicted as parallelograms. Note that in the specific context of this whitepaper, a sticky man does not exclusively represent human entities but rather all kinds of entities, e.g., also vehicles or infrastructure. Functional requirements are also referred to as goals. Non-functional requirements are depicted as clouds and refer to quality goals of the modeled software system. The AOM goal model follows a tree-like hierarchy with the root value proposition of the modeled system at the top. Subsequently, this main goal is decomposed into sub-goals where each sub-goal represents an aspect for achieving its parent goal [25]. The goals are further decomposed into multi-layered sub-goals until the lowest atomic level is reached. Additionally, roles and quality goal may be assigned to goals and are inherited to lower-level goals. The following Section 4.1.1 introduces the top-level goal model our system, followed by Section 4.1.2 focusing on the non-functional goals of the AOM goal model.

4.1.1 Top-Level AOM Goal Model

The presented AOM goal model is similar to the model presented by the authors in [20], since implementation of a V2X system is a specific use case of the more abstract and general M2M (machine-to-machine) interaction platform represented in that paper. Meanwhile, Figure ?? presents the top-level AOM goal model of the system using the modeling method described above. The main value proposition is to provide a V2X interaction and transaction layer library for (autonomous) vehicles, thereby representing the root of the goal model. The complex main value proposition is split into four sub-goals representing the four main components.

First, one component for managing the V2X platform. This functional goal includes managing certain aspects of the platform itself, e.g., creating, updating, deleting a new platform, as well as the management of the underlying smart contracts. Each platform operates a master smart contract and several sub-smart contracts. While the master contract is in charge of platform management and controlled by the hardware vendor (e.g., Tesla), the sub contracts each offer service provision for a specific service, interaction, transaction or application.

The second functional goal enables V2X interaction. That mostly covers onand off-chain supply and demand administration. Entities may register offers or requests on-chain in order to attract business partners, but for the other use cases a local supply demand management off-chain is more suitable, e.g., roadspace negotiation. Supervising on- and off-chain auctions is basically equivalent to the on- and off-chain supply and demand management. Besides that, plug-ins and dApps of the Chorus eco-system might use platform smart contracts for service enactment and have to be integrated as well in this context.

The third functional requirement, that represents the third main component, enables V2X transaction via the blockchain. The most important part here is the transaction management via a smart contract lifecycle that will be detailed later on in Section 5.1.

Finally, the fourth functional requirement focus on the enactment of various plug-ins and decentralized applications (dApps). Applications and plug-ins have to be registered, prepared for enactment, executed and terminated. Moreover, they have to interact with various entities of the eco-system depending on the use case. Since nowadays most blockchains offer Turing-complete smart contract support, the variety of applications and plug-ins in our eco-system is quite vast.




Fig. 4. Chorus - Top-level goal model representation (Source: Based on [20]).

4.1.2 Non-Functional Requirements

Besides the four sub-goals of the top-level AOM goal model, we further identify thirteen quality goals of the main value proposition that are inherited to all refining sub-goals. A scalable system design is necessary to provide Chorus services to a large quantity of users and customers. A further property that supports to achieve this scalability is the non-functional requirement automated, that refers to a high degree of process automation eliminating the need for human interaction, e.g., tedious and repetitive tasks. Cost efficiency is another important quality goal. Flexible digital collaboration is a highly dynamic process that involves the enactment of diverse activities, the participation of diverse partners, and the exchange of diverse data [31]. Thus, we must allow diverse collaboration scenarios and permit the inter-organizational harmonization of heterogeneous concepts and technologies between participating entities. Another key property of the system being easy to use (Usable) for business collaboration. According to [32], easy usability also includes the support of proper error avoidance in or-

der to "anticipate and prevent common errors that occur during a collaboration configuration. Closely related is *error handling*, to help with system support a user to recover from errors. *Learnability* refers to how quickly users master using the system" [32].

Moreover, we assign two additional quality goals that ensure a blockchain agnostic as well as entity agnostic design. Chorus should be neither limited to a specific blockchain nor vehicle hardware of a specific vendor. Interoperable hardware and software design is another consequence of the previous quality goals as well as easy integration (Integrable). It is crucial to interoperate at runtime with information systems supporting other business functions.

Furthermore, a secure service provision is also crucial in terms of operational security, e.g., protect user accounts and personal data from unauthorized access, secure data transfer within the system between entities or preventing data- and information leaks as well as preventing accidents. A reliable enactment of all Chorus-based interactions and transaction facilitates the previous goals as well. Data communicated internally as well as externally has to protected against unauthorized tampering (tamperproof) in order to protect business collaborations, but also ensure the safety of participating entities. Finally, since cars and similar vehicles move much faster than humans, a fast service provision is essential for most tasks.

The presented goal model is used in the following Section 4.2 to derive our system architecture. We do not list all details of the further refined AOM goal model in this whitepaper due to space constraints and in order to focus on the most relevant system components and features.

4.2 Component Diagrams

The abstract system- and business architecture is derived from the functionaland non-function requirements of the AOM goal model presented earlier. The services are powered by a service-oriented architecture (SOA) that is comprised of different designated components. Each of these components is self-contained, well-defined components and provides a specific set of services [14][36]. Dedicated services and components may also consist of other underlying sub-services [39].

In the following, a technology-agnostic UML-component-diagram representation is used to illustrate the system architecture [5][43]. The UML notation elements used to model the architecture are presented in Figure 5. In UML, components are represented as rectangular boxes and labeled either with the keyword *component*, or with the component icon in the right-hand upper corner. A component may consists of further sub-components and is implemented by one, or more classes, or objects. Moreover, components are reusable and communicate via two types of interfaces as illustrated in Figure 5. Small squares depict ports that are attached to the border of components and expose required and provided interfaces. Ports may also specify inputs and outputs as they operate uni-, or bi-directionally [5][43]. Once more, sticky men are used to depict entities and their interactions with the system.




Fig. 5. UML-component diagram notation elements.

The remainder of this section first introduces an abstract high-level overview of the system architecture and components. Afterwards, further illustration present selected sub-components of our architecture.

Work-In-Progress

MAKE SURE TO ADAPT THE COMPONENT DIAGRAM TO THE AOM GOAL MODEL! it is a distributed system that resides in different components on different places - hence we had to add further helper-component that enable communication and proper system execution.

4.2.1 High-Level Architecture

Work-In-Progress



Fig. 6. Caption.

4.3 Library / API

Work-In-Progress

5 System Engagement Processes

The Chorus transaction layer library automates and simplifies VANET-based V2X service provision on several levels. A core element of many of the Chorus use cases is smart contract-based negotiation and contract enactment between entities that are the result of collaborating tasks and subprocesses. For example, as described in Section 2 two vehicles conduct a road-space negotiation auction

that results either in a change of positions or is aborted. This process potentially also involves payment processing, further local as well as global communication and local match-making between vehicles. On an abstract level, most of the use cases presented earlier in this paper follow at some point a similar procedure on smart-contract level. Same applies for scenarios that involve a price negotiation or auction. In the following, we introduce these two abstract processes in more detail The processes are represented using Business Process Model and Notation (BPMN) [33] and UML sequence diagrams [34].

Consequently, Section 5.1 details the BPMN representation of the generalized contract negotiation lifecycle, followed by Section Section 5.2 that details the different auction mechanisms of our platform. Finally, Section 5.3 covers the Chorus token value proposition.

5.1 Smart Contract Negotiation Lifecycle Management

Work-In-Progress




Fig. 7. Smart Contract Negotiation Lifecycle (Based on [11]).

5.2 Auction Algorithm

Work-In-Progress

Vickrey auction [2][23]

Auction stuff that might happen during road-space negotiations as described in Section $3.4\,$

1-1 auction Note: -Vickrey Auction - Buyer max price: 3 Seller min price: 2.80 - only one auction round - Note: If seller offer ξ buyer offer $=\xi$ no deal




Fig. 8. Caption.

X-X auction Note: - (modified) Vickrey Auction - only one auction round buyer-1 max price: 1.80 - buyer-2 max price: 3.20 - buyer-3 max price: 3.5 - seller min price: 2.0 - Note: If seller offer \vdots buyer offer $= \vdots$ no deal - NOTE: In case we have multiple sellers, the workflow is similar. In the end, the highest bidder is matched with the seller of the highest price, the second highest offer with the second highes seller price ... and so on. Please keep in mind that this is a vickrey auction $= \xi$ hence, highest bidder pay price of the second highest offer and so on...




Fig. 9. Caption.

5.3 Token Economics and Value Proposition

${\bf Work\text{-}In\text{-}Progress}$

6 Prototype and Feasibility Study

Intro

what is the use case and purpose of our prototype

traffic wave fixing as one of the major selling points in the prototype as well as the main product $\,$

 $in surance\ example$

burnable tokens ERC721?

- what problem does it solve?

6.1 Prototype Architecture

Work-In-Progress

Dummy.jpg

Fig. 10. System architecture of the Chorus prototype.

- component diagram - scoring algorithm - tech stack (?) - token - testnet - incentive system

6.2 Eco-System and Economics

Work-In-Progress

6.3 Evaluation

 ${\bf Work\text{-}In\text{-}Progress}$

7 Discussion

Intro

7.1 Critical Analysis

Work-In-Progress

7.2 Related Work

Work-In-Progress

8 Conclusion and Future Work

We conclude \dots

 ${\bf Work\text{-}In\text{-}Progress}$

References

- Al-Sultan, Saif and Al-Doori, Moath M and Al-Bayatti, Ali H and Zedan, Hussien: A Comprehensive Survey on Vehicular Ad Hoc Network. Journal of Network and Computer Applications 37, 380–392 (2014)
- 2. Ausubel, L.M., Milgrom, P., et al.: The lovely but lonely vickrey auction. Combinatorial auctions 17, 22–26 (2006)
- 3. Baldessari, R., Bödekker, B., Deegener, M., Festag, A., Franz, W., Kellum, C.C., Kosch, T., Kovacs, A., Lenardi, M., Menig, C., et al.: Car-2-Car Communication Consortium Manifesto (2007)
- 4. Bochem, A., Leiding, B., Hogrefe, D.: Unchained Identities: Putting a Price on Sybil Nodes in Mobile Ad hoc Networks. In: Security and Privacy in Communication Networks (SecureComm 2018). Singapore (August 2018)
- Booch, G., Jacobson, I., Rumbaugh, J., et al.: The Unified Modeling Language. Unix Review 14(13), 5 (1996)
- Calcaterra, C., Kaal, W.A., Vlad, A.: Semada Technical Whitepaper Blockchain Infrastructure for Measuring Domain Specific Reputation in Autonomous Decentralized and Anonymous Systems. URL: https://papers.ssrn.com/sol3/ papers.cfm?abstract_id=3125822 (2018), (Accessed April 18, 2018)
- Christidis, K., Devetsikiotis, M.: Blockchains and Smart Contracts for the Internet of Things. IEEE Access 4, 2292–2303 (2016)
- Civic Technologies, Inc.: CIVIC Whitepaper. URL: https://tokensale.civic.com/CivicTokenSaleWhitePaper.pdf (2017), (Accessed May 01, 2018)
- 9. Copel, N., Ater, T.: DAV Decentralized Autonomous Vehicles (Whitepaper). URL: https://dav.network/whitepaper.pdf (2017), (Accessed April 27, 2018)
- 10. Cortright, J.: Sprawl Tax: How the US Stacks Up Internationally . URL: http://cityobservatory.org/sprawl-tax-how-the-us-stacks-up-internationally/ (2016), (Accessed April 26, 2018)
- Dai, P., Mahi, N., Earls, J., Norta, A.: Smart-Contract Value-Transfer Protocols on a Distributed Mobile Application Platform. URL: https://qtum.org/uploads/ files/a2772efe4dc8ed1100319c6480195fb1.pdf (2017), (Accessed May 01, 2018)
- 12. Davis, A.M.: Software Requirements: Objects, Functions, and States. Prentice-Hall, Inc. (1993)
- 13. Dokic, J., Müller, B., Meyer, G.: European roadmap smart systems for automated driving. European Technology Platform on Smart Systems Integration (2015)
- Erl, T.: Service-Oriented Architecture: Concepts, Technology, and Design. Pearson Education India (2005)
- 15. Faezipour, M., Nourani, M., Saeed, A., Addepalli, S.: Progress and Challenges in Intelligent Vehicle Area Networks. Communications of the ACM 55(2), 90–100 (2012)
- Gehrig, S.K., Stein, F.J.: Dead reckoning and cartography using stereo vision for an autonomous car. In: Intelligent Robots and Systems, 1999. IROS'99. Proceedings. 1999 IEEE/RSJ International Conference on. vol. 3, pp. 1507–1512. IEEE (1999)
- 17. IEEE Computer Society. Software Engineering Technology Committee and Institute of Electrical and Electronics Engineers: IEEE Recommended Practice for Software Requirements Specifications. IEEE Std, Institute of Electrical and Electronics Engineers (1994)
- L. M. Goodman: Tezos A Self-Amending Crypto-Ledger (White paper).
 URL: https://www.tezos.com/static/papers/white_paper.pdf (2014), (Accessed April 27, 2018)

- Lanctot, R.: Accelerating the Future: The Economic Impact of the Emerging Passenger Economy. URL: https://newsroom.intel.com/newsroom/wp-content/ uploads/sites/11/2017/05/passenger-economy.pdf (2017), (Accessed April 27, 2018)
- 20. Leiding, B.: The Machine-to-Machine Economy Revolution A blockchain-based trading platform for the Internet of Things (2018), unpublished
- 21. Leiding, B., Cap, C.H., Mundt, T., Rashidibajgan, S.: Authcoin: Validation and Authentication in Decentralized Networks. In: The 10th Mediterranean Conference on Information Systems MCIS 2016. Cyprus, CY (September 2016)
- Leiding, B., Memarmoshrefi, P., Hogrefe, D.: Self-Managed and Blockchain-Based Vehicular Ad-Hoc Networks. In: Proceedings of the 2016 ACM International Joint Conference on Pervasive and Ubiquitous Computing: Adjunct. pp. 137–140. ACM (2016)
- Lucking-Reiley, D.: Vickrey auctions in practice: From nineteenth-century philately to twenty-first-century e-commerce. Journal of economic perspectives 14(3), 183– 192 (2000)
- MacNeille, P.R., Wisniewski, J., DeCia, N.: Vehicle-to-Vehicle Cooperation to Marshal Traffic (Mar 27 2018), uS Patent 9,928,746
- Marshall, J.: Agent-Based Modelling of Emotional Goals in Digital Media Design Projects. International Journal of People-Oriented Programming (IJPOP) 3(1), 44-59 (2014)
- McCorry, P., Shahandashti, S.F., Clarke, D., Hao, F.: Authenticated key exchange over bitcoin. In: International Conference on Research in Security Standardisation. pp. 3–20. Springer (2015)
- 27. McKenzie, B.: Who Drives to Work? Commuting by Automobile in the United States: 2013. American Community Survey Reports (2015)
- 28. Mieke Berends-Ballast et al.: Transport and Mobility 2016. URL: https://www.cbs.nl/en-gb/publication/2016/25/transport-and-mobility-2016 (2016), (Accessed April 26, 2018)
- 29. Nakamoto, S.: Bitcoin: A Peer-to-Peer Electronic Cash System. URL: https://bitcoin.org/bitcoin.pdf (2008), (Accessed May 01, 2018)
- 30. Nguyen, Q.K.: Blockchain A Financial Technology for Future Sustainable Development. In: Green Technology and Sustainable Development (GTSD), International Conference on. pp. 51–54. IEEE (2016)
- 31. Norta, A.: Exploring Dynamic Inter-Organizational BusinessProcess Collaboration: Privacy Protecting Concepts for ChoreographingeSourcing in B2B with Service-Oriented Computing. VDM Verlag (2008)
- 32. Norta, A., Grefen, P., Narendra, N.C.: A Reference Architecture for Managing Dynamic Inter-Organizational Business Processes. Data & Knowledge Engineering 91, 52–89 (2014)
- 33. Object Management Group: Notation (BPMN) Version 2.0. OMG Specification (2011), (Accessed May 04, 2018)
- 34. Object Management Group: OMG Unified Modeling LanguageTM (OMG UML), Superstructure - Version 2.4.1. OMG Specification (2011), (Accessed May 04, 2018)
- 35. Ouaddah, A., Elkalam, A.A., Ouahman, A.A.: Towards a Novel Privacy-Preserving Access Control Model Based on Blockchain Technology in IoT. In: Europe and MENA Cooperation Advances in Information and Communication Technologies, pp. 523–533. Springer (2017)
- Perrey, R., Lycett, M.: Service-Oriented Architecture. In: Applications and the Internet Workshops, 2003. Proceedings. 2003 Symposium on. pp. 116–119. IEEE (2003)

- Popov, S.: The Tangle Version 1.4.2. URL: https://iota.org/IOTA_Whitepaper.pdf (2018), (Accessed April 22, 2018)
- 38. Porsche AG: Porsche Introduces Blockchain to Cars. URL: https://newsroom.porsche.com/en/themes/porsche-digital/porsche-blockchain-panamera-xain-technology-app-bitcoin-ethereum-data-smart-contracts-porsche-innovation-contest-14906.html (2018), (Accessed April 27, 2018)
- 39. Rosen, M., Lublinsky, B., Smith, K.T., Balcer, M.J.: Applied SOA: Service-Oriented Architecture and Design Strategies. John Wiley & Sons (2012)
- SAE International: Automated Driving Levels of Driving Automation as Defined in SAE International Standard J3016. URL: https://web.archive.org/web/ 20170903105244/https://www.sae.org/misc/pdfs/automated_driving.pdf (2014), (Accessed May 01, 2018)
- 41. SALT Technology, Ltd.: SALT Blockchain-Backed Loans Whitepaper. URL: https://membership.saltlending.com/files/abstract.pdf (2017), (Accessed April 25, 2018)
- 42. SelfKey Foundation: SelfKey Whitepaper. URL: https://selfkey.org/whitepaper/ (2017), (Accessed April 27, 2018)
- 43. Specification, O.A.: OMG Unified Modeling Language (OMG UML), Superstructure, V2.1.2. Object Management Group (2007)
- 44. Statistics New Zealand: Car, bus, bike or train: What were the main means of travel to work (2006)
- 45. Sterling, L., Taveter, K.: The Art of Agent-Oriented Modeling. MIT Press (2009)
- 46. Thrun, S.: Toward robotic cars. Communications of the ACM 53(4), 99–106 (2010)
- 47. Wood, G.: Ethereum: A Secure Decrentralized Generalised Transaction Ledger. URL: http://gavwood.com/paper.pdf (2014), (Accessed May 01, 2018)
- 48. Zhu, W., Miao, J., Hu, J., Qing, L.: Vehicle detection in driving simulation using extreme learning machine. Neurocomputing 128, 160–165 (2014)