## 1: AlertDialog AlertDialog最多支持三个按钮 例: AlertDialog.Builder builder = new AlertDialog. Builder (DialogActivity. this); builder.setIcon(R. drawable.ic\_launcher); builder. setTitle("你确定要离开吗?"); builder. setMessage("你确定要离开吗?"); builder.setPositiveButton("确定", new DialogInterface.OnClickListener() { public void onClick(DialogInterface dialog, int whichButton) { } }); builder.setNegativeButton("取消", new DialogInterface.OnClickListener() { public void onClick(DialogInterface dialog, int whichButton) { } });



builder.create().show();

效果:

1: 设置三个按键:

```
}
                      });
                    builder. setNeutralButton ("取消", new
DialogInterface.OnClickListener() {
                           public void onClick(DialogInterface dialog, int
whichButton) {
                              }
                      });
                  builder.setNegativeButton("退出", new
DialogInterface.OnClickListener() {
                            public void onClick(DialogInterface dialog, int
whichButton) {
                        });
2: 选择列表框
例:
           final String[] mItems =
{"item0", "item1", "itme2", "item3", "itme4", "item5", "item6"};
           final AlertDialog. Builder builder = new
AlertDialog. Builder (DialogActivity. this);
           builder.setTitle("列表选择框");
           builder.setItems(mItems, new DialogInterface.OnClickListener() {
                     public void onClick(DialogInterface dialog, int which) {
                              builder.setTitle("你选择的id为" + which + ", " +
mItems[which]);
                              builder. show();
                     }
           });
           builder.create().show();
效果:
```

列表选择框
item0
item1
itme2
item3
itme4
item5

你选择的id为3 , item3	
item0	
item1	
itme2	
item3	
itme4	
item5	

3: 单项选择列表框

builder.setSingleChoiceItems(.....);

## 4: 多项选择列表框

builder.setMultiChoiceItems(items, checkedItems, listener);