

```

#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>

#define BUFFER_SIZE 1024

int main(int argc, char *argv[])
{
    int source, destination;
    char buffer[BUFFER_SIZE];
    ssize_t bytes_read, bytes_written;

    if (argc != 3)
    {
        printf("Usage: %s <source> <destination>\n", argv[0]);
        return 1;
    }

    source = open(argv[1], O_RDONLY);

    if (source == -1)
    {
        perror("Error opening source file");
        return 1;
    }

    destination = open(argv[2], O_WRONLY | O_CREAT | O_TRUNC, 0644);

    if (destination == -1)
    {
        perror("Error opening destination file");
        close(source);
        return 1;
    }
}

```

[Read 55 lines]

^G Help
^X Exit

^O Write Out
^R Read File

^F Where Is
^\ **Replace**

^K Cut
^U Paste

^T Execute
^J Justify

```
gireesh@Bhashwanth: ~/OSLi x + v
openat(AT_FDCWD, "/etc/ld.so.cache", O_RDONLY|O_CLOEXEC) = 3
close(3) = 0
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libselinux.so.1", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\0\0\0\0\0\0"..., 832) = 832
close(3) = 0
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libgcc_s.so.1", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\0\0\0\0\0\0"..., 832) = 832
close(3) = 0
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libm.so.6", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\0\0\0\0\0\0"..., 832) = 832
close(3) = 0
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libc.so.6", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0 \250\2\0\0\0\0\0"..., 832) = 832
close(3) = 0
openat(AT_FDCWD, "/usr/lib/x86_64-linux-gnu/libpcre2-8.so.0", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\0\0\0\0\0\0"..., 832) = 832
close(3) = 0
openat(AT_FDCWD, "/proc/filesystems", O_RDONLY|O_CLOEXEC) = 3
read(3, "nodev\tsysfs\nnodev\ttmpfs\nnodev\tbd"..., 1024) = 442
close(3) = 0
openat(AT_FDCWD, "/proc/mounts", O_RDONLY|O_CLOEXEC) = 3
read(3, "none /usr/lib/modules/6.18.33.2-"..., 1024) = 1024
read(3, "e 0 0\ndepts /dev/pts devpts rw,"..., 1024) = 1024
read(3, "c,relatime 0 0\nhugetlbfs /dev/hu"..., 1024) = 1024
read(3, "n/user/1000 tmpfs rw,nosuid,node"..., 1024) = 104
read(3, "", 1024) = 0
close(3) = 0
openat(AT_FDCWD, "/proc/self/maps", O_RDONLY|O_CLOEXEC) = 3
read(3, "5b4e075c3000-5b4e076b5000 r--p 0"..., 1024) = 1024
```

```
openat(AT_FDCWD, "/usr/share/coreutils/locales/uucore/en-US.ftl", O_RDONLY|O_CLOEXEC) = 3
read(3, "# Common strings shared across a"... , 4080) = 4080
read(3, "", 32) = 0
close(3) = 0
openat(AT_FDCWD, "/usr/share/coreutils/locales/cat/en-US.ftl", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "sample.txt", O_RDONLY|O_CLOEXEC) = 3
Hello World
close(5) = 0
close(4) = 0
close(3) = 0
+++ exited with 0 +++
gireesh@Bhashwanth:~/OSLab$
```

```
gireesh@Bhashwanth:~/OSLab$ copy.c
copy.c: command not found
gireesh@Bhashwanth:~/OSLab$ nano copy.c
gireesh@Bhashwanth:~/OSLab$ nano copy.c
gireesh@Bhashwanth:~/OSLab$ echo "Hello World" > sample.txt
gireesh@Bhashwanth:~/OSLab$ cat sample.txt
Hello World
gireesh@Bhashwanth:~/OSLab$
```