

tcgetattr(3p) — Linux manual page

[PROLOG](#) | [NAME](#) | [SYNOPSIS](#) | [DESCRIPTION](#) | [RETURN VALUE](#) | [ERRORS](#) | [EXAMPLES](#) | [APPLICATION USAGE](#) | [RATIONALE](#) | [FUTURE DIRECTIONS](#) | [SEE ALSO](#) | [COPYRIGHT](#)

TCGETATTR(3P)

POSIX Programmer's Manual

TCGETATTR(3P)

PROLOG

[top](#)

This manual page is part of the POSIX Programmer's Manual. The Linux implementation of this interface may differ (consult the corresponding Linux manual page for details of Linux behavior), or the interface may not be implemented on Linux.

NAME

[top](#)

`tcgetattr` – get the parameters associated with the terminal

SYNOPSIS

[top](#)

```
#include <termios.h>
```

```
int tcgetattr(int fildes, struct termios *termios_p);
```

DESCRIPTION

[top](#)

The `tcgetattr()` function shall get the parameters associated with the terminal referred to by *fildes* and store them in the **termios** structure referenced by *termios_p*. The *fildes* argument is an open file descriptor associated with a terminal.

The *termios_p* argument is a pointer to a **termios** structure.

The `tcgetattr()` operation is allowed from any process.

If the terminal device supports different input and output baud rates, the baud rates stored in the **termios** structure returned by `tcgetattr()` shall reflect the actual baud rates, even if they are equal. If differing baud rates are not supported, the rate returned as the output baud rate shall be the actual baud rate. If the terminal device does not support split baud rates, the input baud rate stored in the **termios** structure shall be the output rate (as one of the symbolic values).

RETURN VALUE [top](#)

Upon successful completion, 0 shall be returned. Otherwise, -1 shall be returned and *errno* set to indicate the error.

ERRORS [top](#)

The *tcgetattr()* function shall fail if:

EBADF The *fildev* argument is not a valid file descriptor.

ENOTTY The file associated with *fildev* is not a terminal.

The following sections are informative.

EXAMPLES [top](#)

None.

APPLICATION USAGE [top](#)

None.

RATIONALE [top](#)

Care must be taken when changing the terminal attributes. Applications should always do a *tcgetattr()*, save the **termios** structure values returned, and then do a *tcsetattr()*, changing only the necessary fields. The application should use the values saved from the *tcgetattr()* to reset the terminal state whenever it is done with the terminal. This is necessary because terminal attributes apply to the underlying port and not to each individual open instance; that is, all processes that have used the terminal see the latest attribute changes.

A program that uses these functions should be written to catch all signals and take other appropriate actions to ensure that when the program terminates, whether planned or not, the terminal device's state is restored to its original state.

Existing practice dealing with error returns when only part of a request can be honored is based on calls to the *ioctl()* function. In historical BSD and System V implementations, the corresponding *ioctl()* returns zero if the requested actions were semantically correct, even if some of the requested changes could not be made. Many existing applications assume this behavior and would no longer work correctly if the return value were changed from zero to -1 in this case.

Note that either specification has a problem. When zero is returned, it implies everything succeeded even if some of the

changes were not made. When -1 is returned, it implies everything failed even though some of the changes were made.

Applications that need all of the requested changes made to work properly should follow `tcsetattr()` with a call to `tcgetattr()` and compare the appropriate field values.

FUTURE DIRECTIONS

[top](#)

None.

SEE ALSO

[top](#)

`tcsetattr(3p)`

The Base Definitions volume of POSIX.1-2017, *Chapter 11, General Terminal Interface*, `termios.h(0p)`

COPYRIGHT

[top](#)

Portions of this text are reprinted and reproduced in electronic form from IEEE Std 1003.1-2017, Standard for Information Technology -- Portable Operating System Interface (POSIX), The Open Group Base Specifications Issue 7, 2018 Edition, Copyright (C) 2018 by the Institute of Electrical and Electronics Engineers, Inc and The Open Group. In the event of any discrepancy between this version and the original IEEE and The Open Group Standard, the original IEEE and The Open Group Standard is the referee document. The original Standard can be obtained online at <http://www.opengroup.org/unix/online.html>.

Any typographical or formatting errors that appear in this page are most likely to have been introduced during the conversion of the source files to man page format. To report such errors, see https://www.kernel.org/doc/man-pages/reporting_bugs.html.

IEEE/The Open Group

2017

TCGETATTR(3P)

Pages that refer to this page: [termios.h\(0p\)](#), [cfgetispeed\(3p\)](#), [cfgetospeed\(3p\)](#), [tcsetattr\(3p\)](#)

HTML rendering created 2021-08-27 by [Michael Kerrisk](#), author of *The Linux Programming Interface*, maintainer of the [Linux man-pages project](#).

For details of in-depth **Linux/UNIX system programming training courses** that I teach, look [here](#).

Hosting by [jambit GmbH](#).

