

Boosting

Christian Peters

January 29, 2021

What you will know

→ The idea behind boosting

What you will know

- The idea behind boosting
- How to create a strong and efficient learning algorithm

What you will know

- The idea behind boosting
- How to create a strong and efficient learning algorithm
- What is AdaBoost and why is it so successful?

Let's talk about training a model

How to train a machine learning model

What we have learned so far...

- We have to pick a hypothesis class \mathcal{H}

How to train a machine learning model

What we have learned so far...

- We have to pick a hypothesis class \mathcal{H}
- \mathcal{H} can't be too complex (VC dim needs to be finite)

How to train a machine learning model

What we have learned so far...

- We have to pick a hypothesis class \mathcal{H}
- \mathcal{H} can't be too complex (VC dim needs to be finite)
- We need enough training data (more than some threshold $m_{\mathcal{H}}$)

How to train a machine learning model

What we have learned so far...

- We have to pick a hypothesis class \mathcal{H}
- \mathcal{H} can't be too complex (VC dim needs to be finite)
- We need enough training data (more than some threshold $m_{\mathcal{H}}$)
- Then we use ERM to pick the best $h \in \mathcal{H}$ that minimizes the empirical error

How to train a machine learning model

What we have learned so far...

- We have to pick a hypothesis class \mathcal{H}
- \mathcal{H} can't be too complex (VC dim needs to be finite)
- We need enough training data (more than some threshold $m_{\mathcal{H}}$)
- Then we use ERM to pick the best $h \in \mathcal{H}$ that minimizes the empirical error

But there is one problem...

ERM can be hard.

ERM can be hard.

- Depending on \mathcal{H} , the optimization problem can become arbitrarily complex

ERM can be hard.

- Depending on \mathcal{H} , the optimization problem can become arbitrarily complex
- e.g. implementing ERM for halfspaces in the non-separable case is computationally hard (chapter 9)

ERM can be hard.

- Depending on \mathcal{H} , the optimization problem can become arbitrarily complex
- e.g. implementing ERM for halfspaces in the non-separable case is computationally hard (chapter 9)
- For many interesting classes, it is infeasible to implement ERM
 - Solving the optimization problem takes forever

ERM can be hard.

- Depending on \mathcal{H} , the optimization problem can become arbitrarily complex
- e.g. implementing ERM for halfspaces in the non-separable case is computationally hard (chapter 9)
- For many interesting classes, it is infeasible to implement ERM
 - Solving the optimization problem takes forever

...so what can we do?

A first idea...

Idea: Use simpler hypothesis classes where ERM isn't hard.

A first idea...

Idea: Use simpler hypothesis classes where ERM isn't hard.

- Problem: Simple classes can be too "weak" to estimate all relationships in the data
 - Can lead to underfitting and poor performance

A first idea...

Idea: Use simpler hypothesis classes where ERM isn't hard.

- Problem: Simple classes can be too "weak" to estimate all relationships in the data
 - Can lead to underfitting and poor performance
- Approximation error is high (→ B/C tradeoff)

Idea: Use simpler hypothesis classes where ERM isn't hard.

- Problem: Simple classes can be too "weak" to estimate all relationships in the data
 - Can lead to underfitting and poor performance
- Approximation error is high (→ B/C tradeoff)
- Still, these classes can be useful for us
 - If the resulting hypothesis is at least better than random

A first idea...

Idea: Use simpler hypothesis classes where ERM isn't hard.

- Problem: Simple classes can be too "weak" to estimate all relationships in the data
 - Can lead to underfitting and poor performance
- Approximation error is high (→ B/C tradeoff)
- Still, these classes can be useful for us
 - If the resulting hypothesis is at least better than random

Let's call ERM on a simple class a **weak learner**. We will formally define it later...

The idea behind boosting

Why not combine many weak learners?

Can this give us an efficient strong learner?

The idea behind boosting

Why not combine many weak learners?

Can this give us an efficient strong learner?

- This theoretical question is the origin of boosting

The idea behind boosting

Why not combine many weak learners?

Can this give us an efficient strong learner?

- This theoretical question is the origin of boosting
- It was first raised in 1988 by Kearns and Valiant [2]

The idea behind boosting

Why not combine many weak learners?

Can this give us an efficient strong learner?

- This theoretical question is the origin of boosting
- It was first raised in 1988 by Kearns and Valiant [2]
- The first (practical) answer was given in 1995 by Freund and Schapire [1]
 - It is YES!

The idea behind boosting

Why not combine many weak learners?

Can this give us an efficient strong learner?

- This theoretical question is the origin of boosting
- It was first raised in 1988 by Kearns and Valiant [2]
- The first (practical) answer was given in 1995 by Freund and Schapire [1]
 - It is YES!
- The result is **AdaBoost**, a widely popular and award winning algorithm
 - We will take a look at this later...

The idea behind boosting

Why not combine many weak learners?

Can this give us an efficient strong learner?

- This theoretical question is the origin of boosting
- It was first raised in 1988 by Kearns and Valiant [2]
- The first (practical) answer was given in 1995 by Freund and Schapire [1]
 - It is YES!
- The result is **AdaBoost**, a widely popular and award winning algorithm
 - We will take a look at this later...

But first, let's get back to weak learning.

Weak Learnability

What exactly is a weak learner?

Remember, that a strong PAC learner for a class \mathcal{H} ...

What exactly is a weak learner?

Remember, that a strong PAC learner for a class \mathcal{H} ...

- ...if it is presented with $m > m_{\mathcal{H}}(\epsilon, \delta)$ examples

What exactly is a weak learner?

Remember, that a strong PAC learner for a class \mathcal{H} ...

- ...if it is presented with $m > m_{\mathcal{H}}(\epsilon, \delta)$ examples
- ...has to find a hypothesis $h \in \mathcal{H}$

What exactly is a weak learner?

Remember, that a strong PAC learner for a class \mathcal{H} ...

- ...if it is presented with $m > m_{\mathcal{H}}(\epsilon, \delta)$ examples
- ...has to find a hypothesis $h \in \mathcal{H}$
- ...such that $L_{(\mathcal{D}, f)}(h) < \epsilon$ for every D and f with confidence $1 - \delta$ (if RA holds)

What exactly is a weak learner?

Remember, that a strong PAC learner for a class \mathcal{H} ...

- ...if it is presented with $m > m_{\mathcal{H}}(\epsilon, \delta)$ examples
- ...has to find a hypothesis $h \in \mathcal{H}$
- ...such that $L_{(\mathcal{D}, f)}(h) < \epsilon$ for every D and f with confidence $1 - \delta$ (if RA holds)

In weak learning, we only want the error to be less than 50%.

Weak learning definition

An algorithm A is a γ -weak-learner for a class \mathcal{H} , if...

Weak learning definition

An algorithm A is a γ -weak-learner for a class \mathcal{H} , if...

- ...for every $\delta \in (0, 1)$ there exists a threshold $m_{\mathcal{H}}(\delta) \in \mathbb{N}$, such that

Weak learning definition

An algorithm A is a γ -weak-learner for a class \mathcal{H} , if...

- ...for every $\delta \in (0, 1)$ there exists a threshold $m_{\mathcal{H}}(\delta) \in \mathbb{N}$, such that
- ...if trained on at least $m > m_{\mathcal{H}}(\delta)$ examples

Weak learning definition

An algorithm A is a γ -weak-learner for a class \mathcal{H} , if...

- ...for every $\delta \in (0, 1)$ there exists a threshold $m_{\mathcal{H}}(\delta) \in \mathbb{N}$, such that
- ...if trained on at least $m > m_{\mathcal{H}}(\delta)$ examples
- ...it will find a hypothesis h , such that

Weak learning definition

An algorithm A is a γ -weak-learner for a class \mathcal{H} , if...

- ...for every $\delta \in (0, 1)$ there exists a threshold $m_{\mathcal{H}}(\delta) \in \mathbb{N}$, such that
- ...if trained on at least $m > m_{\mathcal{H}}(\delta)$ examples
- ...it will find a hypothesis h , such that
- ... $L_{(\mathcal{D}, f)}(h) < \frac{1}{2} - \gamma$ with confidence $1 - \delta$

Weak learning definition

An algorithm A is a γ -weak-learner for a class \mathcal{H} , if...

- ...for every $\delta \in (0, 1)$ there exists a threshold $m_{\mathcal{H}}(\delta) \in \mathbb{N}$, such that
- ...if trained on at least $m > m_{\mathcal{H}}(\delta)$ examples
- ...it will find a hypothesis h , such that
- ... $L_{(\mathcal{D}, f)}(h) < \frac{1}{2} - \gamma$ with confidence $1 - \delta$
- ...for every labeling function f and every distribution \mathcal{D} (if RA holds)

Weak learning definition

An algorithm A is a γ -weak-learner for a class \mathcal{H} , if...

- ...for every $\delta \in (0, 1)$ there exists a threshold $m_{\mathcal{H}}(\delta) \in \mathbb{N}$, such that
- ...if trained on at least $m > m_{\mathcal{H}}(\delta)$ examples
- ...it will find a hypothesis h , such that
- ... $L_{(\mathcal{D}, f)}(h) < \frac{1}{2} - \gamma$ with confidence $1 - \delta$
- ...for every labeling function f and every distribution \mathcal{D} (if RA holds)

...but how does this help us?

Why we care about weak learning

- We already know that implementing ERM for strong learners can be computationally hard

Why we care about weak learning

- We already know that implementing ERM for strong learners can be computationally hard
- Weak learners don't have to be that accurate (only better than 50%)

Why we care about weak learning

- We already know that implementing ERM for strong learners can be computationally hard
- Weak learners don't have to be that accurate (only better than 50%)
- Maybe we can find weak learners that can be implemented efficiently

Why we care about weak learning


- We already know that implementing ERM for strong learners can be computationally hard
- Weak learners don't have to be that accurate (only better than 50%)
- Maybe we can find weak learners that can be implemented efficiently
- ...and then use boosting to still end up with a strong learner

Why we care about weak learning

- We already know that implementing ERM for strong learners can be computationally hard
- Weak learners don't have to be that accurate (only better than 50%)
- Maybe we can find weak learners that can be implemented efficiently
- ...and then use boosting to still end up with a strong learner

Lets look at an example (Decision Stumps)

Spam detection with decision stumps



Made with Excalidraw

Figure 1: This is a Decision Stump.

AdaBoost

AdaBoost

Conclusion

Conclusion

The End.



Y. Freund and R. E. Schapire.

A decision-theoretic generalization of on-line learning and an application to boosting.

Journal of Computer and System Sciences, 55(1):119 – 139, 1997.



M. Kearns and L. G. Valiant.

Learning boolean formulae or finite automata is as hard as factoring.

Technical Report TR 14-88, Harvard University Aiken Computation Laboratory, 1988.



S. Shalev-Shwartz and S. Ben-David.

Understanding Machine Learning - From Theory to Algorithms.

Cambridge University Press, 2014.