Console
Crypto
Debugger
DNS
Domain
Errors
Events
File System
Globals
HTTP
HTTPS
Modules
Net
OS
Path
Process
Punycode
Query Strings
Readline
REPL
Stream
String Decoder
Timers
TLS/SSL
TTY
UDP/Datagram
URL
Utilities
V8
VM
ZLIB

If the `encoding` option is specified then this function returns a string. Otherwise it returns a buffer.

fs.readlink(path, callback)

Asynchronous readlink(2). The callback gets two arguments `(err, linkString)`.

fs.readlinkSync(path)

Synchronous readlink(2). Returns the symbolic link's string value.

fs.realpath(path[, cache], callback)

Asynchronous realpath(2). The `callback` gets two arguments `(err, resolvedPath)`. May use `process.cwd` to resolve relative paths. `cache` is an object literal of mapped paths that can be used to force a specific path resolution or avoid additional `fs.stat` calls for known real paths.

Example:

```
var cache = {'/etc':'/private/etc'};
fs.realpath('/etc/passwd', cache, (err, resolved
  if (err) throw err;
  console.log(resolvedPath);
});
```

fs.readSync(fd, buffer, offset, length, position)

Synchronous version of `fs.read()`. Returns the number of `bytesRead`.