



Object-Oriented Programming In Mechatronic Systems

Summer School

Module 1

Aachen, Germany, August 7th, 2018

Cybernetics Lab IMA & IfU
Faculty of Mechanical Engineering
RWTH Aachen University




Organization

Synopsis


Today's mechanical engineering relies heavily on advanced software tools. Both industry and research expect you not only to use these tools but to design, develop and deploy them as well. During this course we teach you how.

Topics

- Java 101
- Object Oriented Software Engineering
- Software-Hardware Interaction



■ Theory ■ Practical Exercises



Organization

... at the Institute of Information Management in Mechanical Engineer (IMA)

Information Management for Mechanical Engineering



Prof. Dr.-Ing.
Tobias Meisen

Management
Director of IMA



Johannes Lipp
M.Sc.

Researcher
Industrial
Big Data



**Christian
Scheiderer** M.Sc.

Researcher
Production
Technology



Dr.-Ing.
Max Hoffmann

Research Leader
Industrial Big Data



Daniel Lütticke
Dipl.-Inform

Research Leader
Production
Technology


The Cybernetics Lab

Presentation – Cybernetics Lab IMA & IfU

Who are we?




Interdisciplinary at the Cybernetics Lab IMA & IfU



What drives us

Research Domains





Motivation

Motivation



Mechatronic Systems rely on Advanced Software Tools!


From Computer Aided Design (CAD) to Robotics ...





Mechatronic Systems rely on Advanced Software Tools!


... to learning robots! (at our institute)






Mechatronic Systems rely on Advanced Software Tools!

... to self-optimizing production systems!



Algorithms and Programming Languages

We need an interface between human and computer



Both have different requirements:

Human:

- Analog world
- Visual, haptic and auditory signals
- Comprehensive integration in contextual knowledge
- Fluent, “natural” language

Computer

- Digital World
- Electronic signals
- Majority: no information “outside”
- Structured statements: Algorithms



How do we formulate a problem for the computer?

An **algorithm** is an unambiguous rule of action for solving a problem or a class of problems.

Colloquially:

- Algorithms are "somehow clever" methods that efficiently help to solve specific problems
- Not only arithmetic problems such as efficient addition or multiplication, but also everyday questions:
 - How do I find the exit from a labyrinth?
 - How do I calculate the shortest connection between two cities?
 - How do I search my warehouse shelf as quickly as possible?

Example of an algorithm:

1. Put a filter in the filter container
2. Fill the filter with coffee powder
3. Pour water into the tank provided for this purpose
4. Check whether empty coffee pot is ready
5. If **yes**: Go to step 7  Branch
6. If **not**: empty the coffee pot and place it under the filter
7. Press the start button
8. Wait until the coffee is ready (typically: machine "gurgles", steam rises)  Termination Condition

Properties of algorithms:

Finiteness:

- Formulated in a finite text (static finiteness)
- Finally needs a lot of memory (dynamic finiteness)
- Finished in finally many steps (scheduling)


Executability:

- Each step must actually be executable

Uniqueness:

- Always the same result under the same conditions (Determinacy)
- Only ever exactly one possibility of continuation (Determinism)

Interface between Human and Computer



Still, both have different requirements:

Human:

- Natural language
- Legibility
- Expressiveness

Computer

- Simple translation into machine code
- Efficiency of the generated code

Learning programming languages comparable to "natural" foreign languages

Syntax:

- Defines permitted strings (= vocabulary) and grammar
- In each language there are defined keywords

Semantics:

- Defines the meaning of the syntax
- Builds on syntax

Syntactically correct, semantic nonsense:

"A banana speculates purple the sunset."

Syntactically incorrect, semantically correct:

"A banana is fruit yellow."

Syntactically correct, semantically correct:

"A banana is a yellow fruit."



Algorithms and Programming Languages

```
1. class HelloWorld{  
2.     public static void main(String[] args){  
3.         System.out.println("Hello World!");  
4.     }  
5. }
```

Java

```
1. Program Hello  
2. Print *, "Hello World!"  
3. End Program Hello
```

Fortran

```
1. class HelloWorld(object):  
2.     def __init__(self, args):  
3.         print(„Hello World!“)
```

Python


Different syntax, identical semantics!

The Java Programming Language

The Java Programming Language

Brief History

- Java invented June 1991 by James Gosling at Sun (2010 acquired by Oracle)




- **Five** Design Goals:
 - *“Simple, Object Oriented, and Familiar”*
 - *“Robust and Secure”*
 - *“Architecture Neutral and Portable”*
 - *“High Performance”*
 - *“Interpreted, Threaded, and Dynamic”*
- Current Version: Java 8 Update 144

The Java Programming Language

It's widely spread!

TIOBE 2015 (Popularity Index)

Industry use (to name a few)




Sep 2017	Sep 2016	Change	Programming Language	Ratings	Change
1	1		Java	12.687%	-5.55%
2	2		C	7.382%	-3.57%
3	3		C++	5.565%	-1.09%
4	4		C#	4.779%	-0.71%
5	5		Python	2.983%	-1.32%



The Java Programming Language

Motto: “Write Once, Run Anywhere”



The Java Programming Language

Terminology

- JVM: **J**ava **V**irtual **M**achine. Executes Java byte code.
- JRE: **J**ava **R**untime **E**nvironment. Contains the JVM + set of libraries
- JDK: **J**ava **D**evelopment **K**it. Contains the JRE + Development tools (e.g. *javac*)

JDK

`javac, jar, debugging tools,
javap`

JRE

`java, javaw, libraries,
rt.jar`

JVM


Just In Time
Compiler (JIT)

JVM Features

- **Automatic Garbage Collector**
- JIT Compiler
- Byte Code Verifier
- **Supports other languages:**



What are the basic requirements for writing a Java program?


- A computer with a Java supported OS (e.g. Windows or OS X)
- A text editor, e.g. notepad++ (but we'll use  IDE during this course)
- The Java JDK: <http://www.oracle.com/technetwork/java/javase/downloads/jdk10-downloads-4416644.html>

Five steps to run a Java program


1. Create a Java source file, i.e. write some code.
2. Save it to a .java file (e.g. HelloWorld.java)
3. Compile the Code (using javac, e.g. `javac HelloWorld.java`).
4. The compilation yields a class file (e.g. `HelloWorld.class`)
5. Run the program (e.g. `java HelloWorld`)

The Java Programming Language


Writing, Compiling and Executing



```
1 public class HelloWorld {
2
3     public static void main (String[] args) {
4
5         System.out.println("Hello, World!");
6     }
7 }
8
```




```
C:\Windows\System32\cmd.exe
D:\Work\SUN-IMA\teaching\ase\Lectures\Examples>javac HelloWorld.java
```



```
nis von D:\Work\SUN-IMA\teaching\ase\Lectures\Ex
5 11:36 <DIR> .
5 11:36 <DIR> ..
5 11:36 427 HelloWorld.class
5 11:30 133 HelloWorld.java
2 Datei(en), 560 Bytes
2 Verzeichnis(se), 140.328.673.280 Bytes frei
UN-IMA\teaching\ase\Lectures\Examples>
```

1. Write
2. Compile
3. Yields a .class file
4. Execute



```
C:\Windows\System32\cmd.exe
D:\Work\SUN-IMA\teaching\ase\Lectures\Examples>java HelloWorld
Hello, World!
D:\Work\SUN-IMA\teaching\ase\Lectures\Examples>
```

Structure of a Java Program

Structure of a Java Source File

Structure of a Java Source File

Statements


```
public class Foo {
```

```
void bar() {
```

```
statement2;
```


Structure of a Java Program

Structure of a Java Source File




Structure of a Java Program

Structure of a Java Source File. A closer look at the class.



Structure of a Java Program

Structure of a Java Source File. A closer look at the method.



Structure of a Java Program

Structure of a Java Source File. A closer look at the statement.

```
public class HelloWorld {
```

print to standard
output

```
public void main (String args[]) {
```

What to print in
apostrophes

```
System.out.println("Hello, World!");
```

Statement
must end in a
semicolon!

Structure of a Java Program

What are comments?

- Document the code and keep it readable
- Single line comment: `// myComment`
- Multiple line comment: `/* myMultiLineComment */`

Examples

```
public class HelloWorld { // It's my first class!
    public static void main (String[] args) {
        /* I want to
        print on the command line */
        System.out.println("Hello, World!");
    }
}
```

Variables

What are variables?

- A container, a box or a cup. It contains something.
- They come in different kinds
- They got a name

Examples

- `short numberOfEngines = 5;`
- `double temperature = 23.7;`
- `boolean engineStarted = true;`
- `char c = 'e';`
- `int depth = -343535;`

Two ways of “constructing” variables

- **First**, declare, than initialize: `int length; length = 5;`
- **Second**, define them in one single statement: `int length = 5;`

Examples

- `short numberOfEngines = 5;`
- `double temperature = 23.7;`
- `boolean engineStarted = true;`
- `char c = 'e';`
- `int depth = -343535;`

Four Primitive Data Types in Java

- boolean, char, integer and floating point
- They got a default value
- They only hold one value

Data Type	Example	Keyword
Logical value	true, false	boolean
Single character	a, b, ...	char
Whole number	1, -3, 87, ...	byte, short, int, long
Real number	-2.6, 9.4, ...	float, double

For details (e.g. max or min values) see:

<https://docs.oracle.com/javase/tutorial/java/nutsandbolts/datatypes.html>

Variables

Rules I

- Variables must have a **type**, e.g. `double`!
- Variables must have a **name**, e.g. `temperature`!

```
double temperature;
```



type

name

Rules II and Good Practice

- No keywords are allowed as names, e.g. `class` or `while` are prohibited!
https://en.wikipedia.org/wiki/List_of_Java_keywords
- Names must start with a letter, underscore (`_`) or a dollar sign (`$`)
- No special characters, e.g. `§`.
- **Choose meaningful names**, e.g. `currentVelocity` (as opposed to `cV`);

Three kinds of variables in Java

```
public class Cylinder {  
    public double cylinderCap = 0;  
    public static char vendor = 'A';  
    public double computeCylinderCapacity(int r, int h) {  
        double rSquare = r*r;  
        return rSquare * Math.PI * h;  
    }  
}
```

instance variables

class/static
variables

local variables

Defining Constants Variables

- Are all-round in Mathematics, physics, engineering ...
- Are declared with the keyword `final`
- Convention for naming of constants: UPPERCASE, e.g. PI or E

Examples (the bad and the good)

```
double circumf = 2 * 3.1415 * r;  
double area = r * r * 3.1415;
```

- Typing errors
- Changing code in different places
- Bad Readability

```
final double PI = 3.1415;  
double circumf = 2 * PI *  
r;  
double area = r * r * PI;
```

- Good readability
- DRY principle (don't repeat yourself)

Operators and Variables

- **Allocation (=)**
- **Arithmetic (+, -, *, /, %)**
- **Comparison (==, !=, <, >)**
- **Unary (++ , --)**
- **Logical (! (not), &&, ||)**

Allocation and Arithmetic Operator Examples

- `int number; number = 5;`
- `int x = 5;`
`int y = 7;`
`int sum = x + y;`
`int diff = 40 - y;`
`double div = 30 / 4.3;`

Operators and Variables

- Allocation (=)
- Arithmetic (+, -, *, /, %)
- **Comparison (==, !=, <, >)**
- **Unary (++ , --)**
- **Logical (! (not), &&, ||)**

Comparison, Unary and Logical Operator Examples

- ```
boolean isSmaller;
int one = 1; int two = 2;
isSmaller = one < two;
```
- ```
int i = 3;  
int j = i++;
```
- ```
boolean result = !true || false;
```

## Operators Priorities

- How does Java evaluate an complex expression? E.g.:
- ```
int a = 5;  
int b = 7;  
int c = 2  
a = a - b - c % (a * c++); // (a is -4)
```
- With an internal priority table! Excerpt from:
<https://docs.oracle.com/javase/tutorial/java/nutsandbolts/operators.html>

Priority	Operator
1	Unary, e.g. ++
4	Additive, e.g. +
12	Logical OR e.g.
14	Allocation, e.g. =


Type Casts

- It can be necessary to convert one type of data into an other one
- There are two types of casts
- **Implicit** type casts. Target type is computed **automatically** via context. “Upgrading”.
- **Explicit** type casts. Target type **has to be explicitly defined**. “Downgrading”. Target type has to be defined in “(“ and “)” brackets


Examples

- ```
int i = 70;
double radius = i; // radius contains 70.0
```
- ```
double d = 70.3456;  
int num = (int)d; // num contains 70
```

Implicit type cast only one way



Type cast overview



Output

- How does Java output information on the screen?
- Without linefeed: `System.out.print (<output>)`
- With linefeed: `System.out.println (<output>)`

Examples

- ```
System.out.print("Hello, World");
System.out.print ("!"); // Output: Hello, World!
```
- ```
System.out.println ("Hello, World");
```



Thank you very much!