

LASER TEXTURE
SCANNER

AMES 9400 HD

The handheld model 9400 Laser Texture Scanner is capable of measuring both micro and macro texture accurately and efficiently. With the simple push of a button the unit automatically begins the scanning process, providing the operator with immediate and accurate texture measurements. Studies have shown an excellent correlation to the sand patch test.



AMES 9400HD

LASER TEXTURE SCANNER

SPECS:

OVERVIEW

- Calculates Mean Profile (MPD), Texture Profile Index (TPI), Estimated Texture Depth (ETD), RMS, Ra, Rq, Skewness, Kurtosis and VAR. Scanner immediately displays the results on a sunlight readable LCD display
- Data stored in simple TXR binary files that can be exported to CSV files using Ames windows-based modeling software
- Triangulation Angle at Center of Measurement Range: 22 Deg
- Collects both elevation height data and scan intensity image
- New laser sensor more accurately detects invalid reading so they can be removed from the data leaving almost spike free results
- Data Storage: 2GB internal Flash, Downloadable to a PC through an Ethernet interface
- Batteries pack consists of safe and reliable NiMH cells (Sanyo HR-AUX A).
- Product Dimensions (Width, Height, Depth): 152.4 mm x 152.4 mm x 228.4 mm



LTS9400 LINE LASER TEXTURE SCANNER SPECS

- Vertical Resolution: 0.003 mm
- Measurement Range: 30 mm
- Maximum Length Resolution: 0.00635 mm
- Maximum Width Resolution: 0.0247 mm
- Scan Area: 104.00 mm x 72.00mm
- Dot size at center of range: 25 um
- Dot size at Max and Min range: 60 um
- Max laser sampling speed: 5 KHz
- Windows software application has the ability to crop the original scans into smaller areas of interest
- Includes sun shroud to block out ambient light when performing scans outside
- Index units: Metric or Imperial
- GPS receiver: Built in 1 Hz WAAS enabled receiver
- LCD display with backlight for easy night-time viewing.
- Transport case meets carry-on baggage requirements.

TEXTURE SCAN

