

PQI↕380^{go}

Pavement Quality Indicator

Non-Nuclear
Asphalt Density Gauge

- ⌚ **Fast** - 3 Second Test. Speed That Keeps the Job Moving
- 👉 **Simple** - Easy to Use. Ready to go. Designed for Efficiency
- ✓ **Rugged** - Tough by Design. Built for the Demands of the Job
- 🏆 **Proven** - First In Non-Nuclear. Still Leading the Way



**NON-NUCLEAR
TECHNOLOGY**
No badges • No licensing



**BUILT
FOR THE FIELD**
Fast • Simple • Rugged

PQI 380^{go} Pavement Quality Indicator

Non-Nuclear Asphalt Density Gauge

 **Fast Density**  **Simple Operation**  **Rugged Design**  **Proven**

SPECS

OPERATIONAL SPECIFICATIONS:

Modes:

- Single:** Reading time less than (3) seconds.
- Continuous:** Instantaneous density readings.

Functions:

- Density, % Compaction

Calibration Modes:

- Normal:** Correlation offset to cores.

MEASUREMENT SPECIFICATIONS:

- Sensing Area:** 11 in. (27.9cm) diameter base allows optimum measurement on fine and coarse material types.
- Measurement Depth:** User selected and adjustable from .75 in. to 6 in. (19.05mm - 152.4mm)
- Measurement Display:** Density, % Compaction, Mix Name

MECHANICAL SPECIFICATIONS:

- Unit Weight:** 16.3lbs (7.39kg)
- Unit Dimensions:** 11in x 11in x 12in High (27.9cm x 27.9cm x 30.4cm) with handle extension 29in High (73.6cm)
- Shipping Weight w/Case:** 45.5lbs (20.63kg)
- Shipping Dimensions:** 24in x 19in x 16in (60.96cm x 48.26cm x 40.64cm)

ELECTRICAL SPECIFICATIONS:

- Microprocessor Controlled**
- CE Mark:** Complies with EN61000-4-2, 61000-4-3, 61000-4-8
- Battery:** 14.0 Amp-hr NiMH, 7.2volt
- Recharge Time:** 4 hours
- Battery Charger:** Self Contained CE & UL Certified Universal AC Charger, DC Charger
- Computer Ports:** 1 USB Port used for Updates and Service

OPERATIONAL FEATURES:

- Display:** 7" High-brightness capacitive touchscreen, with anti-scratch surface
- Status Bar:** Battery voltage, low battery, date and time and Mix Name on measurement screens
- Mix Details:** Stores unlimited mixes, details include (MTD, Mix Name, Stone Size, Depth, Offset, Operator Name)
- Update Software:** One touch upload of new software using a USB memory stick
- Set Time & Date:** Quick time and date setup, MM/DD/YY and DD/MM/YY formats
- Units:** Interchangeable settings for Density (kg/m³, lb/ft³), Depth (in, mm) and Stone Size (in, mm)
- Standardization:** While gauge is still in the case, a quick one touch measurement will insure the gauge is still in proper working mode
- Enhanced Customer Support:** Diagnostic screen to aid in factory support
- User Programmable Target Density:** Used for calculating % compaction
- User Changeable Battery:** Easily change battery in the field

WARRANTY:

- Standard:** 12 months

OPTIONAL ACCESSORIES:

- Stand Alone Charger & Extra Battery Packs

PQI 380go
Complies with



D7113



T343



Innovators of Non-Nuclear Density Technology

900 Albany Shaker Rd., Suite 2, Latham, NY 12110 • Phone 518-370-5558 • Toll-free 1-800-724-6306 • Fax 518-370-5538 • www.transtechsys.com

