Classical Mechanics by John R. Taylor Notes

Chris Doble

August 2023

Contents

1 Newton's Laws of Motion

1.2 Space and Time

- In cartesian coordinates the basis vectors don't depend on time so their derivatives are **0**. This means that

$$\begin{aligned}\frac{d}{dt}(x\hat{\mathbf{x}} + y\hat{\mathbf{y}} + z\hat{\mathbf{z}}) &= \frac{dx}{dt}\hat{\mathbf{x}} + x\frac{d\hat{\mathbf{x}}}{dt} + \frac{dy}{dt}\hat{\mathbf{y}} + y\frac{d\hat{\mathbf{y}}}{dt} + \frac{dz}{dt}\hat{\mathbf{z}} + z\frac{d\hat{\mathbf{z}}}{dt} \\ &= \frac{dx}{dt}\hat{\mathbf{x}} + \frac{dy}{dt}\hat{\mathbf{y}} + \frac{dz}{dt}\hat{\mathbf{z}}\end{aligned}$$

  as expected. However, in order coordinate systems (e.g. polar, spherical) the basis vectors may depend on time and their derivatives aren't **0**.

1.4 Newton's First and Second Laws; Inertial Frames

- Newton's second law $\mathbf{F} = m\mathbf{a}$ can be restated as $\mathbf{F} = \dot{\mathbf{p}}$.

- An inertial frame is one where Newton's first law holds. Typically this means the frame isn't accelerating or rotating.

1.5 The Third Law and Conservation of Momentum

- Forces that act along the line joining two objects are called **central forces**.

- The **principle of conservation of momentum** states that if the net external force $\mathbf{F}_{\text{ext}}$ on an N-particle system is zero, the system's total momentum $\mathbf{P}$ is constant.

1.7 Two-Dimensional Polar Coordinates

- In two-dimensional polar coordinates, the unit vectors $\hat{\mathbf{r}}$ and $\hat{\boldsymbol{\phi}}$ depend on position and thus time. Their derivatives are

$$\begin{aligned}\frac{d\hat{\mathbf{r}}}{dt} &= \dot{\phi}\hat{\boldsymbol{\phi}}\\ \frac{d\hat{\boldsymbol{\phi}}}{dt} &= -\dot{\phi}\hat{\mathbf{r}}.\end{aligned}$$

  Consequently, the derivatives of the position vector $\mathbf{r} = r\hat{\mathbf{r}}$ are

$$\begin{aligned}\frac{d\mathbf{r}}{dt} &= \frac{d}{dt}(r\hat{\mathbf{r}})\\ &= \dot{r}\hat{\mathbf{r}} + r\frac{d\hat{\mathbf{r}}}{dt}\\ &= \dot{r}\hat{\mathbf{r}} + r\dot{\phi}\hat{\boldsymbol{\phi}}\end{aligned}$$

  and

$$\begin{aligned}\frac{d^2\mathbf{r}}{dt^2} &= \frac{d}{dt}(\dot{r}\hat{\mathbf{r}} + r\dot{\phi}\hat{\boldsymbol{\phi}})\\ &= \ddot{r}\hat{\mathbf{r}} + \dot{r}\frac{d\hat{\mathbf{r}}}{dt} + \dot{r}\dot{\phi}\hat{\boldsymbol{\phi}} + r\ddot{\phi}\hat{\boldsymbol{\phi}} + r\dot{\phi}\frac{d\hat{\boldsymbol{\phi}}}{dt}\\ &= \ddot{r}\hat{\mathbf{r}} + \dot{r}\dot{\phi}\hat{\boldsymbol{\phi}} + \dot{r}\dot{\phi}\hat{\boldsymbol{\phi}} + r\ddot{\phi}\hat{\boldsymbol{\phi}} - r\dot{\phi}^2\hat{\mathbf{r}}\\ &= (\ddot{r} - r\dot{\phi}^2)\hat{\mathbf{r}} + (r\ddot{\phi} + 2\dot{r}\dot{\phi})\hat{\boldsymbol{\phi}}.\end{aligned}$$

- In light of the above, Newton's second law in polar coordinates can be written

$$\begin{aligned}F_r &= m(\ddot{r} - r\dot{\phi}^2)\\ F_\phi &= m(r\ddot{\phi} + 2\dot{r}\dot{\phi}).\end{aligned}$$