# University Physics with Modern Physics Electromagnetism Notes

## Chris Doble

## December 2022

## Contents

	21.1	Electric Charge	
		Conductors, Insulators, and Incuded Charges	
		Coulomb's Law	
		Electric Field and Electric Forces	
	21.5	Electric-Field Calculations	
	21.6	Electric Field Lines	
	21.7	Electric Dipoles	
22	Gauss's Law		
	22.1	Calculating Electric Flux	
	22.2	Gauss's Law	
		Applications of Gauss's Law	
	22.4	Charges on Conductors	
23	Electric Potential		
	23.1	Electric Potential Energy	
		Electric Potential	
		Equipotential Surfaces	
		Potential Gradient	
24	Сар	pacitance and Dielectrics	
	$24.\bar{1}$	Capacitors and Capacitance	

## 21 Electric Charge and Electric Field

## 21.1 Electric Charge

- $\bullet$  Electrons have a much smaller mass than neutrons and protons
- Neutrons and protons have a very similar mass

- Electrons and protons have the same magnitude of charge
- The number of protons in an atom determins its atomic number
- If an electron is added to a neutral atom it becomes a **negative ion**, if one is removed it becomes a **positive ion** this is called **ionisation**
- The **principle of conservation of charge** states that the algebraic sum of all the electric charges in any closed system is constant
- The electron or proton's magnitude of charge is a natural unit of charge
  every observable amount of electric charge is an integer multiple of this

### 21.2 Conductors, Insulators, and Incuded Charges

- Conductors pemit easy movement of charge, insulators do not
- Holding a charged object near an uncharged object causes free electrons in the latter to move away/towards the former, resulting in a net charge on either side — this is called induced charge

#### 21.3 Coulomb's Law

- The SI unit of charge is called one **coulomb** (1 C) and is defined such that  $1.602176634 \times 10^{-19}$  C is equal to the charge of an electron or proton
- Coulomb's law describes the electric force between two point charges

$$F = \frac{1}{4\pi\epsilon_0} \frac{|q_1 q_2|}{r^2}$$

where the **electric constant**  $\epsilon_0 = 8.854 \times 10^{-12} \,\mathrm{C}^2/\mathrm{N} \cdot \mathrm{m}^2$ ,  $q_1$  and  $q_2$  are the magnitudes of the charges, and r is the distance between them

- The electric force is always directed along the line between the two charges, attracting opposite charges and repelling like charges
- $\frac{1}{4\pi\epsilon_0}$  can be approximated as  $9.0 \times 10^9 \,\mathrm{N\cdot m^2/C^2}$
- The principle of superposition of forces also applies to electric charges

#### 21.4 Electric Field and Electric Forces

- The electric force on a charged object is exerted by the electric field created by other charged objects
- We can determine if there is an electric field at a point by placing a test charge  $q_0$  there and seeing if it experiences an electric force the electric field at that point (the electric force per unit charge) is then given by

$$\mathbf{E} = \frac{\mathbf{F}}{q_0}$$

• Rearranging, the force experienced by a charge  $q_0$  at a point is given by

$$\mathbf{F} = q_0 \mathbf{E}$$

- When considering an electric field produced by a point charge, the location of the point charge is called the **source point** and the location at which we're trying to determine the field is called the **field point**
- The electric field produced by a point charge is given by

$$\mathbf{E} = \frac{1}{4\pi\epsilon_0} \frac{q}{r^2} \hat{\mathbf{r}}$$

where q is the charge of the point charge, r is the distance between the source and field points, and  $\hat{\mathbf{r}}$  is the unit vector from the source to the field point

- Unlike Coulomb's law this equation doesn't use the absolute value of q meaning that the electric fields of positive charges point away from the charge, while those of negative charges point towards them
- ullet In electrostatics, the electric field inside the material of a conductor (but not holes within the material) is ullet

#### 21.5 Electric-Field Calculations

• The **principle of superposition of electric fields** states that the total electric field at a point *P* is the vector sum of the fields at *P* due to each point charge in the charge distribution

$$\mathbf{E} = \mathbf{E}_1 + \mathbf{E}_2 + \cdots$$

- For a line charge distribution the **linear charge density** is represented by  $\lambda$  (the charge per unit length, measured in C/m)
- For a surface charge distribution the surface charge density is represented by  $\sigma$  (the charge per unit area, measured in C/m<sup>2</sup>)
- For a volume charge distribution the volume charge density is represented by  $\rho$  (the charge per unit volume, measured in C/m<sup>3</sup>)
- The electric field of an infinitely long line charge along the y-axis is

$$E = \frac{\lambda}{2\pi\epsilon_0 r}$$

#### 21.6 Electric Field Lines

- An **electric field line** is a line drawn through space such that its tangent at any point is in the direction of the electric field vector at that point
- Fewer lines are drawn in areas where the electric field is weak and more lines are drawn in areas where it's strong

#### 21.7 Electric Dipoles

- An **electric dipole** is a pair of point charges of equal magnitude q and opposite sign separated by a distance d
- ullet The net force on an electric dipole in a uniform electric field is  $oldsymbol{0}$
- The **electric dipole moment p** of an electric dipole is a vector directed from the negative charge to the positive charge with magnitude qd
- The net torque on an electric dipole in a uniform electric field is  $\mathbf{p} \times \mathbf{E}$  or  $qEd\sin\phi$  where  $\phi$  is the angle between the electric dipole and the electric field
- The potential energy of an electric dipole in a uniform electric field is

$$U = -\mathbf{p} \cdot \mathbf{E}$$

#### 22 Gauss's Law

## 22.1 Calculating Electric Flux

 $\bullet$  The electric flux of a uniform electric field through a flat surface A is

$$\Phi_E = \mathbf{E} \cdot \mathbf{A}$$

where  $\mathbf{A}$  is normal to A and has a magnitude equal to its area

 $\bullet$  The electric flux of a nonuniform electric field through a curved surface A is

$$\Phi_E = \int \mathbf{E} \cdot \mathbf{dA}$$

#### 22.2 Gauss's Law

• Gauss's law states that the total electric flux through a closed surface is equal to the total electric charge enclosed by the surface divided by  $\epsilon_0$ 

$$\Phi_E = \oint \mathbf{E} \cdot \mathbf{dA} = rac{Q_{ ext{enc}}}{\epsilon_0}$$

## 22.3 Applications of Gauss's Law

- Gauss's law can be used in two ways:
  - If we know the charge distribution and it has enough symmetry to let us evaluate the integral in Gauss's law, we can find the field
  - If we know the field, we can use Gauss's law to find the charge distribution

- Under electrostatics, excess charge always lies of the surface of a conductor
- The electric field of an infinite line charge is

$$\mathbf{E} = \frac{1}{4\pi\epsilon_0} \frac{2\lambda}{r} \hat{\mathbf{r}}$$

#### 22.4 Charges on Conductors

- If there is excess charge at rest on a conductor, all of that charge must lie on the surface of the conductor and the electric field inside the conductor must be zero. If there is a cavity inside the conductor, the net charge on the cavity walls equals the amount of charge enclosed by the cavity
- Charges outside a conductor have no effect on the interior of the conductor, even if it has a cavity inside this is why Faraday cages work
- At the surface of a conductor, the component of the electric field that is perpendicular to the surface is

$$E_{\perp} = \frac{\sigma}{\epsilon_0}$$

#### 23 Electric Potential

#### 23.1 Electric Potential Energy

• The electric potential energy of two point charges is

$$U = \frac{1}{4\pi\epsilon_0} \frac{q_1 q_2}{r}$$

• The electric potential energy of a point charge  $q_0$  and a collection of charges  $q_1, q_2$ , etc. is

$$U = \frac{q_0}{4\pi\epsilon_0} \left( \frac{q_1}{r_1} + \frac{q_2}{r_2} + \cdots \right) = \frac{q_0}{4\pi\epsilon_0} \sum_i \frac{q_i}{r_i}$$

- For every electric field due to a static charge distribution, the force exterted by that field is conservative
- The total electric potential energy of a collection of charges  $q_1$ ,  $q_2$ , etc. is

$$U = \frac{1}{4\pi\epsilon_0} \sum_{i < j} \frac{q_i q_j}{r_{ij}}$$

where  $r_{ij}$  is the distance between  $q_i$  and  $q_j$ 

#### 23.2 Electric Potential

- Potential is potential energy per unit charge
- The unit of potential is the **volt**, equal to 1 joule per coulomb
- The potential difference between two points  $V_{ab} = V_a V_b$  is called the potential of a with respect to b and equals the amount of work done by the electric force when a unit (1 C) of charge moves from a to b
- The electric potential due to a point charge is

$$V = \frac{1}{4\pi\epsilon_0} \frac{q}{r}$$

• The electric potential due to a collection of point charges is

$$V = \frac{1}{4\pi\epsilon_0} \sum_{i} \frac{q_i}{r_i}$$

• The electric potential due to a continuous charge distribution is

$$V = \frac{1}{4\pi\epsilon_0} \int \frac{dq}{r}$$

• The electric potential difference between two points is given by

$$V_a - V_b = \int_a^b \mathbf{E} \cdot d\mathbf{l} = \int_a^b E \cos \phi \, dl$$

- Positive charges tend to "fall" from high- to low-potential regions while negative charges do the opposite
- When a particle with charge  $e = 1.602 \times 10^{-19} \,\mathrm{C}$  moves between two points with a potential difference of  $1 \,\mathrm{V} = 1 \,\mathrm{J/C}$  the change in energy is  $U_a U_b = q V_{ab} = (1.602 \times 10^{-19} \,\mathrm{C})(1 \,\mathrm{J/C}) = 1.602 \times 10^{-19} \,\mathrm{J}$  which is called 1 **electron volt**

#### 23.4 Equipotential Surfaces

- An **equipotential surface** is a three-dimensional surface on which the electric potential is the same at every point
- Because electric potential energy doesn't change as a test charge moves over an equipotential surface, the electric field can do no work and thus field lines and equipotential surfaces are always perpendicular
- When all charges are at rest, the surface of a conductor is an equipotential surface
- When all charges are at rest, the entire solid volume of a conductor is at the same potential

#### 23.5 Potential Gradient

• The relationship between  $\mathbf{E}$  and V is given by

$$\mathbf{E} = -\nabla V = -\left(\frac{\partial V}{\partial x}\hat{\mathbf{i}} + \frac{\partial V}{\partial y}\hat{\mathbf{j}} + \frac{\partial V}{\partial z}\hat{\mathbf{k}}\right)$$

• If E has a radial component  $E_r$  with respect to an axis or a point and r is the distance from that axis or point, then

$$E_r = -\frac{\partial V}{\partial r}$$

## 24 Capacitance and Dielectrics

## 24.1 Capacitors and Capacitance

- Any two conductors separated by an insulator (or a vacuum) form a **capacitor**
- The capacitance of a capacitor measures its ability to store charge

$$C = \frac{Q}{V_{AB}}$$

• Capacitance is measured in farads where

$$1 \, \mathrm{F} = 1 \, \mathrm{C/V}$$

• The capacitance of a parallel plate capacitor in a vacuum is

$$C = \epsilon_0 \frac{A}{d}$$