

HANAChecker – SAP Note 1999993



SAP Note 1999993 presents a tool that runs the mini-checks (SAP Note 1969700) and sends out emails in case of potential critical issues

1999993 - How-To: Interpreting SAP HANA Mini Check Results

- It is a python script to be downloaded from
<https://github.com/chriselswede/hanachecker>
- It is intended to be executed as <sid>adm on your SAP HANA Server
- It connects via host, port and DB user, provided in hdbuserstore
- It sends out emails via an intern smtp server (to avoid firewall issues) with xmail

A screenshot of a GitHub repository page for 'hanachecker'. The URL at the top is <https://github.com/chriselswede/hanachecker>. Below the URL, there's a file list:

- chriselswede Add files via upload
- README.md
- hanachecker.pdf
- hanachecker.py** (this file is highlighted with a red arrow)
- hanachecker_configurationfile_example.txt

NOTE: You have to install the linux program "sendmail" and add a line similar to DSsmtp.intra.ourcompany.com in the file sendmail.cf in /etc/mail/, see [this page](#)

HANAChecker – using hdbuserstore



Host, port and DB user needs to be provided in the hdbuserstore:

```
hsiadm@dewdfglp00835:/> hdbuserstore SET HANACHECKER1KEY dewdfglp00835:30015 HANACHECKER1 Password1
hsiadm@dewdfglp00835:/> hdbuserstore LIST
DATA FILE      : /usr/sap/HCI/home/.hdb/dewdfglp00835/SSFS_HDB.DAT
KEY FILE       : /usr/sap/HCI/home/.hdb/dewdfglp00835/SSFS_HDB.KEY

KEY HANACHECKER1KEY
  ENV : dewdfglp00835:30015
  USER: HANACHECKER1
```

Then the hanachecker can connect using the info stored in hdbuserstore:

```
hsiadm@dewdfglp00835:/tmp/HANAChecker> whoami
hsiadm
hsiadm@dewdfglp00835:/tmp/HANAChecker> python hanachecker.py -k HANACHECKER1KEY -ff hanachecker_configurationfile.txt
"Mini Check ID 235 Description: Hosts with varying physical memory size Host: Value: yes Expectation: no Potential Impact: None"
```

HANAChecker – needs privileges



The DB user that hanachecker uses to connect with needs proper privileges to run the mini-checks

The DB user that hanachecker uses only needs to read in the statistics server tables

User Name*: Disable ODBC/JDBC access

Authentication

Password
Password*: Confirm*:

Granted Roles		System Privileges	Object Privileges	Analytic Privileges	Package Privileges
Role		Grantor			
MONITORING		SYSTEM			
PUBLIC		SYS			

HANAChecker – Input 1969700 ZIP File



HANAChecker can take the SQLStatements.zip file as input

- The .zip file has to be downloaded from SAP Note [1969700](#)
- HANAChecker will use the corresponding check files based on your HANA revision

Flag	Details	Explanation	Default
-zf	Full path to SQLStatements.zip	Full path of the SQLStatements.zip file (SAP Note 1969700). Cannot be used together with -mf and must be used together with -ct	"
-ct	Check Types	M = Mini-Checks, I = Internal Mini-Checks, S = Security Mini-Checks, T = Trace Mini-Checks, P = Parameter Checks (see some slides below), C = Call Stacks Mini-Checks (see some slides below), R = SQL Recommendations (see some slides below), A = ABAP Mini-Checks (see some slides below)	"

Example:

```
xscadm@atgvm1s866:/tmp/HANAChecker> python hanachecker.py -zf SQLStatements.zip
-ct M,S -M0551 christian.hansen01@sap.com -M0712 chriselswede@gmail.com -S0120
christian.hansen01@sap.com -k T1KEY
"
Mini Check ID M0712 Description: Internal statistics server errors (last day)
Value: 334 Expectation: 0 C: X SAPNote: 2147247" is sent to chriselswede@gmail.com
"
Mini Check ID M0551 Description: Proper setup of timezone table TTZZ Value: n
o Expectation: yes C: X SAPNote: 1791342" is sent to christian.hansen01@sap.
com
"
Mini Check ID S0120 Description: SYSTEM user deactivated Value: no Expectati
on: yes C: X" is sent to christian.hansen01@sap.com
```

One of the emails:

HANAChecker: Potential Critical Situation(s) @XSC!



SAP HANA Database System Administrator <xscadm@atgvm1s866.
To ✓ Hansen, Christian

Mini Check ID M0551 Description: Proper setup of timezone table TTZZ
Value: no Expectation: yes C: X SAPNote: 1791342

HANAChecker – Input Mini-Check File (not needed)



HANAChecker takes a mini-check SQL statement file as input (Note: -mf not needed if you use -zf and -ct)

- Note: Always use the mini-check file that corresponds to your SAP HANA Revision and download these files regularly from SAP Note [1969700](#) to always have the latest versions, as SAP Note [1969700](#) is being updated frequently

Flag	Details	Explanation	Default
-mf	mini-check file	Full path of the mini-check file (Cannot be used together with -zf)	"
Possible Files:			
	HANA_Configuration_MiniChecks_<revision>.txt		XXXXX M0231
	HANA_Configuration_MiniChecks_Internal_<revision>.txt		XXXXX I0076
	HANA_Security_MiniChecks.txt		XXXXX S1045
	HANA_TraceFiles_MiniChecks.txt		XXXXX T1200
	HANA_Configuration_Parameters_<revision>.txt (see some slides below)		
	HANA_Threads_Callstacks_MiniChecks_<revision>.txt (see some slides below)		XXXXX C1013
	HANA_SQL_SQLCache_TopLists_<revision>.txt (see some slides below)		
	HANA_ABAP_MiniChecks.txt (see some slides below)		XXXXX A0510

Example:

```
mo-fc8d991e0:/tmp/HANAChecker> python hanachecker.py
-mf HANA Configuration MiniChecks 1.00.120+.txt -en c
hris@comp.com,smtp.comp.com -M1.115 chris@du.my
```

HANAChecker – Email Notification



HANAChecker sends out emails for all critical mini-checks

The HANAChecker executes the mini-checks and sends out emails for every mini-check that are “Potential Critical”, i.e. for each check where the column “C” is “X”

For this to work an email client, e.g. mailx (see [this page](#) for more information), mail, or mutt, must have been set up and configured (e.g. the sender's email and the internal smtp email server)

In HANAChecker this can be controlled with the following flags:

Flag	Details	Explanation	Default	
-en	email client	For example mail, mailx, mutt, ...	mailx	
-ens	sender's email	To explicitly specify sender's email address	"	(configured is used)
-enm	mail server	To explicitly specify the internal smtp email server	"	(configured is used)

Test:

```
echo -e "$(date)\\n$(hostname)\\n\\nTEST" | mailx -s "TEST mailx" <your email address>
```

sends you an email, then the above flags are not needed when running HANAChecker, e.g.:

```
xscadm@atgvmls866:/tmp> echo -e "$(date)\\n$(hostname)\\n\\nTEST" | mailx -s "TEST mailx" christian.hansen01@sap.com
```



TEST mailx
 SAP HANA Database
 To  Hansen, Christian
 Wed Jul 28 16:44:00 CEST 2021
 atgvmls866
 TEST

HANAChecker – Email Mapping



HANAChecker sends out emails to the addresses mapped for the mini-checks

If the flag -<CHID> is specified for a email address and the mini-check with that check id (CHID) is potential critical then an email is send to that email address

Flag	Unit	Details	Explanation	Default
-<CHID>		mini-check to email address	If that particular mini-check specified by the flag is potential critical an email is sent to the addresses specified by the value of the flag	

Example (mini-checks):

```
mo-fc8d991e0:/tmp/HANAChecker> python hanachecker.py -mf HANA_Configuration_Minichecks_1.00.120+.txt
-en chris@comp.com,smtp.intra.comp.com -M1142 chris@du.my -M1150 per@du.my,lena@du.my

"Mini Check ID M1142 Description: Table(s) using > 10 % of SQL cache Host: mo-fc8d991e0 Value: 2
Expectation: 0 C: X SAPNote: 2124112" is sent to chris@du.my
"Mini Check ID M1150 Description: Pinned statements in SQL cache (%) Host: mo-fc8d991e0 Value: 27
.83 Expectation: <= 20.00 C: X SAPNote: 2124112" is sent to per@du.my
"Mini Check ID M1150 Description: Pinned statements in SQL cache (%) Host: mo-fc8d991e0 Value: 27
.83 Expectation: <= 20.00 C: X SAPNote: 2124112" is sent to lena@du.my
```

Example (security mini-checks):

```
mo-fc8d991e0:/tmp/HANAChecker> python hanachecker.py -mf HANA_Security_Minichecks.txt -en chris@comp.
com,smtp.intra.comp.com -S0120 lena@du.my

"Mini Check ID S0120 Description: SYSTEM user deactivated Value: no Expectation: yes C: X" is sent to lena@du.my
```

HANAChecker – Only One Email



HANAChecker can be told to only send one email per email address

The `-oe` flag tells HANAChecker that if one email address is supposed to get notified by many mini-check warnings, they are sent in only one email

Flag	Unit	Details	Explanation	Default
<code>-oe</code>		one email per address	true: only one email is sent per email address, false: one email is sent per critical mini check	false

Example: Here `lena@du.my` gets only one email, including warnings from mini-check M1142, and M1150

```
mo-fc8d991e0:/tmp/HANAChecker> python hanachecker.py -mf HANA_Configuration_MiniChecks_1.00.120+.txt -en chris@comp.com,smtp.intra.comp.com -M1142 lena@du.my -M1150 lena@du.my -oe true

"Mini Check ID M1142 Description: Table(s) using > 10 % of SQL cache Host: mo-fc8d991e0 Value: 2 Expectation: 0 C: X SAPNote: 2124112
Mini Check ID M1150 Description: Pinned statements in SQL cache (%) Host: mo-fc8d991e0 Value: 27.28 Expectation: <= 20.00 C: X SAPNote: 2124112" is sent to lena@du.my
```

HANAChecker – Always Send a Notification Email



HANAChecker can send an email to all unique email addresses even if none of the mini-checks for those addresses seemed critical – just to notify that HANAChecker was executed

Flag	Unit	Details	Explanation	Default
-as		always send at least a notification email	true: all email addresses will be send at least a notification email, even if none of the mini-checks assigned to the emails were potential critical	false

Example: Here all emails, chris@du.my, [lena@du.my](#), and [per@du.my](#), gets the notification email. Note that Per also get the notification email so he will know that the HANAChecker ran even though none of his mini-checks were critical.

```
oqladm@ls80010:/tmp/HANAChecker> python hanachecker.py -zf SQLStatements.zip -ct M -en chris@comp.com,smtp.intra.comp.com
-M1142 chris@du.my,lena@du.my -M1150 per@du.my,lena@du.my -as true
"HANACecker was executed 2018-06-08 21:42:22 on OQL. If any of the mini-checks that you are responsible for seem critical,
you will be notified now." is sent to lena@du.my ←
"Mini Check ID M1142 Description: Table(s) using > 10 % of SQL cache Host: ls80010 Value: 1 Expectation: 0 C: X SAPN
ote: 2124112" is sent to lena@du.my
"HANACecker was executed 2018-06-08 21:42:22 on OQL. If any of the mini-checks that you are responsible for seem critical,
you will be notified now." is sent to per@du.my ←
"HANACecker was executed 2018-06-08 21:42:22 on OQL. If any of the mini-checks that you are responsible for seem critical,
you will be notified now." is sent to chris@du.my ←
"Mini Check ID M1142 Description: Table(s) using > 10 % of SQL cache Host: ls80010 Value: 1 Expectation: 0 C: X SAPN
ote: 2124112" is sent to chris@du.my
```

HANAChecker – Always Send One Email



If both the **-as** and the **-oe** flags are set to true then all email addresses get one email and one email only; the email includes always the notification that HANAChecker ran and then, if any of the mini-checks were critical, those mini-check notifications will follow

Example: Here all email addresses, chris@du.my, lena@du.my, and per@du.my, get one email

```
oqladm@ls80010:/tmp/HANAChecker> python hanachecker.py -zf SQLStatements.zip -ct M -en chris@comp.com,smtp.intra.comp.com -M1142 chris@du.my,lena@du.my -M1150 per@du.my,lena@du.my -as true -oe true
"HANACecker was executed 2018-06-08 21:44:40 on OQL. If any of the mini-checks that you are responsible for seem critical, you will be notified now.
Mini Check ID M1142 Description: Table(s) using > 10 % of SQL cache Host: ls80010 Value: 1 Expectation: 0 C: X SAPNote: 2124112" is sent to lena@du.my
"HANACecker was executed 2018-06-08 21:44:40 on OQL. If any of the mini-checks that you are responsible for seem critical, you will be notified now." is sent to per@du.my
"HANACecker was executed 2018-06-08 21:44:40 on OQL. If any of the mini-checks that you are responsible for seem critical, you will be notified now.
Mini Check ID M1142 Description: Table(s) using > 10 % of SQL cache Host: ls80010 Value: 1 Expectation: 0 C: X SAPNote: 2124112" is sent to chris@du.mv
```

HANAChecker – Email Grouping



HANAChecker sends out emails to the addresses grouped for the checks

The flag `-cg` can specify ranges of mini-checks and map an email address for each of these ranges

Flag	Unit	Details	Explanation	Default
<code>-cg</code>		mini-check groups	Groupings of mini-checks with responsible email addresses associated	

Example: Here lena@du.my gets emails for every potential critical mini-check between M1140 and M1149 and chris@du.my gets emails for every potential critical mini-check between M1150 and M1159

```
mo-fc8d991e0:/tmp/HANAChecker> python hanachecker.py -mf HANA_Configuration_MiniChecks_1.00.120+.txt -en chris@comp.com,smtp.intra.comp.com -cg M1140-M1149,lena@du.my,M1150-M1159,chris@du.my

"Mini Check ID M1150  Description: Pinned statements in SQL cache (%)  Host: mo-fc8d991e0  Value: 27.28  Expectation: <= 20.00  C: X  SAPNote: 2124112" is sent to chris@du.my
"Mini Check ID M1142  Description: Table(s) using > 10 % of SQL cache  Host: mo-fc8d991e0  Value: 2  Expectation: 0  C: X  SAPNote: 2124112" is sent to lena@du.my
```

HANAChecker – Parameter Email (1/3)



HANAChecker sends out emails to the addresses listed after the flag -pe if there are parameters mentioned by HANA_Configuration_Parameters (SAP Note 1969700)

Flag	Unit	Details	Explanation	Default
-pe		parameter emails	a comma seperated list of emails that catches all parameter checks, this only makes sense if HANA_Configuration_Parameters is included in the input, either with -mf, or -ct P	not used
-is	true/false	ignore check_why_set	parameters that have been set without that there is any recommended value, will be ignored	false

Example: Here per@al.com gets emails for every potential critical parameter issue and if M0208 is potential critical:

```
pqladm@atgls90010:/tmp/HANAChecker> python hanachecker.py -zf SQLStatements.zip -ct M,P
-pe per@al.com -M0208 per@al.com -oe true -k TCHECK
"
Mini Check ID M0208 Description: Supported operating system Host: atgls90010 Value: n
o (SUSE Linux Enterprise Server 12 SP3) Expectation: yes C: X SAPNote: 2235581

Parameter 'global auditing state' in configuration file 'global.ini' and in section 'aud
iting configuration' has an internal default value, is not configured, but the recommend
ation is 'true'. For more information see SAP Note 863362. This has priority 2.
Following scenario has been taken into account:
Revision: 2.00.036 Environment: ABAP,ERP,ESS,MDCTEN,SDA,SINGLE,SYSREP,AUD,XFS

Parameter 'default statement concurrency limit' in configuration file 'global.ini' and i
n section 'execution' has default value '0', is not configured, but the recommendation i
s '16 to 40'. For more information see SAP Note 2222250. This has priority 1.
Following scenario has been taken into account:
Revision: 2.00.036 Environment: ABAP,ERP,ESS,MDCTEN,SDA,SINGLE,SYSREP,AUD,XFS CpuThrea
ds: 80
```

HANAChecker – Parameter Email (2/3)



Example: Here chris@dum.com gets emails for every potential critical SAP HANA Parameter issue. We also see that some parameter checked specific scenario, that can be changed in the Modification Section in SQL: HANA_Configuration_Parameters (see also next slide).

```
pqladm@atgls90010:/tmp/HANAChecker> python hanachecker.py -zf SQLStatements.zip -ct P -oe true -pe chris@dum.com -k TCHECK
"
Parameter 'global_auditing_state' in configuration file 'global.ini' and in section 'auditing configuration' has an internal default value, is not configured, but the recommendation is 'true'. For more information see SAP Note 863362. This has priority 2.
Following scenario has been taken into account:
Revision: 2.00.036 Environment: ABAP,ERP,ESS,MDCTEN,SDA,SINGLE,SYSREP,AUD,XFS

Parameter 'default_statement_concurrency_limit' in configuration file 'global.ini' and in section 'execution' has default value '0', is not configured, but the recommendation is '16 to 40'. For more information see SAP Note 2222250. This has priority 1.
Following scenario has been taken into account:
Revision: 2.00.036 Environment: ABAP,ERP,ESS,MDCTEN,SDA,SINGLE,SYSREP,AUD,XFS CpuThreads: 80 →
Parameter 'log_backup_timeout_s' in configuration file 'global.ini' and in section 'persistence' has default value '7200', is not configured, but the recommendation is '300 to 3600'. For more information see SAP Note 1645183. This has priority 3.
Following scenario has been taken into account:
Revision: 2.00.036 Environment: ABAP,ERP,ESS,MDCTEN,SDA,SINGLE,SYSREP,AUD,XFS

Parameter 'logshipping_max_retention_size' in configuration file 'global.ini' and in section 'system replication' has default value '1048576', is not configured, but the recommendation is '0 to 656384'. For more information see SAP Note 2526877 . This has priority 3.
Following scenario has been taken into account:
Revision: 2.00.036 Environment: ABAP,ERP,ESS,MDCTEN,SDA,SINGLE,SYSREP,AUD,XFS LogVolumeSize: 801 →
```

HANAChecker – Parameter Email (3/3)



Example: Here per@al.com gets emails for every potential critical SAP HANA Parameter issue. Here SQL: HANA_Configuration_Parameters was changed in the Modification Section (number CPU_THREADS was changed to 50), and the changed version was given as input to the –mf flag:

```
pqladm@atgls90010:/tmp/HANAChecker> python hanachecker.py -mf HANA_Configuration_Parameters_cpu50.txt -pe per@al.com
-oe true -k TCHECK
"
Parameter 'global_auditing_state' in configuration file 'global.ini' and in section 'auditing configuration' has an i
nternal default value, is not configured, but the recommendation is 'true'. For more information see SAP Note 863362.
This has priority 2.
Following scenario has been taken into account:
Revision: 2.00.036 Environment: ABAP,ERP,ESS,MDCTEN,SDA,SINGLE,SYSREP,AUD,XFS

Parameter 'default_statement_concurrency_limit' in configuration file 'global.ini' and in section 'execution' has def
ault value '0', is not configured, but the recommendation is '15 to 25'. For more information see SAP Note 2222250. T
his has priority 1.
Following scenario has been taken into account:
Revision: 2.00.036 Environment: ABAP,ERP,ESS,MDCTEN,SDA,SINGLE,SYSREP,AUD,XFS CpuThreads: 50 (manual) →

Parameter 'max_concurrency' in configuration file 'global.ini' and in section 'execution' has default value '0', is n
ot configured, but the recommendation is '50'. For more information see SAP Note 2222250. This has priority 1.
Following scenario has been taken into account:
Revision: 2.00.036 Environment: ABAP,ERP,ESS,MDCTEN,SDA,SINGLE,SYSREP,AUD,XFS CpuThreads: 50 (manual) →

Parameter 'log backup timeout s' in configuration file 'global.ini' and in section 'persistence' has default value '7
```

HANAChecker – Call Stacks Mini Checks



HANAChecker also covers the call stacks mini checks: -ct C

The default value in the modification section of active threads limit, 0.2, is normally fine, but it is possible to change it with the -at flag

Flag	Details	Explanation	Default
-at	active threads	this sets MIN_ACTIVE_THREADS in modification section	(not used, i.e. default value in modification section 0.2 is used)

Example: Here chris@me.com gets emails for all potential critical call stacks mini-checks that have more than 0.01 average active threads

```
hsiadm@atgvm1s7071:/tmp/HANAChecker> python hanachecker.py -zf SQLStatements.zip -ct C -ca chris@me.com -en chris@comp.com,smtp.intra.comp.com -k T1SYSKEY -at 0.01
"
Mini Check ID C1013 Area: Locks Description: Futex lock wait Host: atgvm1s7071 Port: 30003 Count: 21 Active Threads: 0.0104 LastOccurrence: 2021/03/16 08:13:27 C: X SAPNote: 1999998 TraceText: ptime::Futex::lock" is sent to chris@me.com
"
Mini Check ID C1020 Area: Locks Description: Unlocking of mutex Host: atgvm1s7071 Port: 30003 Count: 31 Active Threads: 0.0153 LastOccurrence: 2021/03/16 00:23:27 C: X SAPNote: 1999998 TraceText: Synchronization::Mutex::unlock" is sent to chris@me.com
```

Example: Here chris@me.com gets an email if C1013 is potential critical and has more than 0.01 average active threads

```
hsiadm@atgvm1s7071:/tmp/HANAChecker> python hanachecker.py -zf SQLStatements.zip -ct C -C1013 chris@me.com -en chris@comp.com,smtp.intra.comp.com -k T1SYSKEY -at 0.01
"
Mini Check ID C1013 Area: Locks Description: Futex lock wait Host: atgvm1s7071 Port: 30003 Count: 21 Active Threads: 0.0104 LastOccurrence: 2021/03/16 08:13:27 C: X SAPNote: 1999998 TraceText: ptime::Futex::lock" is sent to chris@me.com
```

HANAChecker – SQL Recommendations



HANAChecker sends out emails to the addresses listed after the flag -se if there are recommendations in SAP Note 2000002 for the SQL statements given in the output of HANA_SQL_SQLCache_TopLists

Flag	Details	Explanation	Default
-se	sql emails	a comma seperated list of emails that catches all sql statements with recommendation in SAP Note 2000002, this only makes sense if HANA_SQL_SQLCache_TopLists is included in the input, either with -mf, or -ct R	not used

Example: Here chris@me.com gets emails for every SQL statement with recommendations:

```
hsiadm@atgvm1s7071:/tmp/HANAChecker> python hanachecker.py -zf SQLStatements.zip -ct R -se chris@me.com -en chris@comp.com,smtp.intra.comp.com -k T1SYSKEY
"
SQL statement d6fd6678833f9a2e25e7b53239c50e9a is one of the most expensive statements in the SQL cache and there is a recommendation available in SAP Note 2000002.
This SQL statement is of type CA, originates from Statistics server, and executed by the Row engine." is sent to chris@me.com
"
SQL statement 430c496e0fe15c0353c80de1c72caab1 is one of the most expensive statements in the SQL cache and there is a recommendation available in SAP Note 2000002.
This SQL statement is of type SE, originates from Statistics server, and executed by the Row engine." is sent to chris@me.com
"
SQL statement d3759ce6047b78f61d5fc3be392d0336 is one of the most expensive statements in the SQL cache and th
```

HANAChecker – Different Emails Example



Example: Here chris@me.com gets emails for every SQL statement with recommendation, lina@me.com gets emails for some call stacks mini-checks, peter@me.com gets emails for some security mini-checks and ole@me.com gets emails for all configuration parameters that do not follow the recommendations.

```
hsiadm@atgvm1s7071:/tmp/HANAChecker> python hanachecker.py -zf SQLStatements.zip -ct R,C,S,P -se chris@me.com  
-cg C1000-C2000,lina@me.com,S0100-S0300,peter@me.com -pe ole@me.com -at 0.01 -en chris@comp.com,smtp.intra.com  
p.com -k T1SYSKEY  
"  
Mini Check ID S0120 Description: SYSTEM user deactivated Value: no Expectation: yes C: X" is sent to peter@me.com
```

```
Mini Check ID C1020 Area: Locks Description: Unlocking of mutex Host: atgvm1s7071 Port: 30003 Count: 30  
Active Threads: 0.0148 LastOccurrence: 2021/03/17 05:08:27 C: X SAPNote: 1999998 TraceText: Synchronization::Mutex::unlock" is sent to lina@me.com
```

```
SQL statement d6fd6678833f9a2e25e7b53239c50e9a is one of the most expensive statements in the SQL cache and there is a recommendation available in SAP Note 2000002.  
This SQL statement is of type CA, originates from Statistics server, and executed by the Row engine." is sent to chris@me.com
```

```
Parameter 'service_thread_sampling_monitor_enabled' in configuration file 'global.ini' and in section 'resource_tracking' has default value 'false', is configured to 'true' in ALTER SYSTEM ALTER CONFIGURATION ('global.ini', 'SYSTEM') SET ('resource_tracking', 'service_thread_sampling_monitor_enabled') = 'true' WITH RECONFIGURE; layer, but the recommendation is '2114710'. For more information see SAP Note DEFAULT. This has priority 2.  
Following scenario has been taken into account:  
Revision: 2.00.053 Environment: ABAP,ESS,LCACHE,MDCTEN,MULTI,PROD,SCM" is sent to ole@me.com
```

HANAChecker – ABAP Mini Checks



HANAChecker also covers the ABAP mini checks: -ct A

The ABAP schema must be specified

Flag	Details	Explanation	Default
-abs	ABAP schema	this sets the ABAP schema before HANA_ABAP_MiniChecks.txt is executed	(not set → it must be set)

Example: Here chris@me.com gets emails for all potential critical ABAP mini-checks

```
oqladm@ls80010:/tmp/HANAChecker> python hanachecker.py -zf SQLStatements.zip -ct A -abs SAPQH1 -ca chris@me.com
-en chris@comp.com,smtp.intra.comp.com -k SYSTEMKEY
"
Mini Check ID A0510  Description: Parameter: dbs/hdb/cmd_buffersize  Value: wrong (1048576 instead of 2097152 to
10485760)  Expectation: like 'okay%'  C: X  SAPNote: 2600030" is sent to chris@me.com
"
Mini Check ID A0520  Description: Parameter: rsdb/tbi_buffer_area_MB  Value: wrong (192 instead of >= 1000)  Exp
ection: like 'okay%'  C: X  SAPNote: 2600030" is sent to chris@me.com
"
Mini Check ID A0521  Description: Parameter: rsdb/tbi_dir_entries  Value: wrong (13200 instead of >= 20000)  Exp
ection: like 'okay%'  C: X  SAPNote: 2600030" is sent to chris@me.com
"
Mini Check ID A0900  Description: SQLM activated  Value: no  Expectation: yes  C: X  SAPNote: 1885926" is sent t
o chris@me.com
"
Mini Check ID A1702  Description: System change option set to modifiable  Value: yes  Expectation: no  C: X" is
sent to chris@me.com
```

HANAChecker – Another Different Emails Example



Example: Here chris@me.com gets an email if A0510 is potential critical, john@me.com gets email an email if T9000 is potential critical, sue@me.com gets an email if M1220 is potential critical, and mila@me.com gets an email if S0120 is potential critical.

```
oqladm@ls80010:/tmp/HANAChecker> python hanachecker.py -zf SQLstatements.zip -ct M,S,T,A -abs SAPQH1 -A0510 chris@me.com
-T9000 john@me.com -M1220 sue@me.com -S0120 mila@me.com -en chris@comp.com,smtp.intra.comp.com -k SYSTEMKEY
"
Mini Check ID T9000 Area: General Description: Max. trace lines per hour Host: ls80010 Port: 30003 Count: 10715 Last occurrence: 2021/03/20 02:00:00 C: X SAPNote: 2380176" is sent to john@me.com
"
Mini Check ID A0510 Description: Parameter: dbs/hdb/cmd_buffersize Value: wrong (1048576 instead of 2097152 to 10485760) Expectation: like 'okay%' C: X SAPNote: 2600030" is sent to chris@me.com
"
Mini Check ID S0120 Description: SYSTEM user deactivated Value: no Expectation: yes C: X" is sent to mila@me.com
"
Mini Check ID M1220 Description: QCM conversion tables Value: 1 Expectation: 0 C: X SAPNote: 9385" is sent to sue@me.com
```

HANAChecker – Catch All



HANAChecker can send out emails for all potential critical checks to the emails defined as “catch all” emails

Flag	Unit	Details	Explanation	Default
-ca		catch all emails	The email addresses specified receive an email about each potential critical mini-check and parameter check	

Example:

```
mo-fc8d991e0:/tmp/HANAChecker> python hanachecker.py -mf HANA_Configuration_MiniChecks_1.00.120+.txt -en chris@comp.com,smtp.intra.comp.com -ca peter@du.my,chris@du.my

"Mini Check ID M0012 Description: Revision level Value: 121.00 Expectation: >= 122.03 C: X SAPNote: 2021789" is sent to chris@du.my
"Mini Check ID M0115 Description: Service startup time variation (s) Host: mo-fc8d991e0 Value: 3299447 Expectation: <= 600 C: X SAPNote: 2177064" is sent to chris@du.my
...
"Mini Check ID M0012 Description: Revision level Value: 121.00 Expectation: >= 122.03 C: X SAPNote: 2021789" is sent to peter@du.my
"Mini Check ID M0115 Description: Service startup time variation (s) Host: mo-fc8d991e0 Value: 3299447 Expectation: <= 600 C: X SAPNote: 2177064" is sent to peter@du.my
...
```

HANAChecker – Ignore Checks



While using the “Catch All” flag, you can “Ignore” some checks with the **-ic** flag, i.e. catch all except some checks

Example:

Flag	Unit	Details	Explanation	Default
-ic		ignore checks	A list of mini-check CHIDs to be ignored by the catch all emails	

Example:

```
mo-fc8d991e0:/tmp/HANAChecker> python hanachecker.py -mf HANA_Configuration_MinChecks
_1.00.120+.txt -en chris@comp.com,smtp.intra.comp.com -ca chris@du.my -ic M0012,M0209
"Mini Check ID M0115 Description: Service startup time variation (s) Host: mo-fc8d99
1e0 Value: 3299447 Expectation: <= 600 C: X SAPNote: 2177064" is sent to chris@du.
my
"Mini Check ID M0551 Description: Proper setup of timezone table TTZZ Value: no Exp
ectation: yes C: X SAPNote: 1791342" is sent to chris@du.my
```

...

HANAChecker – Different Check Types



One can define different mini-check files with the -mf flag and assign different mini-check types to emails, e.g.

```
-mf <mini-check file>,<security-mini-check file>,...  
-cg M0100-M0200,email1@comp.com,S0100-S0200,email2@comp.com
```

Example:

```
mo-fc8d991e0:/tmp/HANAChecker> python hanachecker.py -mf HANA_Configuration_MiniChecks_1.00.120+.txt  
,HANA_Configuration_MiniChecks_Internal_1.00.120-1.00.122.99.txt,HANA_Security_MiniChecks.txt,HANA_T  
raceFiles_MiniChecks.txt -cg M1100-M1150,chris@du.my,I0010-I1000,john@du.my,S0100-S0125,lena@du.my,T  
0099-T0105,per@du.my -en chris@me.com,smtp.intra.me.com  
"Mini Check ID M1142 Description: Table(s) using > 10 % of SQL cache Host: mo-fc8d991e0 Value: 2  
Expectation: 0 C: X SAPNote: 2124112" is sent to chris@du.my  
"Mini Check ID M1150 Description: Pinned statements in SQL cache (%) Host: mo-fc8d991e0 Value: 27  
.93 Expectation: <= 20.00 C: X SAPNote: 2124112" is sent to chris@du.my  
"Mini Check ID T0101 Area: Statistics server Description: Unique constraint violation Host: mo-fc  
8d991e0 Port: 30003 Count: 24 LastOccurrence: 2018/03/05 06:33:41 C: X SAPNote: 2147247 TraceT  
ext: plan plan5636987@mo-fc8d991e0:30003 failed with rc 301; unique constraint violatedTrexUpdate fa  
iled on table '_SYS_STATISTICS:HOST_LOAD_HISTORY_HOST_BASE' with error: unique constraint violation  
in self check for table _SYS_STATISTICS:HOST_LOAD_HISTORY_HOST_BASEen, constraint='$trexexternalkey$',  
'udiv='2018-03-05 06:33:38;12,mo-fc8d991e0;2018-02-22 20:18:42.21', pos=18052, indexname=_SYS_TREE  
CS #150584 #0 #P0, rc=55" is sent to per@du.my  
"Mini Check ID S0120 Description: SYSTEM user deactivated Value: no Expectation: yes C: X" is se  
nt to lena@du.my
```

HANAChecker – Interval



Run hanachecker “forever” with the **–hci** flag

Flag	Unit	Details	Explanation	Default
-hci	Days	hanachecker interval	After these number days hanachecker will restart	-1 (exits)

Example: HANAChecker runs here the mini-checks and sends emails once every day

```
mo-fc8d991e0:/tmp/HANAChecker> python hanachecker.py -mf HANA_Configuration_Minichecks_1.00.120+.txt -en chris@comp.com,smtp.intra.comp.com -M1170 peter@comp.com -hci 1

"Mini Check ID M1170  Description: Average database request time (ms)  Value: 6.91
Expectation: <= 2.00  C: X  SAPNote: 2000002" is sent to peter@comp.com
"Mini Check ID M1170  Description: Average database request time (ms)  Value: 6.91
Expectation: <= 2.00  C: X  SAPNote: 2000002" is sent to peter@comp.com
"Mini Check ID M1170  Description: Average database request time (ms)  Value: 6.91
Expectation: <= 2.00  C: X  SAPNote: 2000002" is sent to peter@comp.com
```

Note: HANAChecker could ofcourse also be scheduled by a cron job – do then NOT use the **-hci** flag!



To control the output of the hanachecker there are these flags

Flag	Unit	Details	Explanation	Default
-od		output directory	full path of the folder where the hanachecker logs are written	/tmp/hanachecker_output
-so		standard out switch	1: write to std out, 0: do not write to std out	1

Example:

Here an output folder is deleted and then automatically created again by hanachecker and a new log file is written into it:

```
mo-fc8d991e0:/tmp/HANAChecker> rm -r /tmp/hanachecker_output/
mo-fc8d991e0:/tmp/HANAChecker> python hanachecker.py -mf HANA_Configuration_Minichcks_1.00.120+.txt -en chris@comp.com,smtp.intra.comp.com -M1170 peter@comp.com -so 0

mo-fc8d991e0:/tmp/HANAChecker>
mo-fc8d991e0:/tmp/HANAChecker> more ../hanachecker_output/hanacheckerlog_2018-03-05_12-37-00.txt
"Mini Check ID M1170 Description: Average database request time (ms) Value: 6.91
Expectation: <= 2.00 C: X SAPNote: 2000002" is sent to peter@comp.com
```

HANAChecker – Used To Only Log Checks



Blank `-en` flag tells HANAChecker to write all critical checks in the log file, without sending out emails:

Example:

```
xscadm@atgvmls866:/tmp/HANAChecker> python hanachecker.py -zf SQLstatements.zip -ct M,S  
-en '' -ca dummy@dum.com -so 0 -k T1KEY  
You have new mail in /var/mail/xscadm  
xscadm@atgvmls866:/tmp/HANAChecker> more /tmp/hanachecker_output/hanacheckerlog_2021-07-  
28_17-45-47.txt  
"  
Mini Check ID M0012 Description: Revision level Value: 52.00 Expectation: >= 122.03  
C: X SAPNote: 2617548"  
"  
Mini Check ID M0312 Description: I/O read latency data max. (ms, last day) Host: atgvmls866 Value: 29.70 Expectation: <= 20.00 C: X SAPNote: 1999930"  
"  
Mini Check ID M0474 Description: Heap allocators with large allocation share Value: Pool/RowEngine/QueryExecution/SearchAlloc (20 %) Expectation: none C: X SAPNote: 1999997"  
"  
Mini Check ID M0551 Description: Proper setup of timezone table TTZZ Value: no Expectation: yes C: X SAPNote: 1791342"  
"  
Mini Check ID M0552 Description: Number of current timezone alerts Value: 2 Expectation: 0 C: X SAPNote: 1791342"  
"  
Mini Check ID M0641 Description: Number of trace files (last day) Host: atgvmls866 Va
```

HANAChecker – MDC (1/2)



In a MDC system the hanachecker can check the SystemDB and multiple Tenants with one key

Maintain a user with same user name and same password in multiple DBs in one HANA System

Example:

Here the user HANACLEANER1 with same password was created in both SystemDB and in a Tenant

SYSTEMDB@PQL (SYSTEM) SiteA-SystemDB

User	User Parameters
HANACHECKER	

PQL@PQL (SYSTEM) SiteA-T1

User	User Parameters
HANACHECKER	

(for privileges,
see earlier slides)

SYSTEMDB@PQL (SYSTEM) SiteA-SystemDB

Overview	Landscape	Alerts	Performance	Volumes	Configuration
Services	Hosts	Redistribution	System Replication	Host: <All>	
Active	Host	Port	Service	SQL Port	
[atgls90010]	30001	nameserver	30013		
[atgls90010]	30010	compileserver			

Then only one key,
for the SystemDB,
was provided in
hdbuserstore

```
pqladm@atgls90010:/tmp> hdbuserstore LIST SDBCHECKERKEY
KEY SDBCHECKERKEY
ENV : atgls90010:30013
USER: HANACHECKER
```

Test that this single
key can be used to
access both databases:

```
pqladm@atgls90010:/tmp> hdbsql -j -A -x -U SDBCHECKERKEY -d SYSTEMDB "select * from m_database"
| SYS | DATABASE | HOST           | START_TIME          | VERSION          | USAG   |
| --- | ----- | ----- | ----- | ----- | ----- |
| PQL | SYSTEMDB | atgls90010 | 2018-11-29 13:01:39.336000000 | 2.00.034.00.1539746999 | TEST   |
pqladm@atgls90010:/tmp>
pqladm@atgls90010:/tmp> hdbsql -j -A -x -U SDBCHECKERKEY -d PQL "select * from m_database"
| SYS | DAT | HOST           | START_TIME          | VERSION          | USAG   |
| --- | --- | ----- | ----- | ----- | ----- |
| PQL | PQL | atgls90010 | 2018-11-29 13:01:50.309000000 | 2.00.034.00.1539746999 | TEST   |
```

In a MDC system the hanachecker can check the SystemDB and multiple Tenants with one key

Flag	Unit	Details	Explanation	Default
-dbs		DB key(s)	this can be a list of databases accessed from the system defined by -k (-k can only be one key if -dbs is used)	"

Example:

Here the key SDBCHECKERKEY is used to access the system, then it is specified with -dbs that two databases, SYSTEMDB and PQL, will be checked:

```
pqladm@atgls90010:/tmp/HANAChecker> python hanachecker.py -zf SQLStatements.zip -ct M -M1142 chris@du.my,lena@du.my -M1150 per@du.my,lena@du.my -as true -oe true -k SDBCHECKERKEY -dbs SYSTEMDB,PQL
"HANACecker was executed 2019-01-23 09:13:50 on SYSTEMDB@PQL with
hanachecker.py -zf SQLStatements.zip -ct M -M1142 chris@du.my,lena@du.my -M1150 per@du.my,lena@du.my -as true -oe true -k SDBCHECKERKEY -dbs SYSTEMDB,PQL
If any of the mini-checks that you are responsible for seem critical, you will be notified now.
Mini Check ID M1142 Description: Table(s) using > 10 % of SQL cache Host: atgls90010 Value: 1 Expectation: 0 C: X SAPNote: 2124112
```

```
"HANACecker was executed 2019-01-23 09:41:15 on PQL@PQL with
hanachecker.py -zf SQLStatements.zip -ct M -M1142 chris@du.my,lena@du.my -M1150 per@du.my,lena@du.my -as true -oe true -k SDBCHECKERKEY -dbs SYSTEMDB,PQL
If any of the mini-checks that you are responsible for seem critical, you will be notified now.
Mini Check ID M1142 Description: Table(s) using > 10 % of SQL cache Host: atgls90010 Value: 1 Expectation: 0 C: X SAPNote: 2124112
```

HANAChecker – Configuration File



**HANAChecker can be controlled with a configuration file
(additional flags given will overwrite flags in the configuration file)**

Flag	Unit	Details	Explanation	Default
-ff		flag file	full path to the configuration file	

Example:

```
mo-fc8d991e0:/tmp/HANAChecker> more hanachecker_configurationfile.txt
Comp's HANA CHECKER Configuration File:

-mf HANA_Configuration_MiniChecks_1.00.120+.txt,HANA_Security_MiniChecks.txt
-en chris@comp.com,smtp.intra.comp.com
-cg M1140-M1145,peter@comp.com,M1146-M1150,sara@comp.com
-M1142 lena@comp.com,per@comp.com
-S0120 chris@ourcompany.com
-so 0

mo-fc8d991e0:/tmp/HANAChecker> rm -r ../hanachecker_output/
mo-fc8d991e0:/tmp/HANAChecker> python hanachecker.py -ff hanachecker_configurationfile.txt
mo-fc8d991e0:/tmp/HANAChecker> more ../hanachecker_output/hanacheckerlog_2018-03-05_12-54-16.txt
"Mini Check ID M1142 Description: Table(s) using > 10 % of SQL cache Host: mo-fc8d991e0 Value: 2 Expectation: 0 C: X SAPNote: 2124112" is sent to peter@comp.com
```

Note: for multiple configuration files, see some slides below

...

HANAChecker – Configuration File Example (1/3)



hanachecker_configurationfile_example.txt - Notepad

File Edit Format View Help

An Example of a HANA CHECKER Configuration File:

#-----#

The hdbuserstore key

-k T1KEY

The .zip file is located in the same directory
as hanachecker.py
-zf SQLstatements.zip

Will run the normal mini-checks and the
security mini-checks

-ct M,S

Recievers will only get one email per execution
-oe true

Recievers will always get one email per execution
(even if their checks were not critical)

-as true

Chris is responsible for HANA revisions and for
that everything is up running at "OurCompany, OC"
-cg M0001-M0199,chris@oc.com

Lena is responsible for the Operating System
-cg M0200-M0299,lena@oc.com

Ole is responsible for the Disk

-cg M0300-M0399,ole@oc.com

Emma is the Memory expert

-cg M0400-M0499,emma@oc.com

Per is responsible for the Tables

-cg M0500-M0599,per@oc.com

Cindy is responsible for Traces, Dumps and Logs

-cg M0600-M0699,cindy@oc.com

Clark makes sure that the Statistics Server,
and Transaction and Threads run smoothly

-cg M0700-M0899,clark@oc.com

Loren is the Backup expert

-cg M0900-M0999,loren@oc.com

Tom checks that all Locks and SQLs are OK

-cg M1000-M1199,tom@oc.com

Jen takes care of the Applications

-cg M1200-M1299,jen@oc.com

Tim is Security responsible

-cg M1300-M1399,tim@oc.com

Mark handles the Network

-cg M1500-M1599,mark@oc.com

John checks the XS Engine, and Nameserver

-cg M1600-M1799,john@oc.com

Michael is responsible for the System Replication

-cg M1800-M1899,michael@oc.com

Ann checks Objects, BW and Consistency

-cg M1900-M2199,ann@oc.com

Oscar handles SDA/SDI

-cg M2200-M2299,oscar@oc.com

Administration is Chris' task,
and he also gets the rest

-cg M2300-M3000,chris@oc.com

Tim is responsible for Security, so he checks
everything from the Security Minichecks

-cg S0001-S2000,tim@oc.com

Gustav is the boss, so he wants to
see ALL Critical Checks

-ca gustav@oc.com

HANAChecker – Configuration File Example (2/3)



First part of
the output:

```
xscadm@atgvm1s866:/tmp/HANAChecker> python hanachecker.py -ff hanachecker_configurationfile_example.txt
"HANAChecker was executed 2021-07-28 18:48:28 on XSC with hanachecker.py -ff hanachecker_configurationfile_example.txt
If any of the mini and/or parameter checks that you are responsible for seem critical, you will be notified now.

Mini Check ID M0474 Description: Heap allocators with large allocation share Value: Pool/RowEngine/QueryExecution/SearchAlloc (20 %) Expectation: none C: X SAPNote: 1999997" is sent to emma@oc.com
"HANAChecker was executed 2021-07-28 18:48:28 on XSC with hanachecker.py -ff hanachecker_configurationfile_example.txt
If any of the mini and/or parameter checks that you are responsible for seem critical, you will be notified now.
" is sent to lena@oc.com
"HANAChecker was executed 2021-07-28 18:48:28 on XSC with hanachecker.py -ff hanachecker_configurationfile_example.txt
If any of the mini and/or parameter checks that you are responsible for seem critical, you will be notified now.

Mini Check ID M0312 Description: I/O read latency data max. (ms, last day) Host: atgvm1s866 Value: 29.70 Expectation: <= 20.00 C: X SAPNote: 1999930" is sent to ole@oc.com
"HANAChecker was executed 2021-07-28 18:48:28 on XSC with hanachecker.py -ff hanachecker_configurationfile_example.txt
If any of the mini and/or parameter checks that you are responsible for seem critical, you will be notified now.

Mini Check ID M0012 Description: Revision level Value: 52.00 Expectation: >= 122.03 C: X SAPNote: 2617548
Mini Check ID M2320 Description: Time since last hdbcons execution (h) Value: 0 Expectation: >= 24 C : X SAPNote: 2222218" is sent to chris@oc.com
```

HANAChecker – Configuration File Example (3/3)



I exchanged all email addresses in the example to my own email address, then HANAChecker send me this:

HANAChecker: Potential Critical Situation(s) @XSC!



SAP HANA Database System Administrator <xscadm@atgvm1s866.wdf.s
To Hansen, Christian

[Reply](#) [Reply All](#) [Forward](#) ·
Mi 28.07.2021 19:05:37

HANAChecker was executed 2021-07-28 19:05:37 on XSC with
hanachecker.py -ff hanachecker_configurationfile_example_only_me.txt
If any of the mini and/or parameter checks that you are responsible for seem critical, you will be notified now.

Mini Check ID M0012 Description: Revision level Value: 52.00 Expectation: >= 122.03 C: X SAPNote: 2617548

Mini Check ID M0312 Description: I/O read latency data max. (ms, last day) Host: atgvm1s866 Value: 29.70 Expectation: <= 20.00 C: X SAPNote: 1999930

Mini Check ID M0474 Description: Heap allocators with large allocation share Value: Pool/RowEngine/QueryExecution/SearchAlloc (21 %) Expectation: none C: X SAPNote: 1999997

Mini Check ID M0551 Description: Proper setup of timezone table TTZZ Value: no Expectation: yes C: X SAPNote: 1791342

Mini Check ID M0552 Description: Number of current timezone alerts Value: 2 Expectation: 0 C: X SAPNote: 1791342

Mini Check ID M0641 Description: Number of trace files (last day) Host: atgvm1s866 Value: 39 Expectation: <= 30 C: X SAPNote: 2119087

Mini Check ID M0646 Description: Number of statement OOM trace files (last day) Host: atgvm1s866 Value: 1 Expectation: 0 C: X SAPNote

HANAChecker – Configuration Files & Config Output



HANAChecker can be controlled with a list of configuration files (files listed later in the -ff list will overwrite flags from files listed earlier in the list, flags on the command line will overwrite the configuration files)

Flag	Unit	Details	Explanation	Default
-ff		comma separated list of flag files	full paths to configuration files	
-oc	true/false	output configuration	logs all set parameters and where the flags were set	false

Example:

```
xscadm@atgvmls866:/tmp/HANAChecker> more hanacheckerconfig.txt
The hdbuserstore key
-k T1KEY
The .zip file
-zf SQLStatements.zip
normal and security mini-checks
-ct M,S
only get one email per execution
-oe true
always one email per execution
-as true
Chris
-cg M0001-M0199,chris@oc.com
Lena
-cg M0200-M0299,lena@oc.com
Ole
-cg M0300-M0399,ole@oc.com
Tim
-cg S0001-S2000,tim@oc.com
Gustav
-ca gustav@oc.com
```

```
xscadm@atgvmls866:/tmp/HANAChecker> more hanacheckerconfig2.txt
Chris --> Lena
-cg M0001-M0199,lena@oc.com
Lena
-cg M0200-M0299,lena@oc.com
Ole --> Lena
-cg M0300-M0399,ole@oc.com
Tim
-cg S0001-S2000,tim@oc.com
Gustav --> Chris
-ca chris@oc.com
```

The example continues on the next slide

HANAChecker – Configuration Files & Config Output



Example (continued):

```
xscadm@atgvm1s866:/tmp/HANAChecker> python hanachecker.py -ff hanacheckerconfig.txt,hanacheckerconfig2.txt -ca chris@oc.com -oc true
"HANAChecker was executed 2021-09-02 17:46:52 with
-as      true from hanacheckerconfig.txt
-ff      hanacheckerconfig.txt,hanacheckerconfig2.txt from command line
-cq      M0001-M0199,lena@oc.com from hanacheckerconfig2.txt      M0200-M0299,lena@oc.com from hanacheckerconfig2.txt      M0300-M0399,o
le@oc.com from hanacheckerconfig2.txt      S0001-S2000,tim@oc.com from hanacheckerconfig2.txt
-k       T1KEY from hanacheckerconfig.txt
-zf      SQLStatements.zip from hanacheckerconfig.txt
-ca      chris@oc.com from command line
-oc      true from command line
-ct      M,S from hanacheckerconfig.txt
-oe      true from hanacheckerconfig.txt on XSC with
hanachecker.py -ff hanacheckerconfig.txt,hanacheckerconfig2.txt -ca chris@oc.com -oc true
If any of the mini and/or parameter checks from following check files:./tmp_sql_statements/HANA_Configuration_MiniChecks_2.00.053+.tx
t,./tmp_sql_statements/HANA_Security_MiniChecks_2.00.030+.txt
that you are responsible for seem critical, you will be notified now.
```

HANAChecker – Real Life Example



Emails were retrieved from HANAChecker for potential critical mini-checks:

A screenshot of three Outlook email messages. Each message has a yellow envelope icon and the subject line "HANAChecker: A Potential Critical Mini-Check".

- The first message is about Mini Check ID 1170, Description: Average database request time (ms), Host: Value: 6.91, Expectation: <= 2.00, Potential Critical: X, SAP Note: 2000002.
- The second message is about Mini Check ID 750, Description: Stat. server tables with retention < 42 days, Host: Value: 14, Expectation: 0, Potential Critical: X, SAP Note: 2147247.
- The third message is about Mini Check ID 2113, Description: Last global table consistency check (days), Host: Value: never, Expectation: <= 32.00, Potential Critical: X, SAP Note: 2116157.