

Module Interface Specification for Sayyara

Team 31

SFWRENG 4G06

Christopher Andrade

Alyssa Tunney

Kai Zhu

Ethan Vince-Budan

Collin Kan

Harsh Gupta

April 6, 2023

Revision History

Date	Version	Notes
Jan. 18, 2023	Rev 0	Revision 0
April 5, 2023	Rev 1	Revision 1

Table 1: Revision History

Contents

1	Introduction	1
2	Module Decomposition	1
3	MIS of Quotes (Backend)	2
3.1	Module	2
3.2	Uses	2
3.3	Syntax	2
3.3.1	Exported Constants	2
3.3.2	Exported Access Programs	2
3.4	Semantics	2
3.4.1	State Variables	2
3.4.2	Environment Variables	3
3.4.3	Assumptions	3
3.4.4	Access Routine Semantics	3
3.4.5	Local Functions	3
4	MIS of QuoteRequest (Backend)	4
4.1	Module	4
4.2	Uses	4
4.3	Syntax	4
4.3.1	Exported Constants	4
4.3.2	Exported Access Programs	4
4.4	Semantics	4
4.4.1	State Variables	4
4.4.2	Environment Variables	5
4.4.3	Assumptions	5
4.4.4	Access Routine Semantics	5
4.4.5	Local Functions	6
5	MIS of Appointments (Backend)	7
5.1	Module	7
5.2	Uses	7
5.3	Syntax	7
5.3.1	Exported Constants	7
5.3.2	Exported Access Programs	7
5.4	Semantics	7
5.4.1	State Variables	7
5.4.2	Environment Variables	8
5.4.3	Assumptions	8
5.4.4	Access Routine Semantics	8

5.4.5	Local Functions	9
6	MIS of Shop Quotes (Frontend)	10
6.1	Module	10
6.2	Uses	10
6.3	Syntax	10
6.3.1	Exported Constants	10
6.3.2	Exported Access Programs	10
6.4	Semantics	10
6.4.1	State Variables	10
6.4.2	Environment Variables	10
6.4.3	Assumptions	10
6.4.4	Access Routine Semantics	10
6.4.5	Local Functions	11
7	MIS of Customer QuoteRequests (Frontend)	12
7.1	Module	12
7.2	Uses	12
7.3	Syntax	12
7.3.1	Exported Constants	12
7.3.2	Exported Access Programs	12
7.4	Semantics	12
7.4.1	State Variables	12
7.4.2	Environment Variables	12
7.4.3	Assumptions	12
7.4.4	Access Routine Semantics	13
7.4.5	Local Functions	13
8	MIS of Shop (Backend)	14
8.1	Module	14
8.2	Uses	14
8.3	Syntax	14
8.3.1	Exported Constants	14
8.3.2	Exported Access Programs	14
8.4	Semantics	14
8.4.1	State Variables	14
8.4.2	Environment Variables	15
8.4.3	Assumptions	15
8.4.4	Access Routine Semantics	15
8.4.5	Local Functions	16

9	MIS of ShopService (Backend)	17
9.1	Module	17
9.2	Uses	17
9.3	Syntax	17
9.3.1	Exported Constants	17
9.3.2	Exported Access Programs	17
9.4	Semantics	17
9.4.1	State Variables	17
9.4.2	Environment Variables	17
9.4.3	Assumptions	17
9.4.4	Access Routine Semantics	18
9.4.5	Local Functions	18
10	MIS of Service (Backend)	19
10.1	Module	19
10.2	Uses	19
10.3	Syntax	19
10.3.1	Exported Constants	19
10.3.2	Exported Access Programs	19
10.4	Semantics	19
10.4.1	State Variables	19
10.4.2	Environment Variables	19
10.4.3	Assumptions	20
10.4.4	Access Routine Semantics	20
10.4.5	Local Functions	20
11	MIS of ShopCreate (Frontend)	21
11.1	Module	21
11.2	Uses	21
11.3	Syntax	21
11.3.1	Exported Constants	21
11.3.2	Exported Access Programs	21
11.4	Semantics	21
11.4.1	State Variables	21
11.4.2	Environment Variables	21
11.4.3	Assumptions	21
11.4.4	Access Routine Semantics	22
11.4.5	Local Functions	22
12	MIS of ShopLookup (Frontend)	23
12.1	Module	23
12.2	Uses	23
12.3	Syntax	23

12.3.1	Exported Constants	23
12.3.2	Exported Access Programs	23
12.4	Semantics	23
12.4.1	State Variables	23
12.4.2	Environment Variables	23
12.4.3	Assumptions	23
12.4.4	Access Routine Semantics	23
12.4.5	Local Functions	24
13	MIS of Profile (Backend)	25
13.1	Module	25
13.2	Uses	25
13.3	Syntax	25
13.3.1	Exported Constants	25
13.3.2	Exported Access Programs	25
13.4	Semantics	26
13.4.1	State Variables	26
13.4.2	Environment Variables	26
13.4.3	Assumptions	26
13.4.4	Access Routine Semantics	26
13.4.5	Local Functions	27
14	MIS of AppContext (Frontend)	28
14.1	Module	28
14.2	Uses	28
14.3	Syntax	28
14.3.1	Exported Constants	28
14.3.2	Exported Access Programs	28
14.4	Semantics	28
14.4.1	State Variables	28
14.4.2	Environment Variables	28
14.4.3	Assumptions	28
14.4.4	Access Routine Semantics	28
14.4.5	Local Functions	29
15	MIS of Authentication (Frontend)	30
15.1	Module	30
15.2	Uses	30
15.3	Syntax	30
15.3.1	Exported Constants	30
15.3.2	Exported Access Programs	30
15.4	Semantics	30
15.4.1	State Variables	30

15.4.2	Environment Variables	30
15.4.3	Assumptions	30
15.4.4	Access Routine Semantics	30
15.4.5	Local Functions	31
16	MIS of Appointments (Backend)	32
16.1	Module	32
16.2	Uses	32
16.3	Syntax	32
16.3.1	Exported Constants	32
16.3.2	Exported Access Programs	32
16.4	Semantics	32
16.4.1	State Variables	32
16.4.2	Environment Variables	33
16.4.3	Assumptions	33
16.4.4	Access Routine Semantics	33
16.4.5	Local Functions	33
17	MIS for VehicleInfo (Backend)	34
17.1	Uses	34
17.2	Syntax	34
17.2.1	Exported Constants	34
17.2.2	Exported Access Programs	34
17.3	Semantics	34
17.3.1	State Variables	34
17.3.2	Environment Variables	34
17.3.3	Assumptions	34
17.3.4	Access Routine Semantics	34
17.3.5	Local Functions	35
18	MIS for CustomerProfile (Frontend)	36
18.1	Uses	36
18.2	Syntax	36
18.2.1	Exported Constants	36
18.2.2	Exported Access Programs	36
18.3	Semantics	36
18.3.1	State Variables	36
18.3.2	Environment Variables	36
18.3.3	Assumptions	36
18.3.4	Access Routine Semantics	36
18.3.5	Local Functions	37

19 MIS for ShopOwnerProfile (Frontend)	38
19.1 Uses	38
19.2 Syntax	38
19.2.1 Exported Constants	38
19.2.2 Exported Access Programs	38
19.3 Semantics	38
19.3.1 State Variables	38
19.3.2 Environment Variables	39
19.3.3 Assumptions	39
19.3.4 Access Routine Semantics	39
19.3.5 Local Functions	39
20 MIS for EmployeeProfile (Frontend)	40
20.1 Uses	40
20.2 Syntax	40
20.2.1 Exported Constants	40
20.2.2 Exported Access Programs	40
20.3 Semantics	40
20.3.1 State Variables	40
20.3.2 Environment Variables	40
20.3.3 Assumptions	40
20.3.4 Access Routine Semantics	40
20.3.5 Local Functions	40
21 MIS for Homepages (Frontend)	41
21.1 Uses	41
21.2 Syntax	41
21.2.1 Exported Constants	41
21.2.2 Exported Access Programs	41
21.3 Semantics	41
21.3.1 State Variables	41
21.3.2 Environment Variables	41
21.3.3 Assumptions	41
21.3.4 Access Routine Semantics	41
21.3.5 Local Functions	41

List of Tables

1 Revision History	i
--------------------	---

1 Introduction

The following document details the Module Interface Specifications for Sayyara, a progressive web applications that connects customers with automotive shop owners for vehicle service inquiries, appointment scheduling, and quotes.

Complementary documents include the System Requirement Specifications and Module Guide. The full documentation and implementation can be found at <https://github.com/atunney/pwa-capstone/tree/main/docs>.

2 Module Decomposition

In the Module Guide document, due to the nature of this project, modules have been separated in categories frontend and backend hiding modules. Many backend modules for the project have a corresponding frontend module that displays the information in a visual format for the user to view and interact with.

3 MIS of Quotes (Backend)

3.1 Module

Quotes Backend

3.2 Uses

QuoteRequest

Shop

ShopService

3.3 Syntax

3.3.1 Exported Constants

PRIORITIES = ('low', 'medium', 'high')

BOOKING_STATUS = ('pending', 'canceled', 'booked')

3.3.2 Exported Access Programs

Name	In	Out	Exceptions
getQuotes	shop: Shop	Quote	NotFound
updateQuote	id: TextField shop: Shop quote_request: QuoteRequest services: ShopService status: TextField priority: TextField message: TextField	-	InvalidFields
createQuote	id: TextField quote_request: QuoteRequest	-	-

3.4 Semantics

3.4.1 State Variables

shop: Shop

quote_request: Array: QuoteRequest

services: ShopService

status: TextField

priority: TextField

message: TextField

3.4.2 Environment Variables

Quotes: Array: Quote QuoteRequests: Array: QuoteRequest

3.4.3 Assumptions

- In order for a shop to modify and send updated quotes, a customer needs to send a quote request to said shop.
- All fields in a Quote will originally be filled out by a customer.

3.4.4 Access Routine Semantics

getQuotes(shop: Shop):

- transition: none
- output: Array: Quote in Quotes such that Quote.shop.id == shop.id
- exception: NotFound: no quotes with associated shop

updateQuote(id: TextField, shop: Shop, quote_request: QuoteRequest, services: ShopService, status: TextField, priority: TextField, message: TextField):

- transition: for Quote in Quotes such that Quote.id == id: Quote.shop = shop, Quote.quote_request = quote_request, Quote.services = services, Quote.status = status, Quote.priority = priority, Quote.message = message
- output: none
- exception: InvalidFields: one or more of inputs is in invalid format

createQuote(id: TextField, quote_request: QuoteRequest):

- transition: $\text{Quotes} = \text{Quotes} \cup \text{Quote}(\text{id} = \text{id}, \text{quote_request} = \text{quote_request})$
- output: none
- exception: none

3.4.5 Local Functions

N/A

4 MIS of QuoteRequest (Backend)

4.1 Module

QuoteRequest Backend

4.2 Uses

User

Vehicle

4.3 Syntax

4.3.1 Exported Constants

N/A

4.3.2 Exported Access Programs

Name	In	Out	Exceptions
getQuoteRequests	customer: Customer	QuoteRequest	NotFound
getVehicles	customer: Customer	Vehicle	NotFound
updateQuoteRequest	part_preference: TextField customer: Customer description: TextField images: TextField vehicle: Vehicle availability: TextField	-	InvalidFields
deleteQuoteRequest	id: TextField	-	NotFound
createQuoteRequest	part_preference: TextField customer: Customer description: TextField vehicle: Vehicle availability: TextField	-	InvalidFields

4.4 Semantics

4.4.1 State Variables

id: TextField

part_preference: TextField

description: TextField

images: TextField

vehicle: Vehicle

created_at: DateTimeField
availability: TextField

4.4.2 Environment Variables

QuoteRequests: Array: QuoteRequest

4.4.3 Assumptions

N/A

4.4.4 Access Routine Semantics

getQuoteRequests(customer: Customer):

- transition: none
- output: Array: QuoteRequest in QuoteRequests such that QuoteRequest.customer.id == customer.id
- exception: NotFound: no quote requests with associated customer

getVehicles(customer: Customer)

- transition: none
- output: customer.vehicles
- exception: NotFound: no vehicles with associated customer

updateQuoteRequest(id: TextField, part_preference: TextField, description: TextField, images: TextField, vehicle: Vehicle, availability: TextField)

- transition: for QuoteRequest such that QuoteRequest.id = id: QuoteRequest.part_preference = part_preference, QuoteRequest.description = description, QuoteRequest.images = images, QuoteRequest.vehicle = vehicle, QuoteRequest.availability = availability
- output: none
- exception: InvalidFields: one or more of inputs is in invalid format

deleteQuoteRequest(id: TextField)

- transition: delete QuoteRequest from QuoteRequests where QuoteRequest.id == id
- output:
- exception: NotFound: no QuoteRequests with associated id

`createQuoteRequest(id: TextField, part_preference: TextField, description: TextField, vehicle: Vehicle, availability: TextField)`

- transition: $\text{QuoteRequests} = \text{QuoteRequests} \cup \text{QuoteRequest}(\text{id} = \text{id}, \text{part_preference} = \text{part_preference}, \text{description} = \text{description}, \text{vehicle} = \text{vehicle}, \text{availability} = \text{availability})$
- output: none
- exception: InvalidFields: one or more of inputs is in invalid format

4.4.5 Local Functions

N/A

5 MIS of Appointments (Backend)

5.1 Module

Appointment Backend

5.2 Uses

Customer
Shop
Quote
EmployeeReservation

5.3 Syntax

5.3.1 Exported Constants

PRIORITIES = ('low', 'medium', 'high')
BOOKING_STATUS = ('pending', 'canceled', 'booked')

5.3.2 Exported Access Programs

Name	In	Out	Exceptions
createAppointment	data: Appointment	Appointment-	
updateAppointment	appointment: Appointment title: TextField description: TextField time_estimate: DurationField price_estimate: DecimalField quote: Quote message: TextField	-	-
setStatus	appointment: Appointment status: TextField	-	InvalidFields

5.4 Semantics

5.4.1 State Variables

customer: Customer
shop: Shop
title: TextField
description: TextField
time_estimate: DurationField
price_estimate: DecimalField

quote: Quote
message: TextField

5.4.2 Environment Variables

appointments: Array: Appointment

5.4.3 Assumptions

- The customer must fill out all relevant fields in the appointment in order to book it.
- An appointment is only valid when a valid quote is supplied along with it.

5.4.4 Access Routine Semantics

createAppointment(customer: Customer, shop: Shop, title: TextField, description: TextField, time_estimate: DurationField, price_estimate: DecimalField, quote: Quote, message: TextField):

- transition: $\text{Appointments} = \text{Appointments} \cup \text{Appointment}(\text{customer} = \text{customer}, \text{shop} = \text{shop}, \text{title} = \text{title}, \text{description} = \text{description}, \text{time_estimate} = \text{time_estimate}, \text{price_estimate} = \text{price_estimate}, \text{quote} = \text{quote}, \text{message} = \text{message})$
- output: Appointment
- exception: none

updateAppointment(appointment: Appointment, title: TextField, description: TextField, time_estimate: DurationField, price_estimate: DecimalField, quote: Quote, message: TextField):

- transition: for Appointment in Appointments such that $\text{Appointment.id} == \text{appointment.id}$: $\text{Appointment.title} = \text{title}, \text{Appointment.description} = \text{description}, \text{Appointment.time_estimate} = \text{time_estimate}, \text{Appointment.price_estimate} = \text{price_estimate}, \text{Appointment.quote} = \text{quote}, \text{Appointment.message} = \text{message}$
- output: none
- exception: none

setStatus(appointment: Appointment, status: TextField):

- transition: for Appointment in Appointments such that $\text{Appointment.id} == \text{appointment.id}$: $\text{Appointment.status} = \text{status}$
- output: none
- exception: InvalidFields: status is invalid

5.4.5 Local Functions

N/A

6 MIS of Shop Quotes (Frontend)

6.1 Module

Quotes Frontend

6.2 Uses

Quotes Backend

QuoteRequest Backend

Shop

ShopService

6.3 Syntax

6.3.1 Exported Constants

N/A

6.3.2 Exported Access Programs

Name	In	Out	Exceptions
getComponent	-	QuotesShop	-

6.4 Semantics

6.4.1 State Variables

shopData: Shop

quoteRequests: Array: QuoteRequest

services: ShopService

status: TextField

priority: TextField

message: TextField

6.4.2 Environment Variables

N/A

6.4.3 Assumptions

6.4.4 Access Routine Semantics

getComponent():

- transition: none
- output: QuotesShop
- exception: none

6.4.5 Local Functions

setShopData(shop: Shop)
setQuoteRequests(quoteRequests: Array: QuoteRequest)
setServices(services: Array: ShopService)
setStatus(status: TextField)
setPriority(priority: TextField)
setMessage(message: TextField)

7 MIS of Customer QuoteRequests (Frontend)

7.1 Module

QuoteRequests Frontend

7.2 Uses

QuoteRequests Backend

User

Vehicle

Shop

7.3 Syntax

7.3.1 Exported Constants

N/A

7.3.2 Exported Access Programs

Name	In	Out	Exceptions
getComponent		QuotesCustomer	-

7.4 Semantics

7.4.1 State Variables

shopData: Array: Shop

userData: Array: User

partPreference: TextField

vehicleData: Array: VehicleMakes

vehicleModels: Array: VehicleModels

vehicleYears: Array: TextField

description: TextField

availability: TextField

7.4.2 Environment Variables

N/A

7.4.3 Assumptions

N/A

7.4.4 Access Routine Semantics

getComponent():

- transition: none
- output: QuotesCustomer
- exception: none

7.4.5 Local Functions

setShopData(shop: Shop)
setUserData(user: User)
setPartPreference(preference: TextField)
setVehicleData(vehicleMakes: Vehicle)
setVehicleModels(vehicleModels: Vehicle)
setVehicleYears(years: Array: TextField)
setDescription(description: TextField)
setAvailability(availability: TextField)

8 MIS of Shop (Backend)

8.1 Module

Shop Backend

8.2 Uses

User

ShopService

8.3 Syntax

8.3.1 Exported Constants

N/A

8.3.2 Exported Access Programs

Name	In	Out	Exceptions
getShop	id : TextField	Shop	NotFound
createShop	name : TextField address: TextField email: TextField phone: TextField description: TextField owner: User	-	InvalidFields
updateShop	id: TextField name : TextField address: TextField email: TextField phone: TextField description: TextField services: Array: ShopService employees: Array: User	-	InvalidFields
deleteShop	id : TextField	-	NotFound

8.4 Semantics

8.4.1 State Variables

id: TextField

owner: User

employees: Array: User
services: Array: ShopService
address: TextField
description: TextField
email: TextField
hours: TextField
name: TextField
phone: TextField

8.4.2 Environment Variables

Shops: Array: Shop

8.4.3 Assumptions

N/A

8.4.4 Access Routine Semantics

getShop(id: TextField):

- transition: none
- output: Shop in Shops such that Shop.id == id
- exception: NotFound: for every Shop in Shops: Shop.id != id

createShop(name : TextField, address: TextField, email: TextField, phone: TextField, description: TextField, owner: User):

- transition: Shops = Shops \cup Shop(name = name, address = address, email = email, phone = phone, description = description, owner = owner)
- output: none
- exception: InvalidFields: one or more of inputs is in invalid format

updateShop(id: TextField, name : TextField, address: TextField, email: TextField, phone: TextField, description: TextField, services: Array<ShopService>, employees: Array<User>):

- transition: for Shop in Shops such that Shop.id == id: Shop.name = name, Shop.address = address, Shop.email = email, Shop.phone = phone, Shop.description = description, Shop.services = services, Shop.employees = employees
- output: none
- exception: InvalidFields: one or more of inputs is in invalid format

deleteShop(id: TextField):

- transition: delete Shop from Shops where Shop.id == id
- output: none
- exception: NotFound: for every ShopService in ShopServices: ShopService.id != id

8.4.5 Local Functions

N/A

9 MIS of ShopService (Backend)

9.1 Module

ShopService Backend

9.2 Uses

Service

9.3 Syntax

9.3.1 Exported Constants

N/A

9.3.2 Exported Access Programs

Name	In	Out	Exceptions
getShopService	id : TextField	ShopService	NotFound
createShopService	service : Service est_time: TextField price: TextField	-	InvalidFields
updateShopService	id: TextField service : Service est_time: TextField price: TextField	-	InvalidFields
deleteShopService	id : TextField	-	NotFound

9.4 Semantics

9.4.1 State Variables

id: TextField
service: Service
est_time : TextField
price: TextField

9.4.2 Environment Variables

ShopServices: Array: ShopService

9.4.3 Assumptions

N/A

9.4.4 Access Routine Semantics

getShopService(id: TextField):

- transition: none
- output: ShopService in ShopServices such that ShopService.id == id
- exception: NotFound: for every ShopService in ShopServices: ShopService.id != id

createShopService(service : Service, est_time: TextField, price: TextField):

- transition: ShopServices = ShopServices \cup ShopService(service = service, est_time = est_time, price = price)
- output: none
- exception: InvalidFields: one or more of inputs is in invalid format

updateShopService(id: TextField, service : Service, est_time: TextField, price: TextField):

- transition: for ShopService in ShopServices such that ShopService.id == id: ShopService.service = service, ShopService.est_time = est_time, ShopService.price = price
- output: none
- exception: InvalidFields: one or more of inputs is in invalid format

deleteShop(id: TextField):

- transition: delete ShopService from ShopServices where ShopService.id == id
- output: none
- exception: NotFound: for every ShopService in ShopServices: ShopService.id != id

9.4.5 Local Functions

N/A

10 MIS of Service (Backend)

10.1 Module

Service Backend

10.2 Uses

N/A

10.3 Syntax

10.3.1 Exported Constants

N/A

10.3.2 Exported Access Programs

Name	In	Out	Exceptions
getService	id : TextField	Service	NotFound
createService	description : TextField name: TextField	-	InvalidFields
updateService	id: TextField description : TextField name: TextField	-	InvalidFields
deleteService	id : TextField	-	NotFound

10.4 Semantics

10.4.1 State Variables

id: TextField
description: TextField
name: TextField

10.4.2 Environment Variables

Services: Array: Service

10.4.3 Assumptions

N/A

10.4.4 Access Routine Semantics

getService(id: TextField):

- transition: none
- output: Service in Services such that Service.id == id
- exception: NotFound: for every Service in Services: Service.id != id

createService(description : TextField, name: TextField):

- transition: Services = Services \cup Service(description = description, name = name)
- output: none
- exception: InvalidFields: one or more of inputs is in invalid format

updateService(id: TextField, description : TextField, name: TextField):

- transition: for Service in Services such that Service.id == id: Service.description = description, Shop.name = name
- output: none
- exception: InvalidFields: one or more of inputs is in invalid format

deleteShop(id: TextField):

- transition: delete Service from Services where Service.id == id
- output: none
- exception: NotFound: for every Service in Services: Service.id != id

10.4.5 Local Functions

N/A

11 MIS of ShopCreate (Frontend)

11.1 Module

ShopCreate Frontend

11.2 Uses

Shop (Backend)

11.3 Syntax

11.3.1 Exported Constants

N/A

11.3.2 Exported Access Programs

Name	In	Out	Exceptions
GetComponent		ShopCreate	-

11.4 Semantics

11.4.1 State Variables

shopName: TextField
shopAddress: TextField
shopEmail: TextField
shopPhone: TextField
shopDescription: TextField
isShopCreated: boolean
isShopCreating: boolean
isShopCreationError: boolean

11.4.2 Environment Variables

N/A

11.4.3 Assumptions

N/A

11.4.4 Access Routine Semantics

getComponent():

- transition: none
- output: ShopCreate
- exception: none

11.4.5 Local Functions

```
setShopName(name : TextField): ShopCreate.shopName = name  
setShopAddress(address : TextField): ShopCreate.shopAddress = address  
setShopEmail(email : TextField): ShopCreate.shopEmail = email  
setShopPhone(phone : TextField): ShopCreate.shopPhone = phone  
setShopDescription(description : TextField): ShopCreate.shopDescription = description  
setIsShopCreated(isCreated : boolean): ShopCreate.isShopCreated = isCreated  
setIsShopCreating(isCreating : boolean): ShopCreate.isShopCreating = isCreating
```

12 MIS of ShopLookup (Frontend)

12.1 Module

ShopLookup Frontend

12.2 Uses

Shop
ShopService
Service

12.3 Syntax

12.3.1 Exported Constants

N/A

12.3.2 Exported Access Programs

Name	In	Out	Exceptions
getComponent		ShopLookup	-

12.4 Semantics

12.4.1 State Variables

allShops: Array: Shop
queryShops: Array: Shop
searchQuery: TextField

12.4.2 Environment Variables

N/A

12.4.3 Assumptions

N/A

12.4.4 Access Routine Semantics

getComponent():

- transition: none

- output: ShopLookup
- exception: none

12.4.5 Local Functions

```
getAllShops()  
setAllShops(shops: Array: Shop)  
setSearchQuery(query : TextField)  
getQueryShops(query : TextField)  
setQueryShops(results : Array: Shop)
```


13 MIS of Profile (Backend)

13.1 Module

Profile Backend

13.2 Uses

User

13.3 Syntax

13.3.1 Exported Constants

ACCOUNT_TYPE: Tuple: ("ShopEmployee", "ShopOwner", "Customer")

13.3.2 Exported Access Programs

Name	In	Out	Exceptions
getProfile	pk: DecimalField	Profile	NotFound
updateProfile	pk: DecimalField first_name: TextField last_name: TextField email: TextField phone: TextField role: AC-COUNT_TYPE	Profile	NotFound InvalidFields
createProfile	username: TextField password: TextField first_name: TextField last_name: TextField email: TextField phone: TextField role: AC-COUNT_TYPE	-	UserExists InvalidFields
resetRequest	id: TextField email: TextField	token: TextField	InvalidFields
resetValidate	id: TextField token: TextField	valid: BooleanField	-
resetConfirm	id: TextField token: TextField password: TextField	-	InvalidToken InvalidFields

13.4 Semantics

13.4.1 State Variables

role: ACCOUNT_TYPE

phone: TextField

user: User

13.4.2 Environment Variables

Profiles: Array: Profile

13.4.3 Assumptions

N/A

13.4.4 Access Routine Semantics

getProfile(pk: DecimalField):

- transition: none
- output: Profile in Profiles such that Profile.user.pk == pk
- exception: NotFound - pk does not point to an existing user

updateProfile(pk: DecimalField, first_name: TextField, last_name: TextField, email: TextField, phone: TextField, role: ACCOUNT_TYPE):

- transition: for Profile in Profiles such that Profile.user.pk == pk: Profile.phone = phone, profile.user.first_name = first_name, profile.user.last_name=last_name, profile.user.email = email, profile.role = role
- output: none
- exception: NotFound - pk does not point to an existing user; InvalidFields - any input is empty or contains invalid formatting (phone, email, role)

createProfile(username: TextField, password: TextField, first_name: TextField, last_name: TextField, email: TextField, phone: TextField, role: ACCOUNT_TYPE):

- transition: Profiles = Profiles \cup Profile(phone = phone, role = role, User(username = username, password = password, email = email, first_name = first_name, last_name = last_name))
- output: none
- exception: UserExists - users[pk] already exists; InvalidFields - any input is empty or contains invalid formatting (phone, email, role)

resetRequest(id: DecimalField, email: TextField):

- transition: for Profile in Profiles such that Profile.user.pk == id: Profile.user.token = GenerateToken()
- output: for Profile in Profiles such that Profile.user.pk == id: SendResetEmail(email = email, token = Profile.user.token, id = Profile.user.id), return Token
- exception: InvalidFields - email input is incorrectly formatted

resetValidate(id: DecimalField, token: TextField):

- transition: none
- output: for Profile in Profiles such that Profile.user.pk == id: return Profile.user.token == token
- exception: N/A

resetConfirm(id: DecimalField, token: TextField, password: TextField):

- transition: for Profile in Profiles such that Profile.user.pk == id and Profile.user.token == token: Profile.user.password = password
- output: N/A
- exception: InvalidToken - uid and token cannot be validated; InvalidFields - password is invalidly formatted (password.length < 8 or contains invalid characters)

13.4.5 Local Functions

generateToken(): A function that generates and returns a new random Token for verification purposes

SendResetEmail(email: TextField, token: TextField, id: DecimalField): A function that creates a unique URL to a reset password page and emails the URL to the given email

14 MIS of AppContext (Frontend)

14.1 Module

AppContext Frontend

14.2 Uses

N/A

14.3 Syntax

14.3.1 Exported Constants

AppWrapper: React.FunctionalComponent

14.3.2 Exported Access Programs

Name	In	Out	Exceptions
setUser	user: Dictionary	-	-
setTokens	tokens: Dictionary	-	-

14.4 Semantics

14.4.1 State Variables

user: Dictionary: {username: TextField, email: TextField, role: TextField, first_name: TextField, last_name: TextField, phone: TextField}

tokens: Dictionary: {accessToken: TextField, refreshToken: TextField, authStatus: TextField}

14.4.2 Environment Variables

LocalStorage : Dictionary : any

14.4.3 Assumptions

Assume that the Dictionary type of user and tokens corresponds to the detailed Dictionary type shown in the above State Variables section (to avoid reptition and improve readability)

14.4.4 Access Routine Semantics

setUser(user: Dictionary):

- transition: AppContext.user = user

- output: none
- exception: none

setTokens(tokens: Dictionary):

- transition: `AppContext.tokens = tokens`
- output: none
- exception: none

14.4.5 Local Functions

N/A

15 MIS of Authentication (Frontend)

15.1 Module

Authentication Frontend

15.2 Uses

AppContext

15.3 Syntax

15.3.1 Exported Constants

N/A

15.3.2 Exported Access Programs

Name	In	Out	Exceptions
getComponent	-	Authentication	-

15.4 Semantics

15.4.1 State Variables

N/A

15.4.2 Environment Variables

N/A

15.4.3 Assumptions

15.4.4 Access Routine Semantics

getComponent():

- transition: none
- output: Authentication
- exception: none

15.4.5 Local Functions

register(): A function that re-renders this page with account registration instructions

login(message: TextField, type: TextField): A function that re-renders this page with a message

forgotten(): A function that re-renders this page with a form to enter an email to send a reset password link to that email

reset(uid: TextField, token: TextField): A function that re-renders this page with a form to reset the password if the given uid and token are valid from the backend

fetchUserProfile(context: AppContext, token: TextField): A function that updates the context with the user's information from the backend (using the token)

16 MIS of Appointments (Backend)

16.1 Module

Appointments Backend

16.2 Uses

Customer

Shop

Quote

EmployeeReservation

16.3 Syntax

16.3.1 Exported Constants

N/A

16.3.2 Exported Access Programs

Name	In	Out	Exceptions
getAppointments	customer: Customer shop: Shop	List[Appointment]	ShopNotFound CustomerNotFound
createAppointment	formData:Appointment	-	ShopNotFound CustomerNotFound

16.4 Semantics

16.4.1 State Variables

- customer: Customer
- shop: Shop
- created_at: DateTimeField
- title: TextField
- description: TextField
- time_estimate: DurationField
- price_estimate: DecimalField

- quote: Quote
- message: TextField
- reservation: EmployeeReservation

16.4.2 Environment Variables

N/A

16.4.3 Assumptions

N/A

16.4.4 Access Routine Semantics

getAppointment(customer: Customer, shop:Shop):

- transition: N/A
- output: List[Appointment] where appointment.customer = customer OR appointment.shop = shop
- exception: ShopNotFound, CustomerNotFound

createAppointment(appointment: Appointment):

- transition: none
- output: List[Appointment]
- exception: ShopNotFound, CustomerNotFound

16.4.5 Local Functions

validateAppointment(instance:Appointment)

17 MIS for VehicleInfo (Backend)

17.1 Uses

Vehicle, VehicleSerializer

17.2 Syntax

17.2.1 Exported Constants

N/A

17.2.2 Exported Access Programs

Name	In	Out	Exceptions
createVehicle	make : TextField model : TextField year : DecimalField		
getVehicle	id : DecimalField	vehicle : Vehicle	VehicleNotFound
putVehicle	id : DecimalField make : TextField model : TextField year : DecimalField		VehicleNotFound
deleteVehicle	id : DecimalField		VehicleNotFound

17.3 Semantics

17.3.1 State Variables

- VehicleList: set of Vehicle

17.3.2 Environment Variables

N/A

17.3.3 Assumptions

- input year is a valid year

17.3.4 Access Routine Semantics

createVehicle(make,model,year):

- transition: VehicleList.append(new Vehicle(make, model, year))

getVehicle(id):

- output: $\text{out} := \text{VehicleList}(\text{id})$
- exception: $\text{id} \notin \text{VehicleList} \Rightarrow \text{VehicleNotFound}$

putVehicle(id, make, model, year):

- transition: $\text{VehicleList}(\text{id}) := \text{new Vehicle}(\text{make}, \text{model}, \text{year})$
- exception: $\text{id} \notin \text{VehicleList} \Rightarrow \text{VehicleNotFound}$

deleteVehicle(id):

- transition: $\text{VehicleList}(\text{id}) := \text{null}$
- exception: $\text{id} \notin \text{VehicleList} \Rightarrow \text{VehicleNotFound}$

17.3.5 Local Functions

N/A

18 MIS for CustomerProfile (Frontend)

18.1 Uses

Auth, AppContext, Profile, Vehicles

18.2 Syntax

18.2.1 Exported Constants

N/A

18.2.2 Exported Access Programs

Name	In	Out	Exceptions
setUserInfo	pk : int		
updateUserInfo	username: TextField email: TextField role: TextField first_name: TextField last_name: TextField phone: TextField		

18.3 Semantics

18.3.1 State Variables

- userInfo : User

18.3.2 Environment Variables

N/A

18.3.3 Assumptions

- Authentication status and user access tokens are available through the Auth module

18.3.4 Access Routine Semantics

setUserInfo(pk):

- transition: userInfo := Profile.get(pk)

updateUserInfo(username, email, TextField, role, first_name, last_name, phone):

- transition: userInfo := new User(username, email, role, first_name, last_name, phone)
Profile.update(username, email, role, first_name, last_name, phone)

18.3.5 Local Functions

N/A

19 MIS for ShopOwnerProfile (Frontend)

19.1 Uses

Auth, AppContext, User, Profile, Shop, ShopServices

19.2 Syntax

19.2.1 Exported Constants

N/A

19.2.2 Exported Access Programs

Name	In	Out	Exceptions
setUserInfo	pk : DecimalField		
updateUserInfo	username : TextField email : TextField role : TextField first_name : TextField last_name : TextField phone : TextField		
setShopInfo	id : TextField		
updateShopInfo	id : TextField name : TextField address : TextField email : TextField phone : TextField desc : TextField		
setServicesInfo	ids : set of TextField		
updateServicesInfo	id : TextField service : Service est_time : TextField price : TextField		

19.3 Semantics

19.3.1 State Variables

- userInfo : User
- shopInfo : Shop
- services : set of Services

19.3.2 Environment Variables

N/A

19.3.3 Assumptions

N/A

19.3.4 Access Routine Semantics

setUserInfo(pk):

- transition: $\text{userInfo} := \text{Profile.get(pk)}$

updateUserInfo(username, email, TextField, role, first_name, last_name, phone):

- transition: $\text{userInfo} := \text{new User}(\text{username}, \text{email}, \text{role}, \text{first_name}, \text{last_name}, \text{phone})$
 $\text{Profile.update}(\text{username}, \text{email}, \text{role}, \text{first_name}, \text{last_name}, \text{phone})$

setShopInfo(id):

- transition: $\text{shopInfo} := \text{Shop.getShop(id)}$

updateShopInfo(id, name, address, email, phone, desc):

- transition: $\text{shopInfo} := \text{new Shop}(\text{name}, \text{address}, \text{email}, \text{phone}, \text{desc})$
 $\text{Shop.updateShop}(\text{id}, \text{name}, \text{address}, \text{email}, \text{phone}, \text{desc})$

setServicesInfo(ids):

- transition: $\forall i \in \text{ids} : \text{services.append}(\text{ShopService.getShopService}(\text{id}))$

updateServicesInfo(id, service, est_time, price):

- transition: $\text{services}(\text{id}) := \text{new Service}(\text{service})$
 $\text{ShopService.updateShopService}(\text{id}, \text{service}, \text{est_time}, \text{price})$

19.3.5 Local Functions

N/A

20 MIS for EmployeeProfile (Frontend)

20.1 Uses

Auth, AppContext, User, Profile, EmployeeAvailability

20.2 Syntax

20.2.1 Exported Constants

N/A

20.2.2 Exported Access Programs

Name	In	Out	Exceptions
setUserInfo	pk : DecimalField		
setAvailability			
updateAvailability			

20.3 Semantics

20.3.1 State Variables

- userInfo : User

20.3.2 Environment Variables

N/A

20.3.3 Assumptions

N/A

20.3.4 Access Routine Semantics

N/A setUserInfo(pk):

- transition: userInfo := Profile.get(pk)

setAvailability():

updateAvailability():

20.3.5 Local Functions

N/A

21 MIS for Homepages (Frontend)

21.1 Uses

Auth, AppContext, User, Profile, Appointments

21.2 Syntax

21.2.1 Exported Constants

N/A

21.2.2 Exported Access Programs

Name	In	Out	Exceptions
getUserInfo	id : DecimalField		
getAppointments	customer : User		

21.3 Semantics

21.3.1 State Variables

- userInfo : User
- userAppointments : set of Appointment

21.3.2 Environment Variables

N/A

21.3.3 Assumptions

N/A

21.3.4 Access Routine Semantics

getUserInfo(id):

- transition: userInfo := Profile.get(id)

getAppointments(customer)

- transition: $\forall s \in Shop(id) : \text{userAppointments.append}(s)$

21.3.5 Local Functions

N/A