

# REPORT OF LOAD TEST

## Per ANSI E1.6-2

Owner Owner

Address \_\_\_\_\_

Hoist Description	Lodestar		
Manufacture	Columbus McKinnon		
Model	Model	Serial No.	Serial
Rated Capacity	1 Ton	Power Supply	440-480/3/60, 208-240/3/60

Load Test Per E1.6-2 Load Test (Spec. 100% -- 125%)		Pounds	
Did Overload Protector reject 230%		Yes <input type="checkbox"/>	No <input type="checkbox"/>
Current Draw Manufacturer Specification Per Phase 3A w/load			
Actual Current Values			
Phase 1	I1	Phase 2	I2
		Phase 3	I3

### COMMENTS

On the \_\_\_\_ day of \_\_\_\_\_, 20\_\_\_\_ the above described device was load tested using as a guide ANSI E1.6-2 and the manufacturer's recommendation stated in the operational manual.

Signature: \_\_\_\_\_

Date \_\_\_\_\_

# REPORT OF LOAD TEST

## Per ANSI E1.6-2

Owner Owner

Address \_\_\_\_\_

Hoist Description	Lodestar		
Manufacture	Columbus McKinnon		
Model	Model	Serial No.	Serial
Rated Capacity	1 Ton	Power Supply	440-480/3/60, 208-240/3/60

Load Test Per E1.6-2 Load Test (Spec. 100% -- 125%)		Pounds	
Did Overload Protector reject 230%		Yes <input type="checkbox"/>	No <input type="checkbox"/>
Current Draw Manufacturer Specification Per Phase 3A w/load			
Actual Current Values			
Phase 1	I1	Phase 2	I2
		Phase 3	I3

### COMMENTS

On the \_\_\_\_ day of \_\_\_\_\_, 20\_\_\_\_ the above described device was load tested using as a guide ANSI E1.6-2 and the manufacturer's recommendation stated in the operational manual.

Signature: \_\_\_\_\_

Date \_\_\_\_\_