Final report outline v3.1 — Chris Crasto Gomes

Final report — outline (v3, revised per Victor's 5 Nov feedback)

Report working title: *What Drives an LLM's Choice? A Controlled Offer-Choice Experiment* **Data:** `results/results.csv` — run 2: 1,041 trials of 1,050 (of which **597 on the final frozen pages**) · `results/results_run3.csv` — run 3: 210 planned / **206 completed** (v3 pages) · 7 models · 5 pages · temperature 0.1 · $54.57 total spend

> **Revision 2 — what changed from the outline reviewed on 1 Nov** 1. **Run 3 moved into Results as §5.5**, immediately after the DeepSeek before/after (§5.3) — not a separate section after the Discussion. The Discussion (§6) now draws on both runs, and the review-volume "bundle" question is answered where §5.5 presents the test. 2. **Run 3 is compared with Run 2 on the same pages.** The pooled figure (Canvas 3 of 1,041) includes trials on the earlier pages; on the final frozen pages Canvas won **3 of 597 (0.5%)**. mimo-v2.6-flash and gemini-3.1-flash-lite saw only the earlier pages in Run 2, so their Run 3 shift mixes the redesign and the rating change and is reported as such. Counts are given beside every percentage, and the result is worded as **support for H1**, not confirmation. 3. The live report page has been updated accordingly: "causally isolates" is removed and the Run 3 tables now show the same-pages baseline and counts.
>
> **Revision 3 — what changed from the feedback of 5 Nov** 1. **Headline comparison now holds the model set constant.** The Run 3 headline is **Canvas 45 of 146 (30.8%) for the five models that appear in both runs** (gpt-6-luna, deepseek-flash, grok-3-mini, gpt-4.1-mini, gemini-3.8-flash — the same five that constitute the 597 final-page Run-2 baseline), used in the abstract, §5.5 and the live report page. mimo-v2.6-flash and gemini-3.1-flash-lite (who saw only v1 in Run 2) are reported separately — **Canvas 10 of 60** — with their declared confound. 2. **Outline brought in line with the Method (§4.2).** "Canvas could not win on the earlier pages" is replaced everywhere: Canvas **did not win** on v1 (0/444), and since v1→v2 changed only the visual layer, the confound for mimo and gemini-3.1-flash-lite is the **visual redesign only** — smaller than earlier drafts claimed. 3. **§4.4: five providers, not six** (OpenAI, Google, xAI, Xiaomi, DeepSeek; OpenAI and Google contribute two models each).

---

1. Abstract (~250 words)

- Question: how do low-tier LLMs choose between five controlled course offers, and what drives the pick?
- Design in one line: 7 models × 5 pages shown together, shuffled, single choice + exit survey; 1,041 run-2 trials (597 on the final frozen pages) and 206 run-3 trials.
- Headline: no page ≥60%; aggregate balance arises from **models disagreeing** — credentials-first vs price-first.
- Run 3 in one sentence: raising only Canvas's rating (4.3★ → 4.6★) moves it from **3 of 597 (0.5%) to 45 of 146 (30.8%) among the five models that appear in both runs** — **support for H1** (rating was the binding constraint for the middle models), with Artistry still first; pooled across all seven models it is 55 of 206 (26.7%), of which the two v1-only models account for 10 of 60, reported separately with their declared confound.
- Honest caveats up front: page-version change mid-run (sensitivity analysis in §5.3), post-hoc survey (§5.4), ~30 trials per model in Run 3.

2. Introduction & research question

- LLMs increasingly act as product/course recommenders; their choice = recommendation.
- Human choice heuristics this study maps onto: price–quality inference, social proof, authority/credentials.
- RQ: *How do low-tier LLMs distribute choices across controlled offers, and do their choices track their stated reasons?*

3. Background / related work

- Heuristics and biases in human decision making (price–quality, social proof, authority; Cialdini's levers).
- Prior work on LLM choice behaviour and prompt/order sensitivity.
- Self-report vs behaviour in LLMs (and why the survey must be read cautiously — see §5.4).

4. Method

4.1 Stimuli and the controlled-feature design

- Five fictional oil-painting course pages; every feature controlled in `pages/features.yaml`.
- Principle: exactly **one strength + one honest tradeoff** per page (price ladder 4.3–4.8★, reviews 180–260, credentials, one certificate, payment plans, badges).

4.2 Page-version history (DECLARED — feedback point 1)

- **v1 (trials of 16 Oct 2026):** run-2 final layout A — 444 trials. Controlled feature values **already at their final run-2 settings**: the Canvas demotion (260 reviews @ 4.3★, community-taught, no credentials) was the **pilot-2b fix applied before any Run-2 trial** — *not* part of the v2 redesign (an earlier outline draft attributed it to v2; corrected here).
- **v2 (trials of 17 Oct 2026 → frozen): visual-layer-only** update (layouts/images; commit `f38306a`, "distinct layouts per page") — 597 trials, controlled values byte-identical to v1 (winner attributes match across the boundary; v1 reasonings quote "260 reviews" 52× and "4.3" 113×, and never the pre-rebalance "15 reviews"/"4.0"). This is the like-for-like baseline for Run 3 (§5.5).
- **v3 (Run 3, 22–23 Oct 2026):** v2 with one change — Canvas rating 4.3★ → 4.6★ (§5.5).
- Which models saw which version in run 2: | Model | Version seen | |—|—| | gemini-3.1-flash-lite, mimo-v2.6-flash | v1 only (150 each) | | gpt-4.1-mini, grok-3-mini | v2 only (150 each) | | deepseek-flash, gpt-6-luna, gemini-3.8-flash | **both** (71/72, 32/118, 41/107) |
- From 17 Oct onward pages are **frozen**; Run 3 is the only sanctioned change (§5.5).

4.3 Procedure

- All five pages as raw HTML in one prompt, order shuffled per trial; choose exactly one + justify.
- Exit survey (11 items, 1–5) in the **same conversation, after** the choice — explicitly described as post-choice self-report.
- **Temperature 0.1** for every provider (stated because "near-deterministic" depends on it); max output tokens 2,000; ≤3 choice attempts, ≤10 interview attempts (observed maxima 3 and 5).
- 30 trials per model → 1,050 planned (run 2); 210 planned (run 3).

4.4 Models

- Table: 7 low-tier models across **5 providers** (OpenAI ×2, Google ×2, xAI, Xiaomi, DeepSeek), pricing per 1M tokens.

4.5 Failures, retries and dropped trials (feedback point 4)

- Failure sources from run logs: grok — xAI credits exhausted (150 failed attempts, **all recovered** after top-up); deepseek — ~110 empty/invalid responses ("No JSON with 'choice' key"); gpt-6-luna — 1 credit exhaustion; mimo — rate/blank retries; gemini-3.8-flash — 2 × "Deadline Exceeded".
- Retry policy: automatic re-run (up to 3 choice / 5 interview attempts) — 87 choice calls and 24 interview calls succeeded only after retries.
- **Run 2: 9 trials dropped** (never completed): 7 deepseek-flash, 2 gemini-3.8-flash → 1,041 / 1,050 = 99.1% completion.
- **Run 3: 4 trials dropped** (DeepSeek empty-response flakes, same failure mode) → 206 / 210 = 98.1% completion.
- Denominators = completed trials per model (Run 2: 143–150; Run 3: 26–30); sensitivity: even if all 7 dropped deepseek trials were Palette picks, deepseek's Palette share moves only 17.5% (25/143) → 21.3% (32/150) — conclusions unchanged.

4.6 Cost accounting

- **$54.57** total across all runs (run 1 $13.59 + run 2 $34.16 + run 3 $6.82), token-priced, cap $100 — the cost-log figure is authoritative everywhere (supersedes the $50–60 figure quoted verbally in the demo video).

5. Results

5.1 Descriptives — did the redesign work?

- Run 2 shares (all 1,041): Artistry 56.1% (584) · Palette 40.0% (416) · Brushstroke 2.3% (24) · Creative 1.3% (14) · Canvas 0.3% (3).
- Of those, 444 trials used the earlier pages (16 Oct, v1) and 597 the final frozen pages (17 Oct, v2); **Canvas did not win on v1 (0/444)**, and since v1→v2 changed only the visual layer (§4.2) the like-for-like baseline for Run 3 is the 597 final-page trials (§5.5).
- No page ≥60% dominance line; run-1 ceiling (96.6%) resolved.

5.2 Per-model choice distributions

- Table + stacked figure: credentials-first (gemini-3.8, mimo, deepseek) vs price-first (grok, gemini-lite, luna) vs heterogeneous (gpt-4.1-mini, all five pages picked).
- Near-determinism at temperature 0.1: within a version, no model approaches uniform 20% across pages.

5.3 Version sensitivity — the DeepSeek before/after (feedback point 1)

Model	16 Oct (v1)	17 Oct (v2)	Shift
deepseek-flash	n=71: A 94% · P 6%	n=72: A 71% · P 29%	**–23pp Artistry**
gpt-6-luna	n=32: P 56% · A 44%	n=118: P 57% · A 43%	stable (±1pp)
gemini-3.8-flash	n=41: A 95% · P 5%	n=107: A 93% · P 7%	stable (2pp)

- Interpretation: two of three dual-version models hold their signature; deepseek does shift with the pages → **part of the between-model difference may be stimulus version, not model identity**; the claim "all variance is between models" is qualified accordingly. Single-version models (lite, mimo, 4.1-mini, grok) are version-pooled with the caveat noted.

5.4 Stated vs revealed choice (feedback point 2 — worded as consistency, not cause)

- Exit survey comes **after** the choice, same conversation → answers may rationalise a decision already made.
- Report as **consistency/association**: Artistry choosers rate credentials 4.99 & price 3.30; Palette choosers rate price 5.00 & credentials 2.51 — self-reports align with behaviour; they **cannot establish** that the rated factor caused the choice.

5.5 Run 3 — rating as the single-variable test (COMPLETE)

Placed here, in Results, so the test sits with the other results and the Discussion (§6) can draw on both runs.

- **Design (one change only):** Canvas rating 4.3★ → 4.6★ (off the floor; now ties Palette). Every other feature and the other four pages byte-identical to the frozen v2 pages (`pages_run3/` , diff-verified). Same protocol: temperature 0.1, all 7 models × 30 = 210 planned, **206 completed**; `page_version=v3` in `results/results_run3.csv` .
- **H1 / H2:** H1 — if rating was the binding constraint, Canvas rises materially above its final-pages baseline. H2 — it stays low → the bundle reading stands.
- **Like-for-like aggregate (run 2 final pages, n = 597 → run 3, n = 206):**

Page	Run 2 final pages	Run 3	Shift
Artistry Academy	311 (52.1%)	90 (43.7%)	–8.4pp
Palette Masters	264 (44.2%)	55 (26.7%)	–17.5pp
Canvas & Color	**3 (0.5%)**	**55 (26.7%)**	**+26.2pp**
Brushstroke Studio	5 (0.8%)	4 (1.9%)	+1.1pp
Creative Canvas	14 (2.3%)	2 (1.0%)	–1.3pp

- **Baseline note (Victor's check):** pooled across all 1,041 run-2 trials Canvas is 3 (0.3%), but 444 of those trials used the v1 pages, where Canvas did not win (0/444). Those 444 v1 trials include three of the five headline models as well (deepseek-flash 71, gpt-6-luna 32, gemini-3.8-flash 41) alongside mimo's and gemini-lite's 300 — the headline is unaffected because it uses only the 597 v2 trials. The like-for-like baseline is **3 of 597 (0.5%)** on the final frozen pages.
- **Headline (Victor's point 1 — model set held constant):** the 597 final-page trials are exactly the **five models that also ran in Run 3** (gpt-6-luna, deepseek-flash, grok-3-mini, gpt-4.1-mini, gemini-3.8-flash). For those five, Run 3 gives **Canvas 45 of 146 (30.8%)** — this is the headline figure in the abstract, here, and on the report page. The other two models (mimo-v2.6-flash, gemini-3.1-flash-lite) saw only v1 in Run 2 and are reported separately: **Canvas 10 of 60 (16.7%)**, with the confound declared below.
- **Per model — Canvas wins / trials** (Run 2 column headed *pages seen*: v2 = final frozen pages; v1 = earlier pages, visual layer only, same data values; every Run 3 model has ≈30 completed trials):

Model	Run 2 · Canvas (pages seen)	Run 3 · counts	Reading
gpt-6-luna	0/118 (v2)	Canvas 17/30 (57%)	flipped outright
deepseek-flash	0/72 (v2)	Artistry 14/26 (54%) · Canvas 11/26 (42%)	split
grok-3-mini	0/150 (v2)	Palette 12/30 (40%) · Canvas 11/30 (37%)	split
mimo-v2.6-flash *	0/150 (**v1**)	Artistry 17/30 (57%) · Canvas 10/30 (33%)	moderate
gpt-4.1-mini	3/150 (v2)	Artistry 15/30 (50%) · Canvas 6/30 (20%)	moderate
gemini-3.1-flash-lite *	0/150 (**v1**)	Palette 24/30 (80%)	unmoved
gemini-3.8-flash	0/107 (v2)	Artistry 30/30 (100%)	unmoved

* **Declared confound:** mimo-v2.6-flash and gemini-3.1-flash-lite ran Run 2 on the **v1 pages**, so their Run 3 comparison is not against their own same-pages baseline. Because v1→v2 changed **only the visual layer** (§4.2 — controlled values byte-identical), the confound for these two is the **visual redesign plus the rating change**, not a data-value change — smaller than earlier drafts claimed. Their headline contribution is therefore reported separately: **Canvas 10 of 60**, not folded into the five-model figure. The other five models are strictly like-for-like (v2 pages in both runs).

- **Reading — support for H1:** for the five models in both runs the rating bump moved Canvas from 3/597 (0.5%) to **45/146 (30.8%)**; pooled across all seven models it is 55/206 (26.7%), the two v1-only models adding 10/60. The movement is driven by the price-leaning and heterogeneous models; the two extreme-signature models did not move (gemini-3.8 30/30 Artistry; gemini-lite 24/30 Palette). The result **supports H1** — rating was the binding constraint for the middle models — and points the same way as the run-2 bundle reading: review volume alone never won; volume plus a non-lowest rating wins 30.8% of trials for the like-for-like five, enough for second place. **Artistry still leads Run 3 (43.7%) and Canvas ties Palette for second (26.7% each pooled)** — not a takeover. At ≈30 trials per model these are tendencies, not precise effects; the wording throughout is “support for H1”, never “confirms” or “causally isolates”.
- **Cost & failures:** $6.82 for 206 completed trials; 4 dropped (DeepSeek empty-response flakes, the same failure mode as run 2), counted out of 210 planned and never imputed; percentages use completed trials as the denominator.

6. Discussion (draws on both runs)

6.1 Main finding, properly hedged

- Aggregate balance from heuristic disagreement between models; qualified by §5.3 version sensitivity. ### 6.2 What models heeded — and what they ignored
- Likert drivers (Description 4.61 ≈ Reviews 4.56 > … > Anchoring 2.00); badges/anchors/payment plans barely register. ### 6.3 Review volume: a bundle, not an isolated driver (feedback point 3)
- Canvas = most reviews **+** lowest rating **+** community teaching — the run-2 0.3% result is about the bundle; no claim that review volume per se is powerless.
- **Answered by §5.5:** lifting only the rating moves Canvas to 55/206 — the bundle reading holds, and rating was the binding constraint for the middle models (support for H1). Volume + a non-lowest rating is worth second place, not first.

7. Threats to validity & limitations

- Page-version confound (mitigated: declared, sensitivity-analysed, pages frozen; Run 3 compared on the same pages).
- Post-choice survey design (mitigated: association language only).
- Run 3 power: ≈30 trials per model → counts reported beside every percentage; result worded as support for H1, not confirmation.
- Run 3 baseline confound for mimo and gemini-3.1-flash-lite (v1 pages only in run 2 — visual redesign only, values byte-identical) — declared in §5.5, reported separately (10/60), not pooled into the headline.
- Low-tier models only, temperature 0.1 → findings characterise this tier; between-model inference, not frontier models.
- Fictional courses / synthetic reviews; single-item-per-page bundling (can’t fully separate features within a page — addressed partly by Run 3).
- 9 dropped trials (run 2, 0.9%) and 4 (run 3, 1.9%) with sensitivity bounds.
- Budget-bounded sample ($54.57 of $100 cap).

8. Conclusion

- The redesign removed dominance; balance comes from models disagreeing with each other. Run 3’s single-variable test (§5.5) supports H1: rating was the binding constraint for the middle models, while Artistry’s credentials still anchor first place. Future work: human baseline arm, frontier models, Creative-bundle separating test.

9. Appendices

- A: full feature manifest (`features.yaml`). B: model × page win table. C: failure/retry log summary. D: cost ledger + provider statements. E: data dictionary (`results/README.md`). F: demo video link + live site URL.