71M ENGINES

	1800 rpm	2100 rpm	2300 rpm
Lubrication System			
Lubricating oil pressure (psi):			
Normal	38-60	40-60	40-60
Minimum for safe operation	27	30	30
*Lubricating oil temperature (degrees F.):			
Normal	200-225	200-225	200-225
Air System			
Air box pressure (inches mercury) - min. at full load:			
At zero exhaust back pressure:			
4-71M engine	4.0	5.8	7.2
6-71M engine	4.8	6.8	8.4
At max. full-load exhaust back pressure:			
4-71M engine	7.2	10.2	11.6
6-71M engine	8.0	11.2	12.8
Air inlet restriction (inches water) - full-load speed, max.:			
Dirty air cleaner (oil bath or dry)	25.0	25.0	25.0
Clean air cleaner (with pre-cleaner) (oil bath or dry)	13.4	15.9	17.5
Clean air cleaner (less pre-cleaner) (dry)	9.1	11.5	12.5
Crankcase pressure (inches water) - max.:			
4-71M engine	2.5	2.8	2.8
6-71M engine	2.8	3.1	3.1
Exhaust back pressure (inches mercury) - max.:			
Full load	4.0	5.5	5.5
No load	2.8	4.0	4.0
Fuel System			
Fuel pressure at inlet manifold (psi):			
Normal (.080" orifice)	45-70	45-70	45-70
Fuel spill (gpm) - min. at no load:			
(.080" orifice)	0.9	0.9	0.9
Fuel pump suction at pump inlet (inches mercury) - max.:			
Clean system	6.0	6.0	6.0
Dirty system	12.0	12.0	12.0
Cooling System			
Coolant temperature (degrees F.) - normal	160-185	160-185	160-185
Raw water pump:			
Inlet restriction (inches mercury) - max.:			
4-71M engine	# 5.0	# 5.0	5.0
6-71M engine	# 5.0	# 5.0	5.0
Outlet pressure (psi) - max.	#10.0	#10.0	10.0
Keel cooler pressure drop (psi) maximum through system:			
4-71M engine	# 5.0	# 5.0	5.0
6-71M engine	# 6.0	# 6.0	6.0
Compression			
Compression pressure (psi at sea level):			
Average - new engine at 600 rpm	440		
Minimum at 600 rpm	390		

*The lubricating oil temperature range is based on the temperature measurement in the oil pan at the oil pump When measuring the oil temperature at the cylinder block oil gallery, it will be approximately 10° lower.
#Maximum when this is full-load speed of engine.

© 1974 General Mo