




602201.40.AL.02.0

## Alder 400

Designed by

NAVA + AROSIO

400mm height bollard, for outdoor installation, 360° light distribution, phospho-chromatised and polyester powder coated die-cast aluminum head and extruded pole. Tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 24 x CREE "XH-G" LED. IP66 rating.



## Light Source Technical Data

|                     |                                                           |
|---------------------|-----------------------------------------------------------|
| <b>Wattage</b>      | 20W                                                       |
| <b>CCT</b>          | 4000K                                                     |
| <b>Beam Angle</b>   | 360°                                                      |
| <b>Lumens</b>       | 1650                                                      |
| <b>Finish</b>       | RAL7016                                                   |
| <b>Dimming</b>      | ON/OFF                                                    |
| <b>IP Rating</b>    | IP66                                                      |
| <b>IK Rating</b>    | IK09                                                      |
| <b>Coating</b>      | Polyester powder coating with phosphocromating pre-finish |
| <b>Light Source</b> | NR. 24 x CREE "XH-G" LED                                  |
| <b>Screws</b>       | Stainless steel                                           |
| <b>Transformer</b>  | Electronic power supply 220/240V 50/60Hz built-in         |
| <b>Gasket</b>       | Silicone rubber                                           |
| <b>Glass</b>        | Tempered                                                  |
| <b>Cable Gland</b>  | PG11                                                      |
| <b>Power Cable</b>  | 1,5 meters power cable included                           |
| <b>Gross Weight</b> | 3,00 Kg                                                   |

## Technical Feature



## Integrated Accessories

Built-in accessories to be requested when ordering

example 602201.40.AL.02.0.HC

602201.40.AL.02.0. \_ \_



.00

NO ACCESSORY

No accessory

## Accessories not included

Accessories to be ordered separately



AC065

ANCHORAGE UNIT FOR ALDER SERIES

## Gallery

