




602202.30.AL.02.0

Alder 800

Designed by

NAVA + AROSIO

800mm height bollard, for outdoor installation, 360° light distribution, phospho-chromatised and polyester powder coated die-cast aluminum head and extruded pole. Tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 24 x CREE "XH-G" LED. IP66 rating.



Light Source Technical Data

Wattage	20W
CCT	3000K
Beam Angle	360°
Lumens	1600
Finish	RAL7016
Dimming	ON/OFF
IP Rating	IP66
IK Rating	IK09
Coating	Polyester powder coating with phosphocromating pre-finish
Light Source	NR. 24 x CREE "XH-G" LED
Screws	Stainless steel
Transformer	Electronic power supply 220/240V 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Cable Gland	PG11
Power Cable	1,5 meters power cable included
Gross Weight	4,30 Kg

Technical Feature



Integrated Accessories

Built-in accessories to be requested when ordering

example 602202.30.AL.02.0.HC

602202.30.AL.02.0. _ _



.00

NO ACCESSORY

No accessory

Accessories not included

Accessories to be ordered separately



AC065

ANCHORAGE UNIT FOR ALDER SERIES

Gallery

