




601501.30.AL.03.0

Promenade Round 01

705mm height bollard, round shape, for outdoor surface installation, 360° downward light emission, phospho-chromatised and polyester powder coated extruded aluminum body and die-cast aluminium cover. Polycarbonate Fresnel diffuser, moulded silicone gasket and stainless steel screws. Anchorage flange with threaded bolts included. Built-in LED driver 220-240V 50-60Hz, with 1 x COB CREE "CXB 1520" LED. IP66 rating.



Light Source Technical Data

Wattage	26W
CCT	3000K
Beam Angle	360°
Lumens	2900
Finish	RAL9005
Dimming	ON/OFF
IP Rating	IP66
IK Rating	IK10
Coating	Polyester powder coating with phosphocromating pre-finish
Light Source	NR. 1 COB CREE "CXB 1520" LED
Screws	Stainless steel
Transformer	Electronic power supply 220/240V 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Cable Gland	M16 rubber grommet
Power Cable	not included
Gross Weight	6,50 Kg

Technical Feature



Integrated Accessories

Built-in accessories to be requested when ordering

example 601501.30.AL.03.0.HC

601501.30.AL.03.0. _ _



.00

NO ACCESSORY

No accessory

Accessories not included

Accessories to be ordered separately



AC053

BASE PLATE

Gallery

