



601710.40.HB.03.0

## Sector 1000 02

1000mm height bollard, round shape, for outdoor surface installation, 2 light windows, phospho-chromatised and polyester powder coated extruded copper-free aluminium body, opaline tempered glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with NR. 1 x CREE XHP70 LED. IP66 rating.



## Light Source Technical Data

|                     |                                                   |
|---------------------|---------------------------------------------------|
| <b>Wattage</b>      | 12W                                               |
| <b>CCT</b>          | 4000K                                             |
| <b>Beam Angle</b>   | 90°+90°                                           |
| <b>Lumens</b>       | 1100                                              |
| <b>Finish</b>       | Matt Black                                        |
| <b>Dimming</b>      | ON/OFF                                            |
| <b>IP Rating</b>    | IP66                                              |
| <b>IK Rating</b>    | IK10                                              |
| <b>Light Source</b> | NR. 1 x CREE XHP70 LED                            |
| <b>Transformer</b>  | Electrical power supply 220/240V 50/60Hz built-in |
| <b>Gasket</b>       | Silicone rubber                                   |
| <b>Glass</b>        | Tempered                                          |
| <b>Power Cable</b>  | 1 meter included                                  |
| <b>Gross Weight</b> | 8,00 Kg                                           |

## Technical Feature



## Integrated Accessories

Built-in accessories to be requested when ordering

example 601710.40.HB.03.0.HC

601710.40.HB.03.0. \_ \_



.00

NO ACCESSORY

No accessory

## Accessories not included

Accessories to be ordered separately



AC053

BASE PLATE

## Gallery

