



SKU

: 202HW94024D0

Housing Material

: Aluminum Die Cast

Housing Colour

: White (RAL 9003)

Luminaire Dimension [mm]

: Ø80x89mm

Cut-Out [mm]

: Ø75mm

Optic

: Reflector

Reflector Colour

: Specular Aluminium

Beam Angle [deg]

: 24°

LED Power [W]

: 7W

System Power [W]

: 8.5W

Luminous Flux [lm]

: 810lm

System Efficiency [lm/W]

: 95lm/W

Light Source

: 940

CCT [K]

: 4000K

CRI [Ra]

: 90

Chromaticity Tolerance

: 3 MacAdam

Mains Voltage [VAc]

: 220-240V / 50-60Hz

Power Supply

: DALI

Nominal Current [mA]

: 200mA

Forward Voltage [V]

: 34V

Ambient Temperature [degC]

: 35°C

Ingress Protection	: IP44/IP43
Light Source Energy Class	: E
Light Source Identifier	: BXRE-40G08FH-E-83
Lifetime/Failure Rate [h]	: 50000h
Electrical Safety Class	: Class II
Net Weight [Kg]	: 0.31Kg
Certificates/Declarations	: CE/UKCA
Warranty [Y]	: 5Y

All rated values @ ambient temperature of 25° C. Electric and photometric values are initially subject to a tolerance of +/- 10%. Tolerance of color temperature +/- 150K.
Technical data can change without prior notice.