



|                            |                      |
|----------------------------|----------------------|
| SKU                        | : 202HW94040D0       |
| Housing Material           | : Aluminum Die Cast  |
| Housing Colour             | : White (RAL 9003)   |
| Luminaire Dimension [mm]   | : Ø80x89mm           |
| Cut-Out [mm]               | : Ø75mm              |
| Optic                      | : Reflector          |
| Reflector Colour           | : Specular Aluminium |
| Beam Angle [deg]           | : 40°                |
| LED Power [W]              | : 7W                 |
| System Power [W]           | : 8.5W               |
| Luminous Flux [lm]         | : 810lm              |
| System Efficiency [lm/W]   | : 95lm/W             |
| Light Source               | : 940                |
| CCT [K]                    | : 4000K              |
| CRI [Ra]                   | : 90                 |
| Chromaticity Tolerance     | : 3 MacAdam          |
| Mains Voltage [VAc]        | : 220-240V / 50-60Hz |
| Power Supply               | : DALI               |
| Nominal Current [mA]       | : 200mA              |
| Forward Voltage [V]        | : 34V                |
| Ambient Temperature [degC] | : 35°C               |

|                           |                     |
|---------------------------|---------------------|
| Ingress Protection        | : IP44/IP43         |
| Light Source Energy Class | : E                 |
| Light Source Identifier   | : BXRE-40G08FH-E-83 |
| Lifetime/Failure Rate [h] | : 50000h            |
| Electrical Safety Class   | : Class II          |
| Net Weight [Kg]           | : 0.31Kg            |
| Certificates/Declarations | : CE/UKCA           |
| Warranty [Y]              | : 5Y                |

All rated values @ ambient temperature of 25° C. Electric and photometric values are initially subject to a tolerance of +/- 10%. Tolerance of color temperature +/- 150K.  
Technical data can change without prior notice.