



|                            |
|----------------------------|
| SKU                        |
| Housing Material           |
| Housing Colour             |
| Luminaire Dimension [mm]   |
| Cut-Out [mm]               |
| Optic                      |
| Reflector Colour           |
| Beam Angle [deg]           |
| LED Power [W]              |
| System Power [W]           |
| Luminous Flux [lm]         |
| System Efficiency [lm/W]   |
| Light Source               |
| CCT [K]                    |
| CRI [Ra]                   |
| Chromaticity Tolerance     |
| Mains Voltage [VAc]        |
| Power Supply               |
| Nominal Current [mA]       |
| Forward Voltage [V]        |
| Ambient Temperature [degC] |

|                      |
|----------------------|
| : 202IB93024F0       |
| : Aluminum Die Cast  |
| : Black (RAL 9005)   |
| : Ø80x89mm           |
| : Ø75mm              |
| : Reflector          |
| : Specular Aluminium |
| : 24°                |
| : 9W                 |
| : 10.5W              |
| : 1000lm             |
| : 95lm/W             |
| : 930                |
| : 3000K              |
| : 90                 |
| : 3 MacAdam          |
| : 220-240V / 50-60Hz |
| : on/off             |
| : 250mA              |
| : 36V                |
| : 35°C               |

|                           |                     |
|---------------------------|---------------------|
| Ingress Protection        | : IP44/IP43         |
| Light Source Energy Class | : E                 |
| Light Source Identifier   | : BXRE-30G08FH-E-83 |
| Lifetime/Failure Rate [h] | : 50000h            |
| Electrical Safety Class   | : Class II          |
| Net Weight [Kg]           | : 0.31Kg            |
| Certificates/Declarations | : CE/UKCA           |
| Warranty [Y]              | : 5Y                |

All rated values @ ambient temperature of 25° C. Electric and photometric values are initially subject to a tolerance of +/- 10%. Tolerance of color temperature +/- 150K.  
Technical data can change without prior notice.