




Inground Radius - R0000

Outdoor

IngroundR E EOP H100 R0000 L0505 / FL56/Nx G5 04W 922 / OR.T1x

|                   |                                                                                                                                       |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| CCT               | 2200K                                                                                                                                 |
| CRI               | CRI 90                                                                                                                                |
| COLOR CONSISTENCY | 3-Step MacAdam                                                                                                                        |
| LUMINOUS FLUX     | Luminaire: 104 Lm<br>Light Source: 227 Lm                                                                                             |
| EFFICACY          | Luminaire: 43 Lm/W<br>Light Source: 95 Lm/W                                                                                           |
| LIFETIME          | L90B10 > 60.000h                                                                                                                      |
| VOLTAGE           | 24VDC                                                                                                                                 |
| LUMINAIRE POWER   | 2.4 W                                                                                                                                 |
| CONTROL           | Dimmable                                                                                                                              |
| COVER             | Opal Encapsulation ( EOP )                                                                                                            |
| HOUSING           | Stainless Steel ( Marine Grande 316L )                                                                                                |
| IP CLASS          | IP67                                                                                                                                  |
| IK RATE           | IK10                                                                                                                                  |
| DIMENSIONS        | Height: 102 mm ( 4 in )<br>Radius: R0000 mm<br>Length: L0505 mm<br>Width: 33 mm ( 1,3 in ) Light Area<br>Width: 73 mm ( 2,9 in ) Base |
| SEGMENT           | End<br>Endcap at the end only<br>Input connector only, no output wire                                                                 |



# Product Code Explanation

---

IngroundR E EOP H100 R0000 L0505 / FL56/Nx G5 04W 922 / OR.T1x

|         |                    |                      |
|---------|--------------------|----------------------|
| E       | End                | Segment type         |
| EOP     | Opal Encapsulation | Cover type           |
| H100    | 102 mm             | Height, mm           |
| R0000   | R0000, mm          | Radius, mm           |
| L0505   | L0505, mm          | Length, mm           |
| FL56/Nx | FL56/Nx            | LED strip model      |
| G5      | G5                 | LED strip generation |
| 04W     | 04W (rounded)      | Wattage, W/m         |
| 9       | CRI90              | CRI                  |
| 22      | 2200K              | CCT                  |