




Inground Radius - R1975

Outdoor

IngroundR E EOP H100 R1975 L0385 / FL56/Nx G5 09W T927 / OR.T1x




|                   |                                              |
|-------------------|----------------------------------------------|
| CCT               | 2700K                                        |
| CRI               | CRI 90                                       |
| COLOR CONSISTENCY | 3-Step MacAdam                               |
| LUMINOUS FLUX     | Luminaire: 235 Lm<br>Light Source: 512 Lm    |
| EFFICACY          | Luminaire: 65 Lm/W<br>Light Source: 142 Lm/W |
| LIFETIME          | L90B10 > 60.000h                             |

|                 |          |
|-----------------|----------|
| VOLTAGE         | 24VDC    |
| LUMINAIRE POWER | 3.6 W    |
| CONTROL         | Dimmable |

|          |                                        |
|----------|----------------------------------------|
| COVER    | Opal Encapsulation ( EOP )             |
| HOUSING  | Stainless Steel ( Marine Grande 316L ) |
| IP CLASS | IP67                                   |
| IK RATE  | IK10                                   |

|            |                                                                                                                                       |
|------------|---------------------------------------------------------------------------------------------------------------------------------------|
| DIMENSIONS | Height: 102 mm ( 4 in )<br>Radius: R1975 mm<br>Length: L0385 mm<br>Width: 33 mm ( 1,3 in ) Light Area<br>Width: 73 mm ( 2,9 in ) Base |
|------------|---------------------------------------------------------------------------------------------------------------------------------------|

|         |                                                                       |
|---------|-----------------------------------------------------------------------|
| SEGMENT | End<br>Endcap at the end only<br>Input connector only, no output wire |
|---------|-----------------------------------------------------------------------|



# Product Code Explanation

---

IngroundR E EOP H100 R1975 L0385 / FL56/Nx G5 09W T927 / OR.T1x

|         |                    |                      |
|---------|--------------------|----------------------|
| E       | End                | Segment type         |
| EOP     | Opal Encapsulation | Cover type           |
| H100    | 102 mm             | Height, mm           |
| R1975   | R1975, mm          | Radius, mm           |
| L0385   | L0385, mm          | Length, mm           |
| FL56/Nx | FL56/Nx            | LED strip model      |
| G5      | G5                 | LED strip generation |
| 09W     | 09W (rounded)      | Wattage, W/m         |
| T9      | CRI90              | CRI                  |
| 27      | 2700K              | CCT                  |

Possible allowed deviation of optical and electrical values are  $\pm 15\%$ . Allowed measurement uncertainty  $\pm 7\%$ .  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.