




Inground Radius - R2950

Outdoor

IngroundR E EOP H100 R2950 L0384 / FL56/Nx G5 09W T927 / OR.T1x

CCT	2700K
CRI	CRI 90
COLOR CONSISTENCY	3-Step MacAdam
LUMINOUS FLUX	Luminaire: 235 Lm Light Source: 512 Lm
EFFICACY	Luminaire: 65 Lm/W Light Source: 142 Lm/W
LIFETIME	L90B10 > 60.000h
VOLTAGE	24VDC
LUMINAIRE POWER	3.6 W
CONTROL	Dimmable
COVER	Opal Encapsulation (EOP)
HOUSING	Stainless Steel (Marine Grande 316L)
IP CLASS	IP67
IK RATE	IK10
DIMENSIONS	Height: 102 mm (4 in) Radius: R2950 mm Length: L0384 mm Width: 33 mm (1,3 in) Light Area Width: 73 mm (2,9 in) Base
SEGMENT	End Endcap at the end only Input connector only, no output wire



Product Code Explanation

IngroundR E EOP H100 R2950 L0384 / FL56/Nx G5 09W T927 / OR.T1x

E	End	Segment type
EOP	Opal Encapsulation	Cover type
H100	102 mm	Height, mm
R2950	R2950, mm	Radius, mm
L0384	L0384, mm	Length, mm
FL56/Nx	FL56/Nx	LED strip model
G5	G5	LED strip generation
09W	09W (rounded)	Wattage, W/m
T9	CRI90	CRI
27	2700K	CCT