



Inground Radius - R0515

Outdoor

IngroundR F EOP H100 R0515 L0393 / FL56/Nx G5 09W T930 / OR.T1x



|                   |                                                                                                                                       |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| CCT               | 3000K                                                                                                                                 |
| CRI               | CRI 90                                                                                                                                |
| COLOR CONSISTENCY | 3-Step MacAdam                                                                                                                        |
| LUMINOUS FLUX     | Luminaire: 247 Lm<br>Light Source: 538 Lm                                                                                             |
| EFFICACY          | Luminaire: 69 Lm/W<br>Light Source: 149 Lm/W                                                                                          |
| LIFETIME          | L90B10 > 60.000h                                                                                                                      |
| VOLTAGE           | 24VDC                                                                                                                                 |
| LUMINAIRE POWER   | 3.6 W                                                                                                                                 |
| CONTROL           | Dimmable                                                                                                                              |
| COVER             | Opal Encapsulation ( EOP )                                                                                                            |
| HOUSING           | Stainless Steel ( Marine Grande 316L )                                                                                                |
| IP CLASS          | IP67                                                                                                                                  |
| IK RATE           | IK10                                                                                                                                  |
| DIMENSIONS        | Height: 102 mm ( 4 in )<br>Radius: R0515 mm<br>Length: L0393 mm<br>Width: 33 mm ( 1,3 in ) Light Area<br>Width: 73 mm ( 2,9 in ) Base |
| SEGMENT           | Full<br>Endcaps on both ends<br>Input connector and output wire                                                                       |



# Product Code Explanation

---

IngroundR F EOP H100 R0515 L0393 / FL56/Nx G5 09W T930 / OR.T1x

|                |                    |                      |
|----------------|--------------------|----------------------|
| <b>F</b>       | Full               | Segment type         |
| <b>EOP</b>     | Opal Encapsulation | Cover type           |
| <b>H100</b>    | 102 mm             | Height, mm           |
| <b>R0515</b>   | R0515, mm          | Radius, mm           |
| <b>L0393</b>   | L0393, mm          | Length, mm           |
| <b>FL56/Nx</b> | FL56/Nx            | LED strip model      |
| <b>G5</b>      | G5                 | LED strip generation |
| <b>09W</b>     | 09W (rounded)      | Wattage, W/m         |
| <b>T9</b>      | CRI90              | CRI                  |
| <b>30</b>      | 3000K              | CCT                  |

Possible allowed deviation of optical and electrical values are  $\pm 15\%$ . Allowed measurement uncertainty  $\pm 7\%$ .  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.