




Inground Radius - R2950

Outdoor

IngroundR F EOP H100 R2950 L0384 / FL112/Nx.48V G5 09W T930 / OR.T1x



|                   |                                                                                                                                       |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| CCT               | 3000K                                                                                                                                 |
| CRI               | CRI 90                                                                                                                                |
| COLOR CONSISTENCY | 3-Step MacAdam                                                                                                                        |
| LUMINOUS FLUX     | Luminaire: 252 Lm<br>Light Source: 548 Lm                                                                                             |
| EFFICACY          | Luminaire: 70 Lm/W<br>Light Source: 152 Lm/W                                                                                          |
| LIFETIME          | L90B10 > 60.000h                                                                                                                      |
| VOLTAGE           | 48VDC                                                                                                                                 |
| LUMINAIRE POWER   | 3.6 W                                                                                                                                 |
| CONTROL           | Dimmable                                                                                                                              |
| COVER             | Opal Encapsulation ( EOP )                                                                                                            |
| HOUSING           | Stainless Steel ( Marine Grande 316L )                                                                                                |
| IP CLASS          | IP67                                                                                                                                  |
| IK RATE           | IK10                                                                                                                                  |
| DIMENSIONS        | Height: 102 mm ( 4 in )<br>Radius: R2950 mm<br>Length: L0384 mm<br>Width: 33 mm ( 1,3 in ) Light Area<br>Width: 73 mm ( 2,9 in ) Base |
| SEGMENT           | Full<br>Endcaps on both ends<br>Input connector and output wire                                                                       |



# Product Code Explanation

---

IngroundR F EOP H100 R2950 L0384 / FL112/Nx.48V G5 09W T930 / OR.T1x

|              |                    |                      |
|--------------|--------------------|----------------------|
| F            | Full               | Segment type         |
| EOP          | Opal Encapsulation | Cover type           |
| H100         | 102 mm             | Height, mm           |
| R2950        | R2950, mm          | Radius, mm           |
| L0384        | L0384, mm          | Length, mm           |
| FL112/Nx.48V | FL112/Nx.48V       | LED strip model      |
| G5           | G5                 | LED strip generation |
| 09W          | 09W (rounded)      | Wattage, W/m         |
| T9           | CRI90              | CRI                  |
| 30           | 3000K              | CCT                  |

Possible allowed deviation of optical and electrical values are  $\pm 15\%$ . Allowed measurement uncertainty  $\pm 7\%$ .  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.