


DATASHEET



Inground Radius - R0272

Outdoor

IngroundR | EOP H100 R0272 L0404 / FL112/Nx.48V G5 09W 922 / OR.T1x



CCT	2200K
CRI	CRI 90
COLOR CONSISTENCY	3-Step MacAdam
LUMINOUS FLUX	Luminaire: 157 Lm Light Source: 341 Lm
EFFICACY	Luminaire: 44 Lm/W Light Source: 95 Lm/W
LIFETIME	L90B10 > 60.000h

VOLTAGE	48VDC
LUMINAIRE POWER	3.6 W
CONTROL	Dimmable

COVER	Opal Encapsulation (EOP)
HOUSING	Stainless Steel (Marine Grande 316L)
IP CLASS	IP67
IK RATE	IK10

DIMENSIONS	Height: 102 mm (4 in) Radius: R0272 mm Length: L0404 mm Width: 33 mm (1,3 in) Light Area Width: 73 mm (2,9 in) Base
------------	---

SEGMENT	Individual Endcaps on both ends Input connector only, no output wire
---------	--



Product Code Explanation

IngroundR I EOP H100 R0272 L0404 / FL112/Nx.48V G5 09W 922 / OR.T1x

I	Individual	Segment type
EOP	Opal Encapsulation	Cover type
H100	102 mm	Height, mm
R0272	R0272, mm	Radius, mm
L0404	L0404, mm	Length, mm
FL112/Nx.48V	FL112/Nx.48V	LED strip model
G5	G5	LED strip generation
09W	09W (rounded)	Wattage, W/m
9	CRI90	CRI
22	2200K	CCT