



Inground Radius - R0000

Outdoor

IngroundR M EOP H100 R0000 L1005 / FL56/Nx G5 09W T940 / OR.T1x



|                   |                                                                                                                                       |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| CCT               | 4000K                                                                                                                                 |
| CRI               | CRI 90                                                                                                                                |
| COLOR CONSISTENCY | 3-Step MacAdam                                                                                                                        |
| LUMINOUS FLUX     | Luminaire: 686 Lm<br>Light Source: 1491 Lm                                                                                            |
| EFFICACY          | Luminaire: 71 Lm/W<br>Light Source: 155 Lm/W                                                                                          |
| LIFETIME          | L90B10 > 60.000h                                                                                                                      |
| VOLTAGE           | 24VDC                                                                                                                                 |
| LUMINAIRE POWER   | 9.6 W                                                                                                                                 |
| CONTROL           | Dimmable                                                                                                                              |
| COVER             | Opal Encapsulation ( EOP )                                                                                                            |
| HOUSING           | Stainless Steel ( Marine Grande 316L )                                                                                                |
| IP CLASS          | IP67                                                                                                                                  |
| IK RATE           | IK10                                                                                                                                  |
| DIMENSIONS        | Height: 102 mm ( 4 in )<br>Radius: R0000 mm<br>Length: L1005 mm<br>Width: 33 mm ( 1,3 in ) Light Area<br>Width: 73 mm ( 2,9 in ) Base |
| SEGMENT           | Middle<br>No endcaps<br>Input connector and output wire                                                                               |



# Product Code Explanation

---

IngroundR M EOP H100 R0000 L1005 / FL56/Nx G5 09W T940 / OR.T1x

|         |                    |                      |
|---------|--------------------|----------------------|
| M       | Middle             | Segment type         |
| EOP     | Opal Encapsulation | Cover type           |
| H100    | 102 mm             | Height, mm           |
| R0000   | R0000, mm          | Radius, mm           |
| L1005   | L1005, mm          | Length, mm           |
| FL56/Nx | FL56/Nx            | LED strip model      |
| G5      | G5                 | LED strip generation |
| 09W     | 09W (rounded)      | Wattage, W/m         |
| T9      | CRI90              | CRI                  |
| 40      | 4000K              | CCT                  |