




602301.27.36.01.0

Coiny Bollard



Light Source Technical Data

Wattage	8W
CCT	2700K
Beam Angle	36°
Lumens	371
Finish	RAL9006
Dimming	ON/OFF
IP Rating	IP66
IK Rating	IK08
Coating	Polyester powder coating with phosphocromating pre-finish
Light Source	1 x LUMENS "EDC 38C" COB LED
Screws	Stainless steel
Transformer	Electrical power supply 220/240V 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Power Cable	1 mt. power cable included
Gross Weight	1,20 Kg

Technical Feature



Integrated Accessories

Built-in accessories to be requested when ordering

example 602301.27.36.01.0.HC

602301.27.36.01.0. _ _



.00

NO ACCESSORY

No accessory

Accessories not included

Accessories to be ordered separately




AC044

SPIKE



AC111


VISOR



AC112

PIPE L 500 mm + BASE

Extension pipe length 500 mm made in anodized aluminum with phospho-chromatised and polyester powder coating; complete with fixing base.



AC113

PIPE L 1000 mm + BASE

Extension pipe length 1.000 mm made in anodized aluminum with phospho-chromatised and polyester powder coating; complete with fixing base.

Gallery

