





FL112/DX G5 14W T940

White LED strips



LIGHT TYPE	White
LED Qty	112 LEDs/m
CCT	4000K
CRI	CRI90
COLOR CONSISTENCY	3-Step MacAdam
PHOTOMETRIC	120° beam angle
LUMINOUS FLUX	2049 Lm/m (625 Lm/ft)
EFFICACY	142 Lm/W
LIFETIME	L70B10 > 50.000h
CONTROL	Dimmable
VOLTAGE	24 VDC
WATTAGE	14.4 W/m (4.39 W/ft)
CUTTING STEP	6,25 cm (2,46 in)
MAX RUN	5.5 m (18 ft)
PACKING	10 m, 50 m or customized length per reel
DIMENSIONS	Width: 8mm; Height: 1.62mm
TEMPERATURE	Tc max 75°C (167°F)
OPERATING TEMP.	-25°C...+50°C (-13°F...122°F)
STORAGE TEMP.	-25°C...+80°C (-13°F...176°F)

MADE IN EUROPE5 YEAR WARRANTY3 STEP MACADAM

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.