




FL112/NX.48V G5 19W T940

White LED strips



|                   |                       |
|-------------------|-----------------------|
| LIGHT TYPE        | White                 |
| LED Qty           | 112 LEDs/m            |
| CCT               | 4000K                 |
| CRI               | CRI90                 |
| COLOR CONSISTENCY | 3-Step MacAdam        |
| PHOTOMETRIC       | 120° beam angle       |
| LUMINOUS FLUX     | 2982 Lm/m (909 Lm/ft) |
| EFFICACY          | 155 Lm/W              |
| LIFETIME          | L90B10 > 60.000h      |

|         |          |
|---------|----------|
| CONTROL | Dimmable |
|---------|----------|

|         |                      |
|---------|----------------------|
| VOLTAGE | 48 VDC               |
| WATTAGE | 19.2 W/m (5.85 W/ft) |

|              |                                          |
|--------------|------------------------------------------|
| CUTTING STEP | 12,5 cm (4,92 in)                        |
| MAX RUN      | 14 m (45.9 ft)                           |
| PACKING      | 10 m, 50 m or customized length per reel |
| DIMENSIONS   | Width: 8mm; Height: 1.58mm               |

|                 |                                 |
|-----------------|---------------------------------|
| TEMPERATURE     | Tc max 75°C ( 167°F )           |
| OPERATING TEMP. | -25°C...+50°C ( -13°F...122°F ) |
| STORAGE TEMP.   | -25°C...+80°C ( -13°F...176°F ) |



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.