



FL175/DX G5 19W T930

White LED strips



LIGHT TYPE	White
LED Qty	175 LEDs/m
CCT	3000K
CRI	CRI90
COLOR CONSISTENCY	3-Step MacAdam
PHOTOMETRIC	120° beam angle
LUMINOUS FLUX	2677 Lm/m (816 Lm/ft)
EFFICACY	139 Lm/W
LIFETIME	L70B10 > 50.000h
CONTROL	Dimmable
VOLTAGE	24 VDC
WATTAGE	19.2 W/m (5.85 W/ft)
CUTTING STEP	4 cm (1,57 in)
MAX RUN	1 m (3.3 ft)
PACKING	10 m, 50 m or customized length per reel
DIMENSIONS	Width: 5mm; Height: 1.8mm
TEMPERATURE	Tc max 75°C (167°F)
OPERATING TEMP.	-25°C...+50°C (-13°F...122°F)
STORAGE TEMP.	-25°C...+80°C (-13°F...176°F)

MADE IN EUROPE5 YEAR WARRANTY3 STEP MACADAM

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.