



Inground Radius - R1000

Outdoor

IngroundR E EOP H100 R1000 L0387 / RGB48/Nx G5 07W RGB\_RGB\_ / OR.T1x




|                   |                                                                                               |
|-------------------|-----------------------------------------------------------------------------------------------|
| CCT               | RGB                                                                                           |
| CRI               | RGB                                                                                           |
| COLOR CONSISTENCY | 3-Step MacAdam                                                                                |
| LUMINOUS FLUX     | Luminaire: 55 Lm ( R: 11, G: 36, B: 7 Lm )<br>Light Source: 119 Lm ( R: 24, G: 78, B: 16 Lm ) |
| EFFICACY          | Luminaire: 20 Lm/W<br>Light Source: 44 Lm/W                                                   |
| LIFETIME          | L90B10 > 60.000h                                                                              |

|                 |          |
|-----------------|----------|
| VOLTAGE         | 24VDC    |
| LUMINAIRE POWER | 2.7 W    |
| CONTROL         | Dimmable |

|          |                                        |
|----------|----------------------------------------|
| COVER    | Opal Encapsulation ( EOP )             |
| HOUSING  | Stainless Steel ( Marine Grande 316L ) |
| IP CLASS | IP67                                   |
| IK RATE  | IK10                                   |

|            |                                                                                                                                       |
|------------|---------------------------------------------------------------------------------------------------------------------------------------|
| DIMENSIONS | Height: 102 mm ( 4 in )<br>Radius: R1000 mm<br>Length: L0387 mm<br>Width: 33 mm ( 1,3 in ) Light Area<br>Width: 73 mm ( 2,9 in ) Base |
|------------|---------------------------------------------------------------------------------------------------------------------------------------|

|         |                                                                       |
|---------|-----------------------------------------------------------------------|
| SEGMENT | End<br>Endcap at the end only<br>Input connector only, no output wire |
|---------|-----------------------------------------------------------------------|



# Product Code Explanation

---

IngroundR E EOP H100 R1000 L0387 / RGB48/Nx G5 07W RGB\_RGB\_ / OR.T1x

|          |                    |                      |
|----------|--------------------|----------------------|
| E        | End                | Segment type         |
| EOP      | Opal Encapsulation | Cover type           |
| H100     | 102 mm             | Height, mm           |
| R1000    | R1000, mm          | Radius, mm           |
| L0387    | L0387, mm          | Length, mm           |
| RGB48/Nx | RGB48/Nx           | LED strip model      |
| G5       | G5                 | LED strip generation |
| 07W      | 07W (rounded)      | Wattage, W/m         |
| RGB_     | RGB_               | CRI                  |
| RGB_     | RGB_               | CCT                  |

Possible allowed deviation of optical and electrical values are  $\pm 15\%$ . Allowed measurement uncertainty  $\pm 7\%$ .  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.