



Inground Radius - R0000

Outdoor

IngroundR F EOP H100 R0000 L0505 / RGBW48/NN G5 09W RGB\_RGB\_T940 / OR.T1x

|                   |                                                                                                                                       |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| CCT               | RGB + 4000K                                                                                                                           |
| CRI               | RGB + CRI90 (White)                                                                                                                   |
| COLOR CONSISTENCY | 3-Step MacAdam                                                                                                                        |
| LUMINOUS FLUX     | Luminaire: 148 Lm ( R: 15, G: 48, B: 10, W: 75 Lm )<br>Light Source: 322 Lm ( R: 33, G: 104, B: 22, W: 164 Lm )                       |
| EFFICACY          | Luminaire: 31 Lm/W<br>Light Source: 67 Lm/W                                                                                           |
| LIFETIME          | L90B10 > 60.000h                                                                                                                      |
| VOLTAGE           | 24VDC                                                                                                                                 |
| LUMINAIRE POWER   | 4.8 W                                                                                                                                 |
| CONTROL           | Dimmable                                                                                                                              |
| COVER             | Opal Encapsulation ( EOP )                                                                                                            |
| HOUSING           | Stainless Steel ( Marine Grande 316L )                                                                                                |
| IP CLASS          | IP67                                                                                                                                  |
| IK RATE           | IK10                                                                                                                                  |
| DIMENSIONS        | Height: 102 mm ( 4 in )<br>Radius: R0000 mm<br>Length: L0505 mm<br>Width: 33 mm ( 1,3 in ) Light Area<br>Width: 73 mm ( 2,9 in ) Base |
| SEGMENT           | Full<br>Endcaps on both ends<br>Input connector and output wire                                                                       |



# Product Code Explanation

---

IngroundR F EOP H100 R0000 L0505 / RGBW48/NN G5 09W RGB\_RGB\_T940 / OR.T1x

|                  |                    |                      |
|------------------|--------------------|----------------------|
| <b>F</b>         | Full               | Segment type         |
| <b>EOP</b>       | Opal Encapsulation | Cover type           |
| <b>H100</b>      | 102 mm             | Height, mm           |
| <b>R0000</b>     | R0000, mm          | Radius, mm           |
| <b>L0505</b>     | L0505, mm          | Length, mm           |
| <b>RGBW48/NN</b> | RGBW48/NN          | LED strip model      |
| <b>G5</b>        | G5                 | LED strip generation |
| <b>09W</b>       | 09W (rounded)      | Wattage, W/m         |
| <b>RGB_</b>      | RGB_               | LED 1 CRI            |
| <b>RGB_</b>      | RGB_               | LED 1 CCT            |
| <b>T9</b>        | CRI90              | LED 2 CRI            |
| <b>40</b>        | 4000K              | LED 2 CCT            |