



Inground Radius - R0000

Outdoor

IngroundR M EOP H100 R0000 L0505 / FL112/Nx.48V G5 09W T940 / OR.T1x

CCT	4000K
CRI	CRI 90
COLOR CONSISTENCY	3-Step MacAdam
LUMINOUS FLUX	Luminaire: 349 Lm Light Source: 759 Lm
EFFICACY	Luminaire: 73 Lm/W Light Source: 158 Lm/W
LIFETIME	L90B10 > 60.000h
VOLTAGE	48VDC
LUMINAIRE POWER	4.8 W
CONTROL	Dimmable
COVER	Opal Encapsulation (EOP)
HOUSING	Stainless Steel (Marine Grande 316L)
IP CLASS	IP67
IK RATE	IK10
DIMENSIONS	Height: 102 mm (4 in) Radius: R0000 mm Length: L0505 mm Width: 33 mm (1,3 in) Light Area Width: 73 mm (2,9 in) Base
SEGMENT	Middle No endcaps Input connector and output wire



Product Code Explanation

IngroundR M EOP H100 R0000 L0505 / FL112/Nx.48V G5 09W T940 / OR.T1x

M	Middle	Segment type
EOP	Opal Encapsulation	Cover type
H100	102 mm	Height, mm
R0000	R0000, mm	Radius, mm
L0505	L0505, mm	Length, mm
FL112/Nx.48V	FL112/Nx.48V	LED strip model
G5	G5	LED strip generation
09W	09W (rounded)	Wattage, W/m
T9	CRI90	CRI
40	4000K	CCT

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.