



Inground Radius - R0000

Outdoor

IngroundR M EOP H100 R0000 L1005 / FL56/Nx G5 02W T930 / OR.T1x

CCT	3000K
CRI	CRI 90
COLOR CONSISTENCY	3-Step MacAdam
LUMINOUS FLUX	Luminaire: 169 Lm Light Source: 368 Lm
EFFICACY	Luminaire: 70 Lm/W Light Source: 153 Lm/W
LIFETIME	L90B10 > 60.000h
VOLTAGE	24VDC
LUMINAIRE POWER	2.4 W
CONTROL	Dimmable
COVER	Opal Encapsulation (EOP)
HOUSING	Stainless Steel (Marine Grande 316L)
IP CLASS	IP67
IK RATE	IK10
DIMENSIONS	Height: 102 mm (4 in) Radius: R0000 mm Length: L1005 mm Width: 33 mm (1,3 in) Light Area Width: 73 mm (2,9 in) Base
SEGMENT	Middle No endcaps Input connector and output wire



Product Code Explanation

IngroundR M EOP H100 R0000 L1005 / FL56/Nx G5 02W T930 / OR.T1x

M	Middle	Segment type
EOP	Opal Encapsulation	Cover type
H100	102 mm	Height, mm
R0000	R0000, mm	Radius, mm
L1005	L1005, mm	Length, mm
FL56/Nx	FL56/Nx	LED strip model
G5	G5	LED strip generation
02W	02W (rounded)	Wattage, W/m
T9	CRI90	CRI
30	3000K	CCT

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.