




Inground Radius - R1000

Outdoor

IngroundR M EOP H100 R1000 L0387 / FL112/Nx.48V G5 04W T930 / OR.T1x



CCT	3000K
CRI	CRI 90
COLOR CONSISTENCY	3-Step MacAdam
LUMINOUS FLUX	Luminaire: 127 Lm Light Source: 276 Lm
EFFICACY	Luminaire: 71 Lm/W Light Source: 154 Lm/W
LIFETIME	L90B10 > 60.000h
VOLTAGE	48VDC
LUMINAIRE POWER	1.8 W
CONTROL	Dimmable
COVER	Opal Encapsulation (EOP)
HOUSING	Stainless Steel (Marine Grande 316L)
IP CLASS	IP67
IK RATE	IK10
DIMENSIONS	Height: 102 mm (4 in) Radius: R1000 mm Length: L0387 mm Width: 33 mm (1,3 in) Light Area Width: 73 mm (2,9 in) Base
SEGMENT	Middle No endcaps Input connector and output wire



Product Code Explanation

IngroundR M EOP H100 R1000 L0387 / FL112/Nx.48V G5 04W T930 / OR.T1x

M	Middle	Segment type
EOP	Opal Encapsulation	Cover type
H100	102 mm	Height, mm
R1000	R1000, mm	Radius, mm
L0387	L0387, mm	Length, mm
FL112/Nx.48V	FL112/Nx.48V	LED strip model
G5	G5	LED strip generation
04W	04W (rounded)	Wattage, W/m
T9	CRI90	CRI
30	3000K	CCT