



Inground Radius - R0272

Outdoor

IngroundR S EOP H100 R0272 L0404 / FL56/Nx G5 04W T927 / OR.T1x



CCT	2700K
CRI	CRI 90
COLOR CONSISTENCY	3-Step MacAdam
LUMINOUS FLUX	Luminaire: 120 Lm Light Source: 261 Lm
EFFICACY	Luminaire: 67 Lm/W Light Source: 145 Lm/W
LIFETIME	L90B10 > 60.000h
VOLTAGE	24VDC
LUMINAIRE POWER	1.8 W
CONTROL	Dimmable
COVER	Opal Encapsulation (EOP)
HOUSING	Stainless Steel (Marine Grande 316L)
IP CLASS	IP67
IK RATE	IK10
DIMENSIONS	Height: 102 mm (4 in) Radius: R0272 mm Length: L0404 mm Width: 33 mm (1,3 in) Light Area Width: 73 mm (2,9 in) Base
SEGMENT	Start Endcaps at the start only Input connector and output wire



Product Code Explanation

IngroundR S EOP H100 R0272 L0404 / FL56/Nx G5 04W T927 / OR.T1x

S	Start	Segment type
EOP	Opal Encapsulation	Cover type
H100	102 mm	Height, mm
R0272	R0272, mm	Radius, mm
L0404	L0404, mm	Length, mm
FL56/Nx	FL56/Nx	LED strip model
G5	G5	LED strip generation
04W	04W (rounded)	Wattage, W/m
T9	CRI90	CRI
27	2700K	CCT