



601604.30.AS.02.1

## Periscope 02

500mm height "L-shape" bollard, for outdoor installation, one-side downward asymmetrical light distribution, phospho-chromatised and polyester powder coated extruded aluminum body. Tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with CREE "XP-G2" LED. IP65 rating.



## Light Source Technical Data

|                     |                                                           |
|---------------------|-----------------------------------------------------------|
| <b>Wattage</b>      | 14W                                                       |
| <b>CCT</b>          | 3000K                                                     |
| <b>Beam Angle</b>   | generic asymmetric                                        |
| <b>Lumens</b>       | 1610                                                      |
| <b>Finish</b>       | RAL7016                                                   |
| <b>Dimming</b>      | 1-10V                                                     |
| <b>IP Rating</b>    | IP65                                                      |
| <b>IK Rating</b>    | IK10                                                      |
| <b>Coating</b>      | Polyester powder coating with phosphocromating pre-finish |
| <b>Screws</b>       | Stainless steel                                           |
| <b>Transformer</b>  | Electronic power supply 220/240V 50/60Hz built-in         |
| <b>Gasket</b>       | Silicone rubber                                           |
| <b>Glass</b>        | Tempered                                                  |
| <b>Cable Gland</b>  | M16 rubber grommet                                        |
| <b>Power Cable</b>  | 0,5 mt. neoprene power cable included                     |
| <b>Gross Weight</b> | 4,50 Kg                                                   |

## Technical Feature



## Integrated Accessories

Built-in accessories to be requested when ordering

example 601604.30.AS.02.1.HC

601604.30.AS.02.1. \_ \_



.00

NO ACCESSORY

No accessory

## Gallery

