



SKU
Housing Material
Housing Colour
Luminaire Dimension [mm]
Cut-Out [mm]
Optic
Reflector Colour
Beam Angle [deg]
LED Power [W]
System Power [W]
Luminous Flux [lm]
System Efficiency [lm/W]
Light Source
CCT [K]
CRI [Ra]
Chromaticity Tolerance
Mains Voltage [VAc]
Power Supply
Nominal Current [mA]
Forward Voltage [V]
Ambient Temperature [degC]

: 202DW183055P0
: Aluminum Die Cast
: White (RAL 9003)
: Ø80x89mm
: Ø75mm
: Reflector
: Specular Aluminium
: 55°
: 8.5W
: 10W
: 650lm
: 65lm/W
: DTW
: 1800K-3000K Dim to Warm
: 90
: 3 MacAdam
: 220-240V / 50-60Hz
: Phase Cut
: 250mA
: 34V
: 35°C

Ingress Protection	: IP44/IP43
Lifetime/Failure Rate [h]	: 50000h
Electrical Safety Class	: Class II
Net Weight [Kg]	: 0.31Kg
Certificates/Declarations	: CE/UKCA
Warranty [Y]	: 5Y

All rated values @ ambient temperature of 25° C. Electric and photometric values are initially subject to a tolerance of +/- 10%. Tolerance of color temperature +/- 150K.
Technical data can change without prior notice.