



SKU	: 202IW92724P0
Housing Material	: Aluminum Die Cast
Housing Colour	: White (RAL 9003)
Luminaire Dimension [mm]	: Ø80x89mm
Cut-Out [mm]	: Ø75mm
Optic	: Reflector
Reflector Colour	: Specular Aluminium
Beam Angle [deg]	: 24°
LED Power [W]	: 9W
System Power [W]	: 10.5W
Luminous Flux [lm]	: 1000lm
System Efficiency [lm/W]	: 95lm/W
Light Source	: 927
CCT [K]	: 2700K
CRI [Ra]	: 90
Chromaticity Tolerance	: 3 MacAdam
Mains Voltage [VAc]	: 220-240V / 50-60Hz
Power Supply	: Phase Cut
Nominal Current [mA]	: 250mA
Forward Voltage [V]	: 36V
Ambient Temperature [degC]	: 35°C

Ingress Protection	: IP44/IP43
Light Source Energy Class	: E
Light Source Identifier	: BXRE-27G08FH-E-83
Lifetime/Failure Rate [h]	: 50000h
Electrical Safety Class	: Class II
Net Weight [Kg]	: 0.31Kg
Certificates/Declarations	: CE/UKCA
Warranty [Y]	: 5Y

All rated values @ ambient temperature of 25° C. Electric and photometric values are initially subject to a tolerance of +/- 10%. Tolerance of color temperature +/- 150K.
Technical data can change without prior notice.